

**BELGIUM'S GREENHOUSE GAS
INVENTORY (1990-2004)**

**National Inventory Report
submitted under the United Nations Framework Convention on
Climate Change**

April 2006

Prepared by:

Flemish Environment Agency (VMM)
Alfons Van de Maelestraat 96 9320 Erembodegem Belgium
Telephone +32 (0)53 72.66.52
Fax +32 (0)53 70.63.44
<http://www.vmm.be>
E-Mail: m.vandenhende@vmm.be and m.dheer@vmm.be

Flemish institute for technological research (Vito)
Boeretang 200 B-2400 Mol Belgium
Telephone + 32 (0)14 33 55 11
Fax + 32 (0)14 33 55 99
<http://www.Vito.be>
E-Mail: kristien.aernouts@Vito.be and kaat.jespers@vito.be

General Directorate for natural resources and environment (DGRNE)
Av. Princes de Liège 155100 Jambes Belgium
Telephone +32 (0) 81-33 51 84
Fax +32 (0) 81 33 51 22
<http://environnement.wallonie.be>
E-Mail: i.higuet@mrw.wallonie.be , ext.perrin@mrw.wallonie.be, a.guns@mrw.wallonie.be

Brussels Institute for the Management of the Environment (IBGE-BIM)
Gulledelle 100 1200 Brussel Belgium
Telephone +32 (0)2 775 7681
Fax +32 (0)2 775 76 21
<http://www.ibgebim.be>
E-Mail: msq@ibgebim.be and mga@ibgebim.be

Interregional Cell for the Environment (IRCEL)
Avenue des Arts/Kunstlaan 10-11 1210 Brussels
Telephone +32 (0)2 227 57 01
Fax +32 (0)2 227 56 99
<http://www.irceline.be>
E-Mail: derouane@irceline.be

Federal Public Service Health, Food Chain Safety and Environment
DG Environment - Climate Change Section
Place Victor Horta 40 Box 10
B-1060 Brussels
Belgium
Telephone +32 (0)2 524 95 29
Fax +32 (0)2 524 96 01
<http://www.klimaat.be>
E-Mail: etienne.hannon@health.fgov.be

TABLE OF CONTENT

National Inventory Report	i
Chapter 1: Introduction	6
1.1. Overview	6
1.2. Institutional arrangements and process of inventory preparation	6
1.3. Description of methodologies and data sources used	7
1.3.1. Flemish region	8
1.3.2. Walloon region	9
1.3.3. Brussels region	9
1.4. Key sources categories	9
1.5. QA/QC plan and related issues	13
1.6 Tier 1 uncertainty calculation	15
1.6.1. General approach.....	15
1.6.2. Comment by category	16
1.6.3. Results and discussion.....	21
Chapter 2: Trends in greenhouse gas emissions	23
2.1. Emission trends for aggregated greenhouse gas emissions	23
2.2. Emission trends by gas	25
2.3. Emission trends by source	27
2.3.1. Energy	28
2.3.2. Industrial processes	30
2.3.3. Agriculture	31
2.3.4. Waste.....	32
2.4. Emission trends for indirect greenhouse gases and SO₂	33
2.4.1. Nitrogen oxides (NO _x)	33
2.4.2. Carbon monoxide (CO).....	33
2.4.3. NMVOC	33
2.4.4. Sulphur dioxide (SO ₂)	33
Chapter 3: Energy	35
3.1 Overview	35
3.1.1 Energy	35
3.1.2 Industry.....	36
3.1.3 Transport	36
3.2 Methodological issues	36
3.2.1 Energy industries (category 1.A.1).....	38
3.2.2 Manufacturing industry and construction (category 1.A.2).....	40
3.2.3. Transport (category 1.A.3 and 1.A.5.b).....	43
3.2.4 Other sectors (category 1.A.4).....	44
3.2.5. Other (category 1.A.5.a and 1.A.5.b)	46
3.2.6. Fugitive emissions from fuels (category 1.B.1 and 1.B.2)	46
3.2.7. International bunkers (category Memo Items – International Bunkers).....	47
3.2.8. CO ₂ emissions from biomass.....	47
3.2.9. Non-energy use of fuels and related emissions (categories 1.A.2, 2.B and 2.G).....	47
3.3.Reference approach	49
3.4. Recalculations and planned improvements	55
3.4.1 Recalculations	55

3.4.2 Planned improvements	57
Chapter 4: Industrial processes	58
4.1. Overview.....	58
4.1.1. Description of the sector.....	58
4.1.2. Allocation of emissions	58
4.2. Methodological issues.....	58
4.2.1. Mineral products (category 2.A)	58
4.2.2. Chemical industry (category 2.B).....	60
4.2.3. Metal production (category 2.C)	61
4.2.4. Fluorinated gases (categories 2.E and 2.F).....	62
4.2.5. Non-energy use of fuels (category 2.G)	64
4.3. Recalculations and planned improvements.....	64
4.3.1. Recalculations	64
4.3.2. Planned improvements	66
Chapter 5: Solvent and other products use	67
5.1 Overview.....	67
5.2. Methodological issues.....	67
5.3 Recalculations and planned improvements.....	68
5.3.1. Recalculations	68
5.3.2. Planned improvements	68
Chapter 6: Agriculture	69
6.1. Overview.....	69
6.1.1. Description of the sector.....	69
6.1.2 Allocation of emissions	70
6.2. Methodological issues.....	70
6.2.1. Data sources	70
6.2.2. Enteric fermentation	71
6.2.3. Manure management	71
6.2.4. Agricultural soils	73
Category.....	74
6.3. Recalculations and planned improvement	76
6.3.1 Recalculations	76
6.3.2. Planned improvements	77
Chapter 7: Land-Use Change and Forestry.....	78
7.1. Overview.....	78
7.2. Methodological issues.....	79
7.2.1 Changes in Forest and Other Woody Biomass Stocks	79
7.3. Recalculations and planned improvement	88
7.3.1. Recalculations	88
7.3.2. Planned improvements	88
Chapter 8: Waste	89
8.1. Overview.....	89
8.1.1. Description of the sector.....	89
8.1.2. Allocation of emissions	89
8.2. Methodological issues.....	90
8.2.1. Solid waste disposal on land.....	90
8.2.2. Wastewater treatment	94
8.2.3. Waste incineration.....	95

8.2.4. Others	96
8.3. Recalculations and planned improvements.....	96
8.3.1. Recalculations	96
8.3.2. Planned improvements	97
<i>Chapter 9: Recalculations and planned improvements</i>	<i>98</i>
9.1. Recalculations and achieved improvements	98
9.2. Implication on emission levels and trends.....	98
9.3. Planned improvements.....	98
<i>References</i>	<i>100</i>
<i>Annexes.....</i>	<i>103</i>
Annex 1 : Key sources analysis	104
Annex 2: GHG emission trends in the three Regions.....	106

CHAPTER 1: INTRODUCTION

1.1. Overview

This fifth National Inventory Report documents the Belgian greenhouse gas emission inventory in accordance with the revised UNFCCC reporting guidelines on annual inventories. It is aimed at complying with decisions 11/CP.4, 3/CP.5 and 18/CP.8 of the *Conference of the Parties*, and the Council Decision 280/2004/EC concerning a Mechanism for Monitoring Community greenhouse gas emissions and for implementing the Kyoto Protocol.

The greenhouse gas inventory presented here contains information on anthropogenic emissions by sources and removals by sinks for direct greenhouse gases (CO₂, CH₄, N₂O, PFCs, HFCs, and SF₆), indirect greenhouse gases (CO, NO_x, NMVOCs) and SO₂. It covers the period 1990-2004. Inventory data for the years 1990 to 2003 have been recalculated, what constitutes a major update on the inventories reported previously.

This fifth National Inventory Report is presented according to the structure outlined in document FCCC/CP/2002/8, amended to fit to the Belgian national context. Complete CRF tables, for years 1990 to 2004, are provided as an annex to this report, under electronic format. Next to the emissions data, the CRF-tables are completed with – as requested - the standard indicators (notation keys), providing information on data gaps, methods applied, emission factors used, completeness and quality.

This national inventory report includes a description of the methodologies and data sources used for estimating emissions by sources and removals by sinks, a discussion of these estimates and their trends (including an analysis of the key source categories), and information on recalculation, uncertainties, quality assessment and quality control.

1.2. Institutional arrangements and process of inventory preparation

In the Belgian federal context, major responsibilities related to environment lie with the regions. Compiling greenhouse gas emissions inventories is one of these responsibilities. Each region implements the necessary means to establish their own emission inventory in accordance with the FCCC guidelines for the common reporting format. The emission inventories of the three regions are subsequently combined to form the national greenhouse gas emission inventory. Since 1980, the three regions have been developing different methodologies (depending on various external factors) for compiling their atmospheric emission inventories. During the last years important efforts are made to tune these different methodologies, especially for the most important (key) sectors. Obviously, this requires some co-ordination to ensure the consistency of the data and the establishment of the national inventory. This co-ordination is one of the permanent duties of the Working Group on « Emissions » of the *Co-ordination Committee for International Environmental Policy* (CCIEP), where the different actors decide how the regional data will be aggregated to a national total, taking into account the specific characteristics and interests of each region as well as the available means. The *Interregional Environment Unit* (CELINE - IRCEL) is responsible for integrating the emission data from the inventories of the three regions and for compiling the national inventory. The National inventory report is then formally submitted to the National Climate Commission, established by the Cooperation agreement of 14 November 2002, for approval, before its submission to the Conference of the Parties to the United Nations Framework Convention on Climate Change and to the European Commission,

under the Council Decision 280/2004/EC concerning a Mechanism for Monitoring Community greenhouse gas emissions and for implementing the Kyoto Protocol.

1.3. Description of methodologies and data sources used

As a consequence of the responsibility of the regions in compiling greenhouse gas inventories, concomitant methodologies have been developed by the three regions for compiling their inventory from basic data. This section describes the general approach developed by each region. A similar presentation of the national inventory in Belgium has been applied in the chapters 3 to 8 for each of the IPCC sectors and for fluorinated gases (see section 4.2.5).

As the QA/QC procedures are not fully implemented in Belgium for the time being, these are not described in chapters 3 to 8 for each sector, but a general description is provided in section 1.5 below. Section 1.6 gives a detailed description of the uncertainty analysis of the emission inventory of 2003 that is carried out for the second time in Belgium.

Inventory data for the years 1990 to 2003 have been recalculated, as a consequence of methodological changes, harmonisation of allocation and/or methods between the regions, and access to new data sources. Emission figures of the greenhouse gases for 2004 are estimated on a temporary basis in Belgium in this submission.

The fluorinated gases (categories 2E and 2F) constitute an exception in that the emission inventory for these gases is set up at the national level as well as for each of the 3 regions, in a single, harmonised approach.

Contrary to all other sectors in the Belgian emission inventory, the emissions of CO₂ from road traffic are not calculated as the sum of the emissions of the 3 regions (see section 3.2.3 for further information). These emissions are calculated bases on the national statistics (fuels sold on the Belgian territory) and IPCC default emission factors.

Because of the importance of fixing the emissionquota of the reference years (1990 for all greenhouse gases except for the F-gases where 1995 is the reference year) in the framework of submitting the assigned amount report pursuant to Article 8(1)(e) of Decision 280/2004/EC before the 15th of January 2006 to the European Commission, special attention is gone during this submission to the optimization of the greenhouse gas emissioninventory of the reference years. Of course in all cases of optimization timeconsistency is guaranteed.

In the same framework, the regions have done special efforts to harmonise methodologies between the 3 regions as much as possible and in the first place for the most important greenhouse gases (mainly CO₂) and sectors. Some inconsistencies between methodologies in the 3 regions remain and will not be changed anymore in the future to keep the timeconsistency with the reference years within the regions. This is f.i. the case for the emission factors of CH₄ and N₂O in the manufacturing industry and construction and in the 'other' sectors where different sources (IPCC, CITEPA and EMEP/CORINAIR) remain used.

The regional inventory systems are fully described in the National Inventory System which has been reported by the end of 2005 for the first time.

1.3.1. Flemish region

In Flanders, the greenhouse gas inventory is set up by the *Department Monitoring and Research* of the *Flemish Environmental Agency* (VMM).

As it became an obligation in 2005 for the most important industrial sites in Flanders to report their emissions of greenhouse gases when exceeding a defined threshold value, the greenhouse gases (mainly for CH₄ and N₂O) of the industrial sector are revised during this submission for the complete time series from 1990 on. This is among others the case for the refineries and the iron and steel sector.

CO₂ emissions

CO₂ emissions are mainly calculated on the basis of the energy balance, which is annually established by the *Flemish Institute for Technological Research* (Vito) [1] funded by the Flemish region. This is based on available statistical data and models, on the information coming from the obliged annual reporting of industrial emissions (mainly class I and class II companies and for emissions exceeding a given threshold value, compulsory since 1993) and on a survey among energy suppliers, federations and individual consumers. The methodology is described in the annual reporting document 'Energiebalans Vlaanderen : Onafhankelijke methode' ('Energy Balance Flanders : Independent methodology'). Last publication of this document dates from September 2005. The energybalances of all years can be found on <http://www.emis.vito.be> This methodology is fine-tuned whenever necessary. Starting from this energy balance, the CO₂ emissions are calculated using CO₂ emission factors. These are mostly the default IPCC emission factors from the Revised 1996 Guidelines, except for some special products (blast furnace gas, coke oven gas, refinery gas, waste products) and sectors (refineries, electricity production) where more accurate, country-specific factors are used.

The other CO₂ emissions (non-energy consumption, waste incineration and process emissions from the glass- and ceramicproduction and from steel production) are calculated by using a country-specific methodology. In general, mostly Tier 1 methodology, the sectoral approach, was used for estimating CO₂ emissions.

The emissions from the LUCF-sector in Flanders are completed during the 2006 submission. More in particular, the emissions and sinks of CO₂ (total net emissions) of terrestrial ecosystems are newly estimated. This source includes the emissions originating from the changes in carbon stock of grasslands, arable lands and forests, changes in biomass of trees in forests and the emissions as a result of trees in forests (See section 7 for further detailed information).

CH₄ and N₂O emissions

CH₄ and N₂O emissions are mostly calculated by multiplying an activity data with an emission factor. Some of the emission factors used originate from CITEPA [2], an institute that established these factors in the framework of the CORINAIR inventory. In some cases these emission factors correspond with the emission factors described in the joint EMEP/CORINAIR handbook [3]. Other sources of emission factors are TNO [4] and country specific emission factors. The methodology used by the Flemish region to calculate the emissions of road transport, the so called MIMOSA-model, is mainly developed for policy objectives. This MIMOSA-model is an emissionmodel that calculates the trafficemissions based on data of mobility per roadsegment. These emissions are calculated based on a traffic flow model of the Flemish region, which means that a geographical performance is possible.

Emissions of air traffic are calculated using the EMEP/CORINAIR methodology [3].

Industrial process emissions are estimated using specific plant information combined with specific or default emission factors or by using the results of monitoring work.

Country-specific methodologies are developed for calculating the emissions of navigation and transport via railways, for agriculture (reference [6] for CH₄ and [7] for N₂O), for solid waste disposal [8] and for distribution, transmission and storage of natural gas.

1.3.2. Walloon region

The emission inventories of the Walloon region are compiled by the *General Directorate for natural resources and environment* (DGRNE) using the IPCC methodology (or EMEP/CORINAIR for some sectors where IPCC does not provide emission factors). Emission factors used, are examined with all industrial sectors. In some cases as agriculture and forestry, the emissions estimates are based on a specific study reflecting the Walloon environment.

1.3.3. Brussels region

The emission inventories of the Brussels region are compiled by the *Brussels Institute for Environmental Management* (IBGE-BIM) using the CORINAIR methodology (or IPCC for some sectors). The emissions are calculated by multiplying an activity data by an emission factor. Generally, these activity data and emission factors used in the Brussels inventory are estimated on the basis of research projects funded by IBGE-BIM (for instance, the annual energy balance that is established on a survey among energy suppliers, federations and individual consumers). These projects combine the socio-economic Brussels specificities and the reference values found in the joint EMEP/CORINAIR handbook [3, 44] as well as in other reference works (IPCC Guidelines, specific bibliographies like PARCOM, TNO, EPA,...). The different sectors taken into account in the Brussels emission inventory reflect the characteristics of a strict urban environment.

1.4. Key sources categories

Key source categories were identified according to the Tier 1 method described in the IPCC Good Practice Guidance and Uncertainty Management in National Greenhouse Gas Inventories [10]. Both a Level Assessment (contribution of each source category to the total national estimate) and a Trend Assessment (contribution of each source category's trend to the total trend) were conducted.

The key source analysis was realised on the basis of a set of sub-categories, at the level of detail of the Sectoral Report Tables. When appropriate (detail for sub-categories not available), sub-categories were aggregated at a higher level. Sources that do not occur in Belgium, as well as those that are not estimated (no data) were excluded, as well as LUCF sources. Each greenhouse gas emitted from a single source category was considered separately. This procedure led to the determination of a set of fifty-four source categories, covering 99.5% of the total aggregated emissions. The key source analysis was then performed, using CO₂-equivalent emissions calculated by means of the global warming potentials (GWPs) specified in the UNFCCC reporting guidelines on annual inventories.

The Level Assessment (see Annex 1) resulted in the identification of 27 key sources, covering 95%¹ of the total national aggregated emissions. 28 key sources were identified from the Trend Assessment (see Annex 1), as those that contribute 95% to the trend of the inventory. Key source categories identified from the Level and the Trend Assessments overlap to a large extent. As a whole (Level and Trend Assessments), 34 key source categories were determined (Table 1.1). The absolute change in direct greenhouse gas emissions of these key sources over the period 1990-2004 is listed in Table 1.1 and shown in Figure 1.1.

CO₂ emissions from road transportation is the first key source of greenhouse gas emissions in Belgium (17.4% of total aggregated emissions). It constitutes the main drivers of emissions trends (Annex 1). CO₂ emissions from road transportation, electricity production and residential space heating are pointed out by the Level Assessment as the three main key source categories, each contributing to 15 to 18% of the total national emissions (together, these three sources cover 48.7% of the total emissions). CO₂ emissions from iron and steel industry and chemical industry (IPCC category 1.A.2.c) also constitute major key sources, which respectively account for 7.3 % and 5.3 % of the total emissions.

The three most important key sources of non-CO₂ emissions in Belgium are CH₄ emissions from cattle (enteric fermentation) (2.5%), N₂O emissions from nitric acid production (2.1%), and N₂O emissions from agricultural soils (1.5%). One may finally notice that the five key source categories which displayed the most important absolute increase in their emissions over the period 1990-2004 (figure 1.1, table 1.1), are CO₂ from road transportation (+6529 Gg CO₂-eq.), CO₂ from residential (+2588 Gg CO₂-eq.), CO₂ from commercial & institutional (+1852 Gg CO₂-eq.), energy related CO₂ from chemicals (IPCC category 1.A.2.c, +1536 Gg CO₂-eq.), and HFCs emissions from refrigeration and air conditioning equipment (+1039 Gg CO₂-eq.). On the contrary, CO₂ from Iron and steel (-3375 Gg CO₂-eq.), CH₄ from waste disposal on land (-1815 Gg CO₂-eq.), CO₂ from solid fuels (IPCC category 1.A.1.c, -1719 Gg CO₂-eq.), SF₆ production (-1559 Gg CO₂-eq.) and PFCs production (-1447 Gg CO₂-eq.) are the source categories that displayed the most important drop in GHG emissions between 1990 and 2004.

¹ This threshold (95%) is recommended in the *IPCC Good Practice Guidance and Uncertainty Management in National Greenhouse Gas Inventories*, for both the Level Assessment and the Trend Assessment ; it was determined to be the level at which 90% of the uncertainty in a 'typical' inventory would be covered by key source categories, for the Tier 1 method.

IPCC Source Categories	Direct Greenhouse Gas	Criteria for identification	Absolute emission trend (1990-2004) (Gg CO2 eq.)
ENERGY			
1.A.1.a. Public Electricity and Heat Production	CO2	Level	403
1.A.1.b. Petroleum Refining	CO2	Level, Trend	812
1.A.1.c. Manufacture of Solid Fuels and Other Energy Industries	CO2	Trend	-1719
1.A.2.a. Iron and Steel	CO2	Level, Trend	-3375
1.A.2.c. Chemicals	CO2	Level, Trend	1536
1.A.2.e. Food Processing, Beverages and Tobacco	CO2	Level, Trend	-567
1.A.2.f. Other (Manufacturing Industries and Construction)	CO2	Level, Trend	-1001
1.A.3.b. Road Transportation	CO2	Level, Trend	6529
1.A.4.a. Commercial/Institutional	CO2	Level, Trend	1852
1.A.4.b. Residential	CO2	Level, Trend	2588
1.A.4.c. Agriculture/Forestry/Fisheries	CO2	Level, Trend	-412
1.B.2.b. Natural Gas	CH4	Trend	-112
1A.1. Energy Industries	N2O	Trend	134
1A.2. Manufacturing Industries and Construction	N2O	Trend	-129
1A.3. Transport	N2O	Level, Trend	477
1A.4. Other Sectors	N2O	Level	39
INDUSTRIAL PROCESSES			
2.A.1. Cement Production	CO2	Level	14
2.A.2. Lime Production	CO2	Level	131
2.B.1. Ammonia Production	CO2	Level, Trend	571
2.B.2. Nitric Acid Production	N2O	Level, Trend	-444
2.B.5. Other (Chemical Industry)	CO2	Level, Trend	845
2.C.1. Iron and Steel Production	CO2	Level, Trend	-294
2.E. Production of Halocarbons and SF6	SF6	Trend	-1559
2.E. Production of Halocarbons and SF6	PFCs	Trend	-1447
2.F.1. Refrigeration and Air Conditioning Equipment	HFCs	Level, Trend	1039
2.F.2. Foam Blowing	HFCs	Trend	-115
AGRICULTURE			
4.A.1. Cattle	CH4	Level, Trend	-636
4.B.1. Cattle	CH4	Level, Trend	-199
4.B.12. Solid Storage and Dry Lot	N2O	Level	-90
4.B.8. Swine	CH4	Level	-76
4.D.1. Direct Soil Emissions	N2O	Level, Trend	-304
4.D.2. Animal Production	N2O	Level, Trend	-118
4.D.3. Indirect Emissions	N2O	Level, Trend	-244
WASTE			
6.A. Solid Waste Disposal on Land	CH4	Level, Trend	-1815

Table 1.1. : Key source category analysis: summary (see details in Annex 1).




Figure 1.1. : Key source category analysis : GHG Emission Trends 1990-2004 (Gg CO₂ equivalent).

1.5. QA/QC plan and related issues

The Working Group on « Emissions » of the *Co-ordination Committee for International Environmental Policy* (CCIEP) has conducted intern quality insurance and quality control work by continuously exchanging information about methodologies used and estimated results. Feedback is given and extra controls are made by the responsible person for compiling the Belgian emission inventory of greenhouse gases. As a consequence this all gives extra checks of the regional emission inventories as well.

Following the IPCC Good Practice Guidance [10] and Uncertainty Management in National Greenhouse Gas inventories (June 2001), QC procedures (Tier 1) will be implemented to check the inventory on selected sets of data and processes. In a first approach, the key sources categories will be checked over their input data, their parameters and their calculations. In this view, several technical meetings are conducted since January 2003 with the three regions to identify for each sector on which level the Good Practice Guidance (e.g. uncertainty analysis, QA/QC,...) has to be implemented and to devise a work programme until the next submission.

Independent audits of the greenhouse gas inventories of the regions and the national inventory have started in the course of 2002 and all the results of the 3 regions in Belgium became available in 2003. The purpose of these audits was to analyse the difficulties encountered while compiling the regional and national emission inventories in order to improve the quality and completeness of the Belgian national emission inventory and to evaluate the differences met between the present process of information and the IPCC Guidelines and the obligations need to be fulfilled in the framework of the Kyoto Protocol.

The results of these audits of greenhouse gases show clearly that - taking into account the limitations in available time, manpower and means – the Belgian national inventory is of qualitative good value. The difference between the actual situation in Belgium and the fulfilling of the IPCC Guidelines is mainly the absence of the complete implementation of the IPCC Good Practice Guidance [10]. As mentioned already above working groups are set up since the beginning of 2003 to investigate in detail the implementation of the Good Practice Guidance for the different sectors in Belgium and to try to limit the inconsistencies between the 3 regional emission inventories in Belgium as much as possible. The overall conclusion in the different technical working groups was that the regional and the national inventories in Belgium are set up to the best of the ability, that appropriate methods are used for all sectors and in accordance with the IPCC Good Practice Guidance.

In Flanders, the procedures to prepare the Flemish energy balance are part of a certified ISO9001 systemsince July 2000. The certificate number is 08376-2003-AQ-ROT-BELCERT. This certificate is currently applicable to the development and implementation of complete evaluation methods and management concepts for the sustainable use of materials, energy and environment, including the electronic distribution of information on energy and environmental information (EMIS).

The quality system consists of quality procedures and planning activities. Specific for the preparation of the energy balance, there are 7 procedures in place.

EMIS-PRO 021	Energy balance Flanders	General procedure with methodology to prepare an energy balance for a specific year.
EMIS-PRO 022	Survey of industry	The procedure describes the methodology to carry out a survey in the industrial sectors in a specific year.
EMIS-PRO 023	Extrapolation of industry	The procedure describes the methodology to extrapolate the energy consumptions from the survey in the industry to a global energy consumption for the

		industry in Flanders for a specific year.
EMIS-PRO 024	Survey of service sector	The procedure describes the methodology to carry out a survey in the service sectors in a specific year.
EMIS-PRO 025	Extrapolation of service sector	The procedure describes the methodology to extrapolate the energy consumptions from the survey in the service sector to a global energy consumption for the service sector in Flanders for a specific year.
EMIS-PRO 026	Transformation sector	The procedure describes the methodology to compose the transformation sector in the energy balance.
EMIS-PRO 027	Survey of electricity sector	The procedure describes the methodology to carry out the survey for electricity and heat-production in cooperation with ANRE and implementation of the resolution.

Procedure EMIS-PRO 021 describes the general methodology used to establish a yearly energy balance for Flanders. Purpose of this procedure is to give information and instructions to be able to establish in a coherent way an energy balance for Flanders in a specific year. The procedure refers where appropriate to the other procedures for specific sectors.

The mentioned EMIS-procedures for the preparation of the energy balance for Flanders are part of the covering quality system of the expertise center IMS (Integral Environmental Studies) in VITO. The quality handbook of the expertise center gives an overview on the global quality system with references to the specific procedures of specific activities. An example of a general procedure is *'ALG-PRO 011 Continuous quality improvement, quality renewal and control of aberrations'*. This procedure describes the responsibilities and actions of all staff members in case of aberrations.

In the beginning of 2004, in Flanders a study started to calculate the uncertainties (both on Tier 1 and Tier 2 level) and to guide in the implementation of a quality system (QA/QC-plan) of the emission inventory of greenhouse gases. Final results of this study became available in May 2004.

A complete development of the system (among others further description in detail of all the procedures involved) as well as a first internal review became operational in the course of 2005, this means that the full implementation for all sectors and on the most detailed level is started in the beginning of 2006.

The quality system set up in Flanders is completely based on the standardized norm ISO 9001:2000. In the process of development of the quality management system in Flanders, a gap-analysis was carried out, a quality structure and different standardized procedures were set up. A quality handbook was published which includes all aspects of a technical and organizational level to set up the emission inventory of GHG.

Standardized procedures of different levels are defined.

In what follows a summary is given of all procedures involved in the QA/QC-system (state of affairs february 2005) :

More general procedures :

VMM/AMO/GP1/0.004: Procedure for the treatment of a complaint;

VMM/AMO/GP1/0.006: Procedure for the management of quality care-personnel files;

VMM/AMO/GP1/0.008: Procedure for the performance of audits;

VMM/AMO/GP1/0.010: Procedure for setting up a general quality care–management report;

VMM/AMO/GP1/0.011: Procedure for the management of documents.

More detailed procedures :

VMM/AMO/GP2/5.001: Procedure to determine non-conformities, quality problems and proposals for improvement and follow-up by means of corrective and preventive measures;

VMM/AMO/GP2/5.002: Procedure for the training of the personnel of the service “Emissie Inventaris Lucht” (Emission Inventory Air);

VMM/AMO/GP2/5.003: Procedure for the main process: setting up the greenhouse gas emission inventory;

VMM/AMO/GP2/5.004: Procedure to manage the Balanced Score Card.

The results of this Flemish study will be taken into account to set up a comparable system in the 2 other regions in Belgium.

In Wallonia, the inventory is conducted by the Air Cell, which is part of the General Directorate for Natural Resources and Environment, and the latter has now obtained its EMAS certification. An ISO 9001 certification is also foreseen.

For what concerns the measures used to determine country-specific emission factors, it can be mentioned that in Wallonia, before performing any air emissions measure, all the laboratories must first be agreed by ISSEP, which conducts a review of material and methodologies used and check the compliance with the requirements of a legal decree (Arrêté royal du 13 décembre 1966 relatif aux conditions et modalités d'agrément des laboratoires et organismes chargés des prélèvements, analyses et recherches dans le cadre de la lutte contre la pollution atmosphérique (M.B. 14.02.1967)) .The updated list of agreed laboratories is published on the website of DGRNE, the responsible institut in Wallonia.

In the Brussels region, the energy balance is established by an independent institute, ICEDD (Institut de Conseil et d'Etudes en Développement Durable), who is certified ISO 9001 for its internal procedures. For information, the emissions from energy consumption constitute nearly all the emissions of this urban region.

Calculations of uncertainties on greenhouse gas emissions on the national level are calculated on Tier 1-level (see section 1.6 for more details).

These uncertainties and the quality system that is in progress include all the recommendations expressed in the “IPCC Good Practice Guidance and Uncertainty Management in National Greenhouse Gas Inventories”(IPCC 2000) and the “Revised 1996 IPCC Guidelines for National Greenhouse Gas Inventories (IPCC 1996).

1.6 Tier 1 uncertainty calculation

1.6.1. General approach

The IPCC Good Practice Guidance Tier 1 method has been applied to assess the uncertainty in the emission inventory of 2001 in the previous submission. During this submission the uncertainty calculation is applied on the Belgian greenhouse gas emission inventory of 2003 as submitted on the 15th of March 2006 to the European Commission.

The uncertainty calculation during this submission is carried out for the year 2003 and a trend uncertainty analysis for the years 1990 (1995 for F-gases) and 2003. All sectors (except LULUCF) are included in the calculation, this means that the uncertainty analysis of the emissions of F-gases is included for the first time. The uncertainty calculation at a tier 1-level of the fluorinated greenhouse

gases has been carried out in 2005 by Econotec and the Vito for the years 1995 (base year for F-gases), 2003 and 2004.

In Flanders, a complete study of the uncertainty was conducted in 2004 by an independent consultant, Det Norske Veritas, both on Tier 1 and Tier 2 level. The uncertainties were determined for the emission level 2001 and for the 1990-2001 trend in emissions for all source categories comprising emissions of CO₂, CH₄ and N₂O. These results are available in the technical report 'Quantification of Uncertainties – Emission Inventory of Greenhouse Gases of the Flemish Region of June 2004'.

As most of the data suppliers in Belgium do not provide any information on the associated uncertainty, the IPCC default values have been largely used in the 3 regions in Belgium, together with expert judgement regarding their applicability in the national /regional circumstances.

In the absence of default IPCC values, estimates have been searched in other sources such as the EMEP/CORINAIR guidebook [3] and studies on uncertainty in emission inventories conducted in other member states, in the case where national circumstances could be assumed comparable.

The results of the three regions have then been compiled using expert judgement and/or error propagation equation from the Good Practice Guidance, in order to produce one single table 6.1 (as expressed in the guidelines).

According to the available references, in most member states the ultimate choice of an uncertainty estimate is often based on expert judgement and is therefore also rather uncertain. However, as stressed by the IPCC Good Practice Guidance [10], uncertainty calculation is a mean to identify and prioritise improvement activities, rather than an objective on itself.

1.6.2. Comment by category

1A1 Energy industries

According to IPCC Good Practice Guidance (table 2.6), the uncertainty on activity data is less than 1% in the case of survey. The uncertainty takes into account that a complete survey of energy industries is conducted yearly for the purpose of establishing the energy balance. The uncertainty on emission factors come from table 2.5 and page 2.15 of the IPCC Good Practice Guidance, associated with expert judgement.

1A1b Petroleum Refining

The uncertainties both on activity data and emission factors for CO₂, CH₄ and N₂O are mainly based on IPCC Good Practice Guidance in combination with expert judgement and mostly in line with the estimates given in other countries. For gaseous fuels the uncertainty on activity data is estimated as 1% because of very accurate statistics in Flanders for this fuel.

1A2 Manufacturing industries and construction.

According to IPCC Good Practice Guidance (table 2.6), the uncertainty on activity data is between 2 and 3 % in the case of survey. In Belgium, the annual survey is cross-checked with other sources of information for the biggest industries. However, it is considered that measuring is more accurate for gaseous fuels (Monni and Syri, 2001) leading to 2% uncertainty on the activity data, compared in most cases with 5 % for solid fuels. For liquid fuels, the uncertainty lies between 2 and 8 %, depending on the sector considered. Higher values are chosen for biomass and other fuels, respectively 20 and 5%.

The uncertainty on emission factors is the same as for energy industries, as the same emission factors are used.

1A3 Transport

The uncertainty on activity data for CO₂ emissions from road transport is given by IPCC Good Practice Guidance (page 2.49), which mentions that it is the main source of uncertainty for CO₂. The same uncertainty on activity data is used for all gases. For CH₄ and N₂O, the uncertainty on emission factors are those recommended by IPCC Good Practice Guidance. A higher uncertainty is estimated for N₂O, taking into account the lack of precise monitoring on the combustion conditions (vehicles types, average speed, etc...).

Default IPCC values are used for civil aviation, both for activity data and emission factors. For railways, 78% of the Belgian railways are using electricity, whose uncertainty is treated under energy. The rest of the locomotives uses diesel as fuel. In the absence of IPCC default value, the uncertainty on activity data is estimated at 6 %, considering that this data is collected and delivered yearly by one single national operator. The emissions factors are taken from EMEP/CORINAIR guidebook where their uncertainty rating are respectively "C" and "E" for CH₄ and N₂O. This ranking seems quite consistent with the values used in Finland [40], respectively 60-110% for CH₄ and 70- 150 % for N₂O. Similar values were consequently adopted as a first estimate.

Fuel consumption in navigation is estimated on the basis of the traffic, which is quite controlled on the domestic scale. The uncertainty on activity data is estimated at 10 %. For emissions factors, the uncertainty is in the same range as for railways, considering the same rating of these emission factors in the EMEP/CORINAIR guidebook.

The CO₂ emissions under category "other" includes energetic emissions originating from the transport through pipelines (compression stations). An uncertainty is assumed of 5% on activity data (information data from the gas federation) and of 1% on the emission factor (default IPCC emission factor).

1A4 Other sectors

Commercial and residential fuel consumption is the main activity data in this sector. Surveys are combined with extrapolations in order to estimate the consumption. The uncertainty on activity data is based on IPCC Good Practice Guidance (table 2.6) and takes into account the type of fuels : natural gas is measured with accuracy, but wood consumption is extrapolated from available data. The uncertainty on emission factors is the same as for energy and industrial sectors (table 2.5, IPCC Good Practice Guidance).

1B Fugitive emissions from fuels

Fugitive emissions under 1B1 are linked to the production of coke. Production is assumed well known, while the uncertainty on the emission factor is estimated at 60 %, taking into account the EMEP quality estimate and range of values.

Uncertainty estimates on the fugitive emissions from oil refining and storage (category 1B2a) are for the activity data and for the emission factors assumed to be the same as in the category 1A1b (5% for the activity data and 50 % for the emission factor).

The uncertainty on the amount of gas leaked through the distribution network is high according to IPCC Good Practice Guidance (page 2.92). Since the activity data (length of pipelines for the different materials of pipelines) is based on information of the gas distribution company, the uncertainty is estimated at 10%. Emission factors (= leak rates) are based on statistics on measurements from this company and their uncertainty is estimated at 30%.

2A Mineral products

For lime and cement plants, the uncertainty on activity data comes from IPCC Good Practice Guidance (pages 3.15 and 3.21). The uncertainty on emission factors is assumed to be low, as plant-specific emission factors are used in both sectors.

The uncertainty on activity data for glass production is assumed to be comparable with the others industrial productions. The CO₂ emission factor cited in the EMEP/CORINAIR guidebook comes from studies in the Netherlands. Consequently, the uncertainty on the emission factor was taken from the NIR of the Netherlands for this sector.

2B Chemical industry

For ammonia production, the Norwegian uncertainty calculation [41] and the Irish NIR were the only references found. Following expert judgement, average values from those references were used in this study.

Since there is only one producer of nitric acid remaining since 2000 in the Flemish region with reliable production data available, the uncertainty in activity data is estimated at 2%. Based on the Finnish evaluation in 2001, the uncertainty on the N₂O emission factor is estimated at 80% in spite of an agreement of the companies of the emission factor used.

For the production of caprolactam the same uncertainty in activity data is used as for the production of nitric acid (2%). The uncertainty of the emission factor is estimated at 30% by expert judgment.

2C Metal production

The uncertainty on activity data is estimated at 2% because these figures come directly from the companies which dispose of well developed statistical systems. As the emission factors are mainly plant-specific, their uncertainty is assumed to be in the low range of IPCC values.

2E Production of halocarbons

The emission figures are a result of measurements combined with a mass balance. The calculated scientific and model uncertainty is 13 % (based on error propagation analysis).

The non-fugitive emissions of CF₄ are measured. Their calculated uncertainty is 45 %.

The uncertainty figures have been reviewed and confirmed by an audit bureau in 2004. However, they seem to be unrealistically low according to both VITO and the company itself. In order to get a conservative estimate, they have been doubled in the uncertainty calculation table. Given the small share of the emission source in the overall GHG emissions, the overall impact of this change remains limited (in the order of 0,1% of the total national GHG emissions).

2F Consumption of halocarbons

The main emission source is the operation of distributed refrigeration systems (refrigeration plants in industry and the commercial sector, as well as air conditioning plants that are built and filled with refrigerant on site). The emissions are calculated as the product of the bank (activity variable) by the emission rate (emission factor). The size of the bank is itself calculated on the basis of past refrigerant deliveries and assumptions on the emission rate. Therefore the activity variable and the emission factor are correlated.

Because of this correlation, the uncertainty has been assessed globally, and this in particular by carrying out sensitivity analyses on the impact of the emission rate on the emissions, using the emission calculation model.

For the remaining emission sources, the uncertainty has in general been estimated separately for an activity variable and an emission factor. Given the lack of statistical data and default values in the IPCC guidelines, the figures are generally based on expert judgement.

2G Feedstocks

The uncertainties both on activity data and emission factors for CO₂ are mainly based on expert judgment. Information originated from the emission inventories of Finland and the Netherlands is also taken into account to obtain a final uncertainty of 25% on activity data and of 30% on the emission factor.

3D N₂O from anaesthesia

The activity data is the number of hospital beds, which is well known. As no default emission factor is available by EMEP/CORINAIR nor by the IPCC Guidelines [10], a national specific emission factor has been estimated through surveys in hospitals. The uncertainty on this emission factor is considered high.

4A Enteric fermentation

The only activity data here is the national livestock census. Given the features of the monitoring (census twice a year, individual earmarks and registration for all bovines, ...), the uncertainty is

judged small. The emission factors are mainly taken from the IPCC default values, using Tier 1 methodology. Consequently, the IPCC uncertainty estimate of 40% is used for the emission factor.

4B Manure management

The activity data are the livestock census, but also the type of animal housing. The type of housing is more difficult to assess than the number of animals, so the uncertainty on the activity data is estimated at 10 %.

The CH₄ emission factors are based on a regional-specific study. However, given that many assumptions were necessary to calculate these emission factors, the uncertainty on these emission factors is estimated to be similar to the uncertainty on enteric fermentation emission factor.

The IPCC emission factors are used for N₂O emissions. Consequently, the IPCC uncertainty (page 4.43) in combination with information of the Finnish emission inventory, are used in the uncertainty calculation.

4D Agricultural soils

For CH₄, this small source is linked to the manure applied during grazing. The same uncertainty than for CH₄ from manure management is applied.

In comparison with the previous agricultural sectors, N₂O emissions from soils involves the use of more activity data, such as the use of mineral fertilisers, the atmospheric deposition and runoff, the amount of manure applied on the fields, etc... The uncertainty on activity data is thus estimated at 30%, which seems in line with the values cited by other parties.

It is well known that the uncertainty of N₂O from agricultural soils is crucial for the determination of the overall uncertainty. Although most countries use the IPCC default values, the uncertainty on emission factors varies widely : 2 orders of magnitude (Norway, [41]), 509 % (UK, in IPCC Good Practice Guidance), 200 % (France and the Netherlands, NIR 2003), 100 % (Ireland, NIR 2003), 75 % (Finland, overall uncertainty for AD*EF, [40]), 24 % (Austria, NIR 2003). For the time being, a more or less average value of 250 % is used in this calculation.

6A Solid waste disposal on land

In Wallonia, complete statistics on the amount of waste put in solid waste disposal sites are delivered on a yearly basis since 1994. For the previous years, the amounts have been estimated using available data and expert judgement from the waste offices. Hence, the uncertainty on activity data is lower since 1994. However, given that in the model the activity data of a single year is used over a 25 years degradation time, the same uncertainty of 30 % (1990 estimate) has been applied on the whole time series. For the same reasons, the activity data are assumed to be correlated for the calculation of the uncertainty in trend due to activity data.

The overall uncertainty on emission factors reported in other member states goes from 30 % (Netherlands, Finland, Norway) to 50 % (Ireland, France). A provisional value of 40 % is adopted for this calculation.

6B Wastewater handling

IPCC recommends an activity data uncertainty of 5% for population and 30 % for BOD/person. An overall uncertainty of 20 % is considered for activity data. The same uncertainty is used for N₂O calculation, assuming that the uncertainty on the annual per capita protein intake and the fraction of nitrogen in these proteins lies in the same range.

The uncertainty on CH₄ emission factor reported by other parties goes from 48 % (UK, 2000) to 104 % (Finland), mainly depending on the uncertainty on the Methane Conversion Factor (fraction treated anaerobically). A default value is used for the time being and further expert judgement is needed on this estimate. Thus, an average uncertainty of 70 % is used for the time being.

For N₂O, the default IPCC emission factor of 0.01 kg N₂O/kg N is used. This emission factor comes from IPCC 1996 Guidelines, table 4.18, with a given range of 0.0025-0.0225. This range represents an uncertainty of -75% / +125%. An uncertainty of 110 % is used in this calculation.

6C Waste incineration

For N₂O, an uncertainty of 100% on the emission factor is applied, following IPCC Good Practice Guidance. The uncertainty on activity data (amount of waste) is estimated at 5%.

In Wallonia, CO₂ emissions are measured in each waste incinerator. The confidence interval was calculated for each of the incinerators, based on the standard deviation of the mean. Those uncertainties were then combined according to equation 6.3 of the IPCC Good Practice Guidance, using the 1990-2001 average quantities of waste for each plant. This estimate gives an overall uncertainty of 24 % on the CO₂ emission factor. However, the estimate of the biogenic content of the waste is another source of uncertainty. Six results on the average composition of the municipal waste are available since 1997, allowing a calculation of the confidence interval. It appears that the average biogenic part of those wastes is rather stable, although the effect of some waste policies such as separate collection of paper can be observed. The uncertainty based on the confidence interval is 3%. Using equation 6.4, the total uncertainty on the CO₂ emission factor is 24,2%.

In Flanders the major uncertainty for the estimation of CO₂ is the estimation of the fossil carbon fraction. As in Flanders the methods to determine this fossil carbon fraction are identical for this sector (combustion of waste without energy recuperation) and for the energy sector (combustion of waste or other fuels with energy recuperation), the uncertainty on the CO₂ emission fraction for waste combustion is estimated at 10% (the same as for category 1A1-other fuels). The average of both estimations gives an average uncertainty of 17 %.

Flaring in the chemical industry is monitored, but uncertainty on activity data is estimated at 20% according to expert judgement. The uncertainty on the emission factor is also estimated at 20 %.

6D Composting

The uncertainties both on activity data and emission factors for CH₄ are based on expert judgment and results in an uncertainty of 30% on the activity data and 200% on the emission factor.

1.6.3. Results and discussion

The Tier 1 analysis of the uncertainty results in an overall uncertainty of 7.5 % in the 2003 inventory of Belgium and a trend uncertainty of 2,7 %. While the uncertainty on CO₂ emission is estimated at 1,9

%, the emissions of CH₄, fluorinated gases and N₂O are much more uncertain, respectively 24 %, 27 per cent and 100 %.

As in other Parties, this outcome is largely determined by the uncertainty on the estimate of N₂O emissions from agricultural soils. While reviewing the uncertainty calculation of five industrialised countries, Rypdal and Winiwarter [42] pointed out that *"The differences in uncertainty are, in particular, due to different subjective assessment of the uncertainty in emissions of nitrous oxide from agricultural soils"*. The other sectors of which the combined uncertainty represent more than 1 % of total national emissions are N₂O emissions from liquid fuels in the residential sector, N₂O from nitric acid production in the chemical industry and CH₄ from enteric fermentation.

It can be pointed that, given the relatively limited change in the emissions from agricultural sources between 1990 and 2003, their influence is not as large in the case of the trend. Anyway, more reliable data on this sector is certainly needed on a global level.

CHAPTER 2: TRENDS IN GREENHOUSE GAS EMISSIONS

GHG emission trends are presented in this section. Emission trends are analysed for each greenhouse gas and for the main key sources, as well as in an aggregated format, using global warming potential (GWP) values. The distribution of emissions by gases and by sources is also commented. A distance-to-target assessment, aiming at evaluating progress of Belgium towards fulfilling its commitment under the Kyoto Protocol and the EU ‘burden sharing’ agreement, is commented as well. A division of GHG emission trends at the regional level is presented in Annex 2. Trends of indirect GHG and SO₂ are presented at the end of the chapter.

2.1. Emission trends for aggregated greenhouse gas emissions

Total greenhouse gas emissions (without LUCF) in Belgium amounted to 147.9 Mt CO₂ eq in 2004 (Table 2.1.), which constitutes an increase by 1.4 % compared to GHG emissions in 1990. Emissions in 2004 are 0.7% above base year emissions² (Figure 2.1). Under the Kyoto Protocol and the EU ‘burden sharing’ agreement, Belgium is committed to reduce its GHG emissions by 7.5%. Assuming a linear target path from 1990 to 2010, total GHG emissions in 2004 were 5.9 index points above this target path.




Figure 2.1. : Belgium GHG and CO₂ emissions 1990-2004 (excl. LULUCF), compared with Kyoto target.

Unit: Index point (base year = 100).

Note: For the fluorinated gases, the base year is 1995; as the y-axis refers to the base year, the index value for the year 1990 is not necessarily 100.

² Base year is 1995 for fluorinated gases, 1990 for other gases

Table 2.1. : Overview of Belgium GHG emissions and removals from 1990 to 2004 (Gg CO₂ equivalents).

	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004
Net CO2 emissions/removals	117650	121102	119175	117692	121262	122246	126505	120864	126648	121688	122436	121313	120974	125257	125734
CO2 emissions (without LUCF)	119081	122295	120738	119175	122828	123632	127762	122272	127933	122911	123986	124110	123311	126974	126907
CH4	10825	10714	10661	10594	10619	10661	10420	10254	10066	9766	9471	8960	8468	8085	7916
N2O	12010	12011	11633	11957	12487	13071	13384	12979	13125	12967	12588	12413	11886	10782	11210
HFCs	434	434	434	434	434	434	514	622	753	790	897	1031	1249	1406	1468
PFCs	1753	1678	1830	1759	2113	2335	2217	1211	669	348	361	223	82	209	306
SF6	1663	1576	1744	1677	2035	2205	2120	525	270	120	109	105	94	75	66
Total (with net CO2 emissions/removals)	144335	147515	145476	144112	148951	150953	155160	146456	151532	145678	145860	144043	142753	145813	146700
Total (without CO2 from LUCF)	145766	148707	147039	145596	150516	152339	156417	147864	152817	146902	147411	146841	145090	147530	147873

Table 2.2. : Overview of GHG emissions and removals in the main sectors from 1990 to 2004 (Gg CO₂ equivalents).

	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004
Energy	112728	116660	115276	113902	116080	116519	121325	115405	120986	115616	116631	117401	115824	119471	119557
Industrial Processes	16398	15698	15470	15511	18114	19401	19064	16546	16079	15793	15782	15007	15183	14718	15063
Solvent and Other Product Use	246	246	249	247	244	240	238	238	237	236	253	252	250	120	250
Agriculture	13043	12887	12800	12913	12930	13127	12886	12770	12782	12812	12431	12287	11966	11486	11357
Land-Use Change and Forestry	-1431	-1192	-1563	-1483	-1566	-1386	-1257	-1408	-1285	-1223	-1550	-2798	-2337	-1717	-1173
Waste	3351	3215	3244	3022	3148	3051	2905	2905	2733	2444	2314	1895	1867	1736	1646

2.2. Emission trends by gas

The major greenhouse gas in Belgium is carbon dioxide (CO₂), which accounted for 85.8 % of total GHG emissions in 2004. Methane (CH₄) accounts for 5.4 %, nitrous oxide (N₂O) for 7.6 %, and fluorinated gases for 1.2% (Figure 2.2). Emissions of CO₂ increased 6.6% during 1990-2004, while CH₄, N₂O and fluorinated gas emissions have dropped with respectively 26.9%, 6.7% and 63.0 %³ during the same period.




Figure 2.2. : Share of greenhouse gases in Belgium (2004), and changes compared to base year (1990 for CO₂, CH₄ and N₂O; 1995 for F gases)

Total CO₂ emissions (without LUCF) in Belgium amounted to 126.9 Mt CO₂ eq in 2004 (Table 2.1). A net sink of 1173 kton CO₂ eq is reported for the LUCF sector, which offers only a tiny compensation for these emissions (0.9%). Due to the large contribution of CO₂ to total emissions (85.8%), GHG emissions in Belgium are closely connected with the emissions of CO₂, mainly related to energy consumption.

Total CH₄ emissions amounted to 7.9 Mt CO₂ eq in 2004 (Table 2.1). CH₄ emissions have substantially decreased since 1990 (-26.9%), mainly due to the deep cut in emissions from landfills.

Total N₂O emissions in Belgium amounted to 11.2 Mt CO₂ eq in 2004 (Table 2.1). The largest key sources that contribute to N₂O emissions are nitric acid production and direct soil emissions, followed by indirect emissions and transport. Other various sources contribute to a lesser extent to N₂O emissions.

Emissions of fluorinated gases in Belgium amounted to 1.8 Mt CO₂ eq in 2004. Compared to 1990, this represents a decrease of 52.2% (63.0% when compared to 1995). The major decrease is observed

³ compared to 1995 emissions

in the production of PFC's and SF₆ (-89.1%). In the meantime, emissions from refrigeration and air conditioning have increased.

2.3. Emission trends by source

An overview of the contribution of the main sectors to Belgium greenhouse gas emissions is given in Figure 2.3. Energy industries, manufacturing industry, transport, space heating and industrial processes are the most important sectors in the total GHG emissions in 2004. Agriculture (7.7 %) and waste (1.1%) account for the remaining part. Main drivers of the total increase in GHG emissions are the transport sector and space heating (residential, commercial, institutional and agriculture sector). In absolute terms, these sectors have respectively increased by 6.9 Mt CO₂ eq and 4.0 Mt CO₂ eq (Figure 2.3(b)). On the contrary, total emissions from energy industries, industry (energy and process), agriculture and waste have declined over the period 1990-2004.

The sections below give a detailed picture of the main key sources that contribute to GHG emissions in each of the four sectors : energy, industrial processes, agriculture and waste.




Figure 2.3. : GHG emissions : share of main sectors in 2004 (a) and changes from 1990 to 2004 (b).

2.3.1. Energy

In 2004, energy consumption accounted for 80.9% of total GHG emissions in Belgium. The largest key source category in the energy sector is road transport (21.6%), followed by ‘public electricity and heat production’ (19.9%), by residential space heating (IPCC category 1.A.4.b) (19.1%), iron and steel (9.1%) and chemicals (6.6%). All together, these five categories account for more than 75% of the emissions of this sector (Figure 2.4(a)).





Figure 2.4. : GHG emissions in sector 1 ‘Energy’:
 (a) share of largest key sources in 2004
 (b) changes from 1990 to 2004 (Gg CO₂ equivalent)

Although GHG emissions from the energy sector remained stable in 2004 compared to 2003, these emissions are 6.1% above 1990 emissions. The main drivers of this continuous increase are CO₂ emissions from road transport (+33.9% compared to 1990), and from space heating (residential and commercial/institutional, which increased respectively 12.8% and 43.4%). Figure 2.4.(b) shows to the extent to which the different emission sources have contributed to the overall increase in the energy sector. N₂O emissions from transport, although rather small contributor to emissions in the energy sector (0,7%), have more than doubled between 1990 and 2004. This is partly due to the introduction of catalytic converters (the use of catalytic converters on all petrol-engine cars was made compulsory in Belgium in 1993). On the other hand, CO₂ emissions from the iron and steel sector, solid fuels and other energy industries (IPCC category 1.A.1.c) and some other sectors of the manufacturing industry (IPCC category 1.A.2.f) have respectively decreased with 23.7%, 80.2% 12.4%.

(a)



(b)




Figure 2.5. : GHG emissions in sector 2 'Industrial processes':
 (a) share of largest key sources in 2004
 (b) changes from 1990 to 2004 (Gg CO₂ equivalent)

2.3.2. Industrial processes

GHG emissions from industrial processes accounted for 10.2% of total emissions in 2004. The share of emissions by the largest key sources in this sector is shown in figure 2.5, as well as changes in emissions over the period 1990-2003. N₂O emissions from nitric acid production are the main key source in this sector (20.7% of the sector emissions), followed by CO₂ emissions from cement production (18.8%), CO₂ emissions from lime production (14.8%), CO₂ emissions from iron and steel production (11.0%) and CO₂ emissions from ammonia production (8.4%). Other key sources include HFCs emissions from refrigeration and air conditioning equipment (7.4%) and CO₂ emissions from other industrial processes in the chemical industry (7.1%).

As a whole, GHG emissions from industrial processes have dropped with 1335 ktonne CO₂ equivalent between 1990 and 2004 (-8.1%). This reduction mostly originates in the PFCs and SF₆ emissions from the category 'production of halocarbons and SF₆', which peaked in 1995, and then dropped to almost zero. N₂O emissions from nitric acid production have also decreased (-444 ktonne CO₂ eq.), while CO₂ emissions from ammonia production and HFCs emissions from refrigeration and air conditioning equipment have grown considerably (+571 ktonne CO₂ eq. and 1039 ktonne CO₂ eq. respectively).

2.3.3. Agriculture

GHG emissions from agriculture accounted for 7.7% of the total emissions in Belgium in 2004. About one third of these emissions are CH₄ emissions from enteric fermentation of cattle (Figure 2.6(a)). N₂O emissions from soil account for another 19.1%, followed by CH₄ emissions from swine (11.9%), N₂O indirect emissions (8.3%), and CH₄ emissions from management of cattle manure (8.2%). Overall, emissions from agriculture have decreased by 12.9% between 1990 and 2004. All key sources of this sector have dropped. The main drivers of the GHG emission decrease in this sector are CH₄ emissions from cattle, and direct and indirect N₂O emissions (Figure 2.6(b)).




Figure 2.6. : GHG emissions in sector 4 'Agriculture':
 (a) share of largest key sources in 2004
 (b) changes from 1990 to 2004 (Gg CO₂ equivalent)

2.3.4. Waste

GHG emissions from waste accounted only for 1.1% of the national emissions in 2004. CH₄ emissions from waste disposal on land represent about 50% of total emissions of the sector (Figure 2.7(a)). Other main sources in this sector are CO₂ emissions from incineration (26.8%), and N₂O emissions from wastewater handling (16.2%). CH₄ emissions from landfills have continuously decreased since 1990 (Figure 2.7(b)), mainly as a result of the increased use of flaring, leading to a substantial cut of GHG emissions for the entire sector (-50.9%), despite a substantial increase of CO₂ emissions from waste incineration (+30.6%).




Figure 2.7. : GHG emissions in sector 6 ‘Waste’: share of largest key sources in 2003 and changes from 1990 to 2003.

2.4. Emission trends for indirect greenhouse gases and SO₂

Emissions of ozone precursors (CO, NO_x, NMVOCs) and SO₂ are presented in Figure 2.8 (share of sectors and changes 1990-2004). These data are commented below.

2.4.1. Nitrogen oxides (NO_x)

The primary NO_x emitting source in Belgium is transport (51.6% in 2003), followed by manufacturing industries (16.0%) and energy industries (15.2%). Total NO_x emissions have substantially decreased (-24.0% in 2004 compared with 1990), mainly as a result of improved performances in the production of electricity. Emissions from transport have decreased with 26% between 1990 and 2004, thanks to the use of catalytic converters on petrol-engine cars (since 1993-94), as well as emissions from energy consumption in industry. On the other hand, NO_x emissions from space heating have increased with 12% (notably as a result of the more widespread use of natural gas for heating). NO_x emissions from waste incineration have also increased in 2004, compared to 1990 (+22%).

2.4.2. Carbon monoxide (CO)

CO emissions in Belgium come mainly from energy consumption in industry (47.2%), transport (29.0%), and industrial processes (12.7%). Fuel combustion for space heating also contributes slightly (9.9%).

Between 1990 and 2004, national CO emissions fell by 41.0%, chiefly as a result of the introduction in 1993 of catalytic converters and to some extent following efforts made by industry, particularly the steel industry and refineries, and the diminished use of coal for heating purposes.

2.4.3. NMVOC



NMVOC emissions are caused mainly by the use of solvents and other products (44.5%), followed by combustion of petrol for transport (18.4%). Some industrial processes also contribute (13.3%), as well as fugitive emissions from fuels (11.3%). On the whole, these emissions decreased by 50% between 1990 and 2004, partly as a result of altered vehicle emission standards, and partly as a result of the prevention of solvent use.

2.4.4. Sulphur dioxide (SO₂)



SO₂ emissions produced by the energy, industry and residential (space heating) sectors declined sharply in Belgium between 1990 and 2004, leading to a general drop of these emissions by 58%. These reductions basically coincide with fuel substitution and with cuts in the sulphur content of the oil products used. The energy sector still accounts for 40.1% of SO₂ emissions, followed by energy consumption in industry (23.6%) and space heating (21.2%).

In the transport sector, sulphur dioxide emissions have dropped (-92% in 2004 compared with 1990), mainly due to the constant reduction in the sulphur content of fuels since 1996.



NO_x :



CO :



NMVOC :



SO₂ :





Figure 2.8. : Indirect GHG emissions and SO₂: share in 2004 and changes 1990-2004.

CHAPTER 3: ENERGY

3.1 Overview

3.1.1 Energy

In 2004, Belgium's apparent gross consumption of primary energy rose to 57.2 Mtoe (Million tonnes oil equivalent), i.e. approximately 5.50 toe per inhabitant. This level is higher than the consumption per inhabitant in neighbouring countries and above the European average. Nearly 75% of Belgium's energy needs are met by the import of fossil fuels (43.485 Mtoe in 2004). This was made up of 6,427 Mtoe of coal, 22.448 Mtoe of oil (crude and petroleum products), and 14,610 Mtoe of gas. In 2004, the primary production of energy, 94% of which was derived from nuclear fuels (whose use provided 55.4% of the electricity produced), amounted to 13,15 Mtoe. Although the hydroelectric potential is vigorously exploited in Belgium, its share in the production of energy remains negligible given the topography of the country. The production of wind energy is also very limited, due to the lack of open spaces exposed to the wind, which greatly constrains the potential for the development of on-shore wind energy. Nevertheless, wind energy from offshore wind farms, could contribute significantly to the production of electricity from renewable energy sources in the future. The use of other renewable sources of energy, in particular biomass, which is currently insignificant, could also eventually contribute to the primary energy production, assuming regional objectives are met.

The residential and other sectors are the largest end consumer of energy in Belgium. The transport sector has the most spectacular increase recorded over last 25 years (+68% from 1979 to 2004). During the same period, the industrial sector as a whole saw its overall consumption decrease by 12%. Structural and technological changes have undeniably played a dominant role in this evolution. The recent evolution of the energy market in Belgium is furthermore marked by a very strong reduction in the consumption of solid fuels, mainly on the part of industry (coke, iron and steel). The primary consumption of gas is increasing sharply, especially because of a stronger demand for electricity generation.

To prepare the Belgian greenhouse gas inventory for the section energy, the regional energy balances of Flanders, Wallonia and Brussels are the prime source of activity data and not the Belgian energy balance because of the regional responsibility to set up the atmospheric emission inventories. One exception on this general rule is the calculation of the emissions of CO₂ originating from road transport (see sections 1.3 and 3.1.3).

The energy industries contain the following sectors: the public electricity and heat production, petroleum refining and the manufacture of solid fuels and other energy industries. Petroleum refining only occurs in the Flemish region.

The category 'Public Electricity and Heat production (1.A.1.a)' includes fuel combustion emissions associated with the generation of electricity for commercial or public sale. The auto-generators category is mapped out in the IPCC category 1.A.2 'Manufacturing Industries and Construction' and 1.A.4 'Other sectors'. The allocation to the sub-categories under 1.A.2 and 1.A.4 depends on the type of the sector or industry where the energy is used. However, the allocation of CHP (Combined Heat and Power) plants needs more explanation. The most recent CHP units are in joint venture with the energy sector, in which all heat is delivered to the industrial plant and the electricity is sold to the energy sector. In these cases, all fuel in the energy balance is included in the energy sector.

The emissions originating from category 1.A.1.c 'Manufacture of Solid Fuels and Other Energy Industries' are the emissions coming from the combustion in the coke ovens. Only the total Belgian CO₂ emissions are reported in this category. The emissions of the other pollutants are reported in the category 1.A.2. in Flanders (except for the CH₄-emissions which are reported in category 1.B.1.b.). In Wallonia and Brussels, the emissions of other pollutants are reported in category 1.A.1.c, but the CH₄

emissions are in fact negligible and the N₂O emissions are rather small. The fugitive emissions are reported in category 1.B.1.b.

3.1.2 Industry

The following industries are integrated in category 1.A.2.f (Other): non-metallic mineral products, (cement, lime, asphalt concrete, glass, mineral wool, bricks and tiles, fine ceramic materials), metal products, textile, leather and clothing and other industry (wood industry, rubber and synthetic material, manufacturing of furniture, recycling and construction included).

The urban environment of the Brussels region does not satisfy the establishment of the great surfaces required by industry. With the exception of a manufacturer of cars, the Brussels industry is made up of small and very small manufactures with high added value or close to the ultimate consumer. All these “industries” are integrated in category 1.A.2.f (Other).

3.1.3 Transport

Belgium is provided with a very dense road (4.7 km/km²) and rail (112 m/km²) network. These densities of road and rail networks should be looked at in conjunction with the very high density of population in Belgium : relative to the number of inhabitants the infrastructure is close to the European average. The port of Antwerp is very important for Belgium. It is the second largest European seaport, and one of the 5 largest in the world. The port of Antwerp benefits from excellent connections to the hinterland and the large French and German industrial basins by waterway (1500 km of navigable routes). It has also been decided to strengthen the rail infrastructure giving access to the port of Antwerp. Road transport is the mean of transport the most generally used in Belgium, both for the transport of goods and passengers, generating severe traffic congestion. Even though congestion is lower than in the neighbouring countries, the number of road accident victims is very high, but is going down. Damages to the environment resulting from fuel use in road traffic are considerable. Goods are transported, on average, over a longer distance by railway (125.3 km in 1998) than by navigable waterways (58.4 km), but the gap between these two modes of transport has lessened in recent years.

Since the submission in 2004, the CO₂ emissions for road transport are based on fuels sold. These figures are originating from the Belgian energy balance of fuels sold. Emissions of CH₄ and N₂O are not calculated based on the Belgian energy statistics, but are the sum of the emissions calculated by the 3 regions using a methodology based on the COPERT methodology in the Walloon and Brussels region and a country-specific methodology (the so-called MIMOSA-model see also section 1.3.1) for the Flemish region.

3.2 Methodological issues

Greenhouse gas emissions are mostly reported directly by the individual large companies on the basis of their fuel consumption. For most sectors the remainder of the emissions is calculated on the basis of the remaining fuel consumption (estimated as the difference between energy consumption reported in the regional energy statistics for the whole sector and the fraction reported by the large companies) and standard emission factors. The emission factors of CO₂ are the same for all sectors and are listed below. In these emission factors of CO₂ the IPCC default oxidation factors are already adjusted. These oxidation factors take into account that not 100% of the carbon in the fuel is transmitted to CO₂. This factor is 0.98 for solid fuels and 0.99 for liquid and 0.995 for gaseous fuels.

Products	emission factors (g CO ₂ /MJ)		
	Flanders	Wallonia	Brussels
coal tars	92,7	-	
coking coal	92,7 ⁽⁶⁾	92,7 99,2	92.7
Brown coal/lignite			
coke oven coke	106,0	106 ⁽³⁾	
crude oil	72,6	-	
Refinery gas	55,1 - 56,5 ⁽¹⁾	-	
LPG	62,4	-	
Gasoline	68,6	-	
Kerosene	70,8	-	
gas/diesel oil	73,3	73,3	73.3
lamp petroleum	71,1	-	
residual fuel oil	76,6	76,6	76.6
Naphta	72,6	-	
petroleum coke	99,8	99,8	
other petroleum	72,6	-	
natural gas	55,8	55,8	55.8
coke oven gas	47,4	47,4	47.4
blast furnace gas	258-260 ⁽⁵⁾	256,8-264,3 ⁽⁴⁾	
other products	⁽²⁾	-	
biogas	-	75 ⁽³⁾	
Waste gas	-	66-72,5 ⁽³⁾	
Industrial waste	-	86,6 ⁽³⁾	
Black liquor	-	100 ⁽³⁾	
wood	-	100 ⁽³⁾	

Table 3.1. : Emission factors used to calculate energy related emissions of CO₂ (IPCC default unless indicated).

⁽¹⁾ Inquiry with the refineries

⁽²⁾ Depending on the product in question, information through inquiries with the companies involved or default

⁽³⁾ Source: EMEP/CORINAIR

⁽⁴⁾ Country specific emission factors⁽⁵⁾ Inquiry with the electricity sector and iron and steel sector

⁽⁶⁾ The default IPCC value, this is not used for the large power plants

In the lime and cement plants, the CO₂ emission factors originates from the IPCC 1996 Guidelines.

Fuel		UNIT	CO ₂ x 10 ³
Fuel	cement	g/GJ	78 ^c
Diesel oil	cement	g/GJ	74 ^c
Coal	cement	g/GJ	92,7-105
Petroleum coke	cement	g/GJ	96
Industrial waste	cement	g/GJ	75-102
Gas naturel	cement	g/GJ	56 ^c
Coal	Lime	g/GJ	92,7-105
Industrial waste	Lime	g/GJ	88
Coke	Lime	g/GJ	100 ^c
Fuel	Lime	g/GJ	77,2 ⁱ
natural gas	Lime	g/GJ	55,8 ⁱ

Table 3.2. : Emissions factors per fuel in lime and cement plants.
(Source : IPCCⁱ and EMEP/CORINAIR^c)

3.2.1 Energy industries (category 1.A.1)

Public electricity and heat plants (category 1.A.1.a)

CO₂

The activity data are collected from energy statistics and from surveys of the individual companies. The number of companies is limited and well known. For the large power plants in the public electricity sector, the CO₂ emissions are reported that are directly given by the power plants and based on analyses of the fuels (in Flanders this is the case since the submission in 2005, before the default IPCC emission factors for CO₂ were used in Flanders).

For the smaller plants for which no emissions of CO₂ are reported directly to the responsible authorities, default CO₂ emission factors are used except for specific fuel types. In that case more detailed information of the individual companies is used (see table 3.1). In the Brussels region there is only one significant power plant. The electricity used is produced from the municipal waste incineration. The CO₂ emission factor from EPA is used. The fraction of organic municipal waste has been deduced from analyses of dustbins [37 and 48] and have led to a fraction of biomass origin, variable for the whole time-serie, from 62 % to 53 %. For the smaller plants in Brussels, default CO₂ emission factors are used (see table 3.1).

CH₄ and N₂O

In Flanders, emission factors from TNO (Netherlands) [4] (Table 3.3) are now used to calculate the emissions of N₂O for the installations for public electricity and from the EMEP/CORINAIR handbook (table 27) [3] to calculate the emissions of CH₄. These emission factors are agreed with the electricity producers.

In Wallonia and in Brussels, emissions of CH₄ and N₂O are calculated using emission factors of the IPCC Guidelines.

Fuel	UNIT	CH ₄			N ₂ O		
		F1 (1)	Wall (2)	Br (2)	F1 (3)	Wall (2)	Br (2)
Coal	g/GJ	0,6	1	/	1,40	1.40	/
Fuel	g/GJ	0,7	3	/	0,60	0.60	/
diesel oil	g/GJ	0,3	1,5	/	0,60	0.60	/
natural gas (in gas turbine)	g/GJ	2.5	2,5	2.5	0,10	0.10	0.1
natural gas	g/GJ	0.1	1	/	0,10	0.10	/
Cokesgas	g/GJ	0,1	1	/	0,10	0.10	/
blast furnace-gas	g/GJ	0,1	1	/	0,10	0.10	/
H ₂ -gas	g/GJ	0,00	-	/	0,00	-	/
Dry sludge	g/GJ	0,6	-	/	1.4	-	/
Bisfenol-resin	g/GJ	0,6	-	/	0,60	-	/
Agricultural waste	g/GJ	-	30	/		4	/
Municipal waste				-	60 g/ton (1)		60 g/ton (1)

Table 3.3 : Emission factors of CH₄ and N₂O for the sector 1.A.1.a Public electricity and Heat Production.

- (1) Source: CITEPA
- (2) Source: IPCC
- (3) Source : TNO

Petroleum refining (category 1.A.1 b)

As indicated in section 3.1.1. petroleum refining only occurs in Flanders. The emissions of CO₂ are reported to the responsible authorities by the Belgian Petroleum Federation and the petroleum refining companies and since the submission of 2004 these emissions are included in the inventory.

CH₄ and N₂O emissions from petroleum refining are calculated using a combination of monitoring results (for the 2 largest companies) and emission factors of CITEPA [2] for the smaller companies. These emission factors are based on the input of crude oil :

- 0.24 g CH₄/ ton crude oil originating from 6% auto-combustion *4 g CH₄/ton crude oil;
- 22 g N₂O/ton crude oil originating from 6% auto-consumption and an emission factor of 9g/GJ (50% fuel oil and 50% gas);
- To calculate the fugitive emissions an emission factor of 5 g CH₄ / ton crude oil is used.

Compared to previous submission, a small correction is made on the activity data (input of crude oil) from 1990 on.

The results of the monitoring of the emissions of CH₄ and N₂O in 2004 became available in 2005 only for 2 companies exceeding the threshold value (10 ton/year for N₂O and 100 ton/year for CH₄). Based on these results, the emissions of CH₄ and N₂O were revised from 1990 on (partly monitoring and partly extrapolation) and actualized emissions for the complete time series were included in the inventory.

All CH₄-emissions of this sector are allocated in category 1.B.2.a and all N₂O-emissions are allocated in category 1.A.1.b because of the diffuse character of the CH₄-emissions.

Manufacture of solid fuels and other energy industries (category 1.A.1.c)

As indicated in section 3.1.1, the emissions originating from category 1.A.1.c ‘Manufacture of Solid Fuels and Other Energy Industries’ are the emissions coming from the combustion in the cokes ovens. In Wallonia, in the category 1.A.1.C the emission factors for CO₂ and CH₄ are those proposed in the EMEP/CORINAIR guidebook and the IPCC Guidelines [24]. The emission factor for CO₂ for the blast furnace gas is given directly by the power plant. For N₂O, emission factors from the Table 1.8 of the Revised 1996 IPCC Guidelines [28] are used.

Fuel	UNIT	Wallonia	
		CH ₄	N ₂ O
Diesel oil	g/GJ	1,5 ⁽²⁾	0,60 ⁽¹⁾
natural gas	g/GJ	2,5 ⁽²⁾	0,10 ⁽¹⁾
Coke oven gas	g/GJ	1 ⁽²⁾	0,10 ⁽¹⁾
blast furnace-gas	g/GJ	0,16(2)	0,10 ⁽¹⁾

Table 3.4. : CH₄ and N₂O emissions factors per fuel in the coking works.

(1) Source: IPCC

(2) Source: EMEP/CORINAIR

There was a coke plant in the Brussels region until 1993. The emission factors used, are the same as the ones used in Wallonia (except CH₄ from EPA).

In Flanders the emission factors used to calculate the emissions of CO₂ are included in table 3.1. The calculation and the allocation of the emissions of CH₄ is done in a different way in Flanders. These CH₄-emissions are allocated in the category 1.B.1.b (see this section for more explanation of the methodology used). Contacts with the relevant industry in Flanders indicates that no emissions of N₂O occurs in this sector.

3.2.2 Manufacturing industry and construction (category 1.A.2)

CO₂

General

The energy consumption data originate from the regional energy balances in the 3 regions, supplemented with specific information from the companies themselves, for example activity data from iron and steel industry.

To calculate the emissions of CO₂, the emission factors listed in table 3.1 are used.

Iron and steel sector

The CO₂-emissions from the iron and steel sector are partly put in category 1.A.2.a (energetic part / except for the emissions from the cokes ovens which are allocated in the category 1.A.1.c) and partly in category 2.C.1 (process part).

In Wallonia, the CO₂ emissions from the blast furnace are calculated by a CO₂ balance :

CO₂ from “fuel inputs and reducing agents” – CO₂ from “blast furnace gas used for energy purposes” – CO₂ in “pig iron”.

The CO₂ emissions from the blast furnace gas used are included in the category where the energy is used.

Other sectors

In the lime and cement plants, the CO₂ emission factors as presented in table 3.2 are used (activities take place only in the Walloon region).

CH₄ and N₂O

General

The emissions of CH₄ and N₂O in Flanders are calculated using emission factors originating from CITEPA [2] (Table 3.5).

The emission factors used to calculate the emissions of CH₄ and N₂O in Wallonia are based upon those proposed in the EMEP/CORINAIR guidebook and the Revised IPCC Guidelines.

In the Brussels region, a specific study has been funded on behalf of the IBGE-BIM [12] to determine the emission factors to take into account specific socio-economic conditions in Brussels.

			Flanders (1)	Wallonia	Brussels (4)	Flanders (1)	Wallonia	Brussels (4)
Fuel	Boiler	Unit	CH₄			N₂O		
Coal		g/GJ	0.27	10 ⁽²⁾	1.5	12.3	1,4 ⁽²⁾	3
Coke oven gas		g/GJ	0.5	1 ⁽²⁾		3	0,1 ⁽²⁾	
coke		g/GJ	-	10 ⁽²⁾		-	4 ⁽²⁾	
Natural gas	>50MW	g/GJ		1 ⁽²⁾				
	<50MW		0.3	4 ⁽³⁾	2.5	3	0,1 ⁽²⁾	1,5
blast furnace-gas		g/GJ	0.5	1 ⁽²⁾		3	0,1 ⁽²⁾	
Fuel	>50MW	g/GJ		3 ⁽²⁾				
	<50MW		0.1	2 ⁽²⁾	3	13.4	0,6 ⁽²⁾	14
Diesel oil	>50MW	g/GJ		1,5 ⁽²⁾				
	<50MW		0.1	2 ⁽²⁾	1	13.4	0,6 ⁽²⁾	12
Biogas	< 50MW	g/GJ	-	4 ⁽³⁾		-	0,1 ⁽²⁾	
Waste gas	<50MW	g/GJ	-	2,5 ⁽³⁾		-	0,1 ⁽²⁾	
Industrial waste	<50MW	g/GJ	-	10 ⁽³⁾		-	2 ⁽³⁾	
Black liquor	< and >	g/GJ	-	15 ⁽³⁾		-	0,6 ⁽²⁾	
Wood	< and >	g/GJ	-	30 ⁽²⁾		-	4 ⁽²⁾	

Table 3.5. : Emission factors of CH₄ and N₂O in the sector 1.A.2 Manufacturing Industries and Construction.

- (1) Source : CITEPA
- (2) Source: IPCC
- (3) Source: EMEP/CORINAIR
- (4) Specific study IBGE-BIM [12]-Corinair

Iron and steel sector

For iron and steel plants in Wallonia following CH₄ and N₂O emission factors are used :

Fuel		UNIT	CH ₄	N ₂ O
Coke breeze	Sinter and pelletizing plants	g/GJ	50 ⁽²⁾	4 ⁽¹⁾
Coke oven gas	Sinter and pelletizing plants	g/GJ	257 ⁽²⁾	0.1 ⁽¹⁾
natural gas	Blast furnace	g/GJ	2,5 ⁽²⁾	0.1 ⁽¹⁾
Coke oven gas	Blast furnace	g/GJ	57 ⁽¹⁾	0.1 ⁽¹⁾
blast furnace-gas	Blast furnace	g/GJ	112 ⁽¹⁾	0.1 ⁽¹⁾
Coal	Electric arc furnace	g/GJ	15 ⁽²⁾	1,4 ⁽¹⁾
Coke breeze	Electric arc furnace	g/GJ	15 ⁽²⁾	4 ⁽¹⁾
Natural gas	Electric arc furnace	g/GJ	2,5 ⁽²⁾	0.1 ⁽¹⁾
natural gas	Reheating furnaces steel and iron	g/GJ	2,5 ⁽²⁾	0.1 ⁽¹⁾

Table 3.6. : CH₄ emissions factors for the different fuels in the iron and steel plants in Wallonia.

- (1) Source: IPCC
- (2) Source: EMEP/CORINAIR

The consumption of coal not used as a reducing agent in the blast furnace is calculated by a CO₂ balance on the furnace in Wallonia and the emissions are reported in this section. Only CO₂ emissions are calculated.

In Flanders the emissions of CH₄ of the iron and steel sector are allocated in the categories 1.B.1.b (production of cokes) and 2.C.1 (production of sinter) (see these respective sections for more explanation of the methodology used).

Other sectors

The emission factors are those proposed in the EMEP/CORINAIR guidebook for CH₄ and the IPCC factors for N₂O.

Fuel	UNIT	CH ₄	N ₂ O
Fuel	g/GJ	3	0,6
Diesel oil	g/GJ	1,5	0,6
Natural gas	g/GJ	2,5	0,1

Table 3.7. : Emissions factors per fuel in glass production (EMEP/CORINAIR and IPCC)

2) In the lime and cement plants (activities which only take place in the Walloon region), the emissions of CH₄ and N₂O are plant-specific and determined by measurement. Implied emission factors for CH₄ and N₂O are then derived from the energy consumption data and the reported emissions.

3.2.3. Transport (category 1.A.3 and 1.A.5.b)

Road transport

The energy consumption and CO₂ emissions for road transport are based upon federal (Belgian) energy statistics. The activity data (combustion figures) represent the amount of fuels sold in Belgium for road transport. These activity data are multiplied with default IPCC emission factors to calculate the CO₂ emissions. Emissions of CH₄ and N₂O are calculated by compiling the emissions of each region based on the use of the specific models used in the 3 regions (based on COPERT III in the Walloon and the Brussels region and on the MIMOSA-model in the Flemish region).

Air transport

In the two regions (Flemish and Walloon region) where air transport is relevant, a slightly different approach was taken in estimate the emissions from air transport.

In Flanders, concerning air transport, only domestic air traffic is considered for calculating the CO₂ emissions. All kerosene used in air transport is assigned to the bunker fuels, all gasoline for air transport is allocated to domestic air transport. This approach was chosen because it is not easy to split these fuels otherwise and because, due to the small size of Belgium (and Flanders), most kerosene is used for international transport. A default IPCC emission factor for CO₂ is used to calculate the emissions. CH₄ and N₂O emissions from air transport are calculated for the Landing and Take-Off cycle. The methodology is mainly based on the methodology described in the EMEP/CORINAIR handbook [3]. These emissions are calculated for 3 airports for civil aviation (Antwerp, Ostend and the international airport of Brussels-National) and for 5 airports for military aviation (Kleine Brogel, Brasschaat, Koksijde, Sint-Truiden and Goetsenhove).

In Wallonia, the emissions from civil aviation (category 1.A.3.a) are estimated on the basis of the number of LTO in two airports (Liège and Charleroi), following a very simple methodology described in the EMEP/CORINAIR guidebook [3]. Some information on the country's total number of LTO is available. Unfortunately, there is no general knowledge about the aircraft types carrying out the aviation activities. 58 % of the LTO are supposed to be domestic flights. A distinction is also made between emissions from domestic and international LTO and cruise activities. Emissions factors used to estimate emissions from domestic and international traffic are based on the table 8.2 in the EMEP/CORINAIR guidebook [3]. The emissions from domestic LTO and cruise activities are reported under the category 1.A.3.a (civil aviation), while emissions from international LTO and cruise activities are reported under "international bunkers : aviation". Kerosene used in international airtransport is assigned to the bunker fuels. Data on LTO activities and fuel consumption in the airports of Charleroi and Liège come from the statistics of these airports.

Railways

The greenhouse gas emissions from the railway traffic is estimated for the 3 regions in the same way:

In Flanders, the fuel consumption is based on a proportional fraction of fuel used in Belgium for rail transportation. Default IPCC emissions factors are used for CO₂ (table 3.1). The emissions of CH₄ and N₂O are calculated by using the activity data (fuel consumption) of the regional energy balance combined with emissions factors of the EMEP/CORINAIR handbook [3]. These emission factors are the same as the emission factors from the IPCC Revised 1996 guidelines. Other emissions are calculated with the results of a model developed by the Vito [1] and based on the registered kilometres with distinction between different types of trains.

The emissions from railways are estimated in the Walloon region and in the Brussels region by multiplying the train's fuel consumption [21 and 11] by the fuel specific emission factors. For CO₂, the emission factors used are those as indicated in table 3.1. For CH₄ and N₂O, the specific emission factors are those described in table 8.1 of the EMEP/CORINAIR guidebook [3]

Navigation

For navigation, fuel consumption is taken from the regional energy balances.

Fuel consumption is multiplied with a CO₂ default emission factor (see table 3.1).

In Flanders statistics are used to calculate the total freight kilometres and to calculate the total amount of fuel used.

During this submission the emissions of CH₄ and N₂O in Flanders are optimized by using the results of a so-called susatrans-model which is developed by the Vito [1] and technology-related. This methodology gives a more accurate estimation of the emissions compared to the use of IPCC default emission factors until the previous submission.

Other emissions in Flanders are calculated with this same model developed by the Vito [1].

In the two other regions, other emissions are calculated using emission factors of the EMEP/CORINAIR handbook [3].

Other transportation

In this category 1.A.3.e. the energetic emissions originating from the compression activities in the sector storage and transport of natural gas. The emissions of CO₂ are estimated by using the default emission factors (table 3.1). In the Flemish region the emissions of CH₄ en N₂O are calculated by using the same emission factors as these used in the sector 1.A.2. 'Manufacturing industry and construction' (see section 3.2.2).

3.2.4 Other sectors (category 1.A.4)

The fuel consumption of the service sector is based on general statistics of natural gas, supplemented with results from surveys for solid and liquid fuels. Agricultural fuel consumption is estimated from statistical information concerning area used, etc., combined with specific energy consumption from literature. The energy consumption of these sectors is published in the regional energy balances. The used default emission factors for CO₂ are listed in table 3.1.

The category 1.A.4.c Agriculture/Forestry/Fisheries is negligible in the Brussels region. As a consequence no greenhouse gases from this sector are taken into account for this region.

In table 3.8 below, the emission factors for CH₄ are listed.

Fuel		Unit	Flanders	Wallonia	Brussels
			CH ₄		
Coal	Commercial	g/GJ	10 ⁽¹⁾	10 ⁽²⁾	/
	residential	g/GJ		300 ⁽²⁾	200 ⁽⁴⁾
	Agriculture heating	g/GJ	0,3 ⁽¹⁾	-	/
Natural gas	Heating	g/GJ	1 ⁽¹⁾	5 ⁽²⁾	5 ⁽⁴⁾
	Heating agriculture	g/GJ	0,3 ⁽¹⁾		/
Fuel/diesel oil	Heating	g/GJ	3 ⁽¹⁾	10 ⁽²⁾	7 ⁽⁴⁾
	Heating agriculture	g/GJ	0,1 ⁽¹⁾		/
	Farming vehicles.	g/GJ	4 ⁽²⁾	4 ⁽³⁾	/
Fuel	Fishing activities	g/GJ	5 ⁽²⁾	-	/
Heavy fuel	Commercial	g/GJ	3 ⁽¹⁾	-	3 ⁽⁴⁾
	residential				
	Agriculture heating		0.1 ⁽¹⁾		
Propane/butane/		g/GJ	0 ⁽¹⁾	-	0 ⁽¹⁾
Lampptroleum	Commercial	g/GJ	3 ⁽¹⁾	-	/
	residential				
	Agriculture heating		0.1 ⁽¹⁾		
wood		g/GJ	150 ⁽¹⁾	300 ⁽²⁾	300 ⁽⁴⁾

Table 3.8. : Emission factors of CH₄ for category 1.A.4 Other sectors (households and service sector).

- (1) source: Citepa
- (2) source: IPCC
- (3) EMEP/CORINAIR
- (4) Specific study on behalf of IBGE-BIM [12]-Corinair

In table 3.9 below, the emission factors for N₂O are listed.

Fuel		Unit	Flanders	Wallonia	Brussels
			N ₂ O		
Coal	Heating	g/GJ	12 ⁽¹⁾	1,4 ⁽²⁾	12 ⁽⁴⁾
	Agriculture heating	g/GJ	14 ⁽¹⁾	-	/
Natural gas	Heating	g/GJ	2 ⁽¹⁾	0,1 ⁽²⁾	2 ⁽⁴⁾
	Heating agriculture	g/GJ	3 ⁽¹⁾		/
Fuel/diesel oil	Heating	g/GJ	12 ⁽¹⁾	0,6 ⁽²⁾	12 ⁽⁴⁾
	Heating agriculture	g/GJ	14 ⁽¹⁾		/
	Farming vehicles.	g/GJ	30 ⁽²⁾	30 ⁽³⁾	/
Fuel	Fishing activities	g/GJ	0,6 ⁽²⁾	-	/
Heavy fuel	Heating	g/GJ	12 ⁽¹⁾	-	14 ⁽⁴⁾
	Agriculture heating		14 ⁽¹⁾		
Propane/butane/		g/GJ	3 ⁽¹⁾	-	2 ⁽⁴⁾
Lampptroleum	Heating	g/GJ	12 ⁽¹⁾	-	/
	Agriculture heating		14 ⁽¹⁾		
wood		g/GJ	4 ⁽¹⁾	4 ⁽²⁾	4 ⁽⁴⁾

Table 3.9. : Emission factors of N₂O for category 1.A.4 : Other sectors (households and service sector).

- (1) source: Citepa
- (2) source: IPCC
- (3) EMEP/CORINAIR
- (4) Specific study on behalf of IBGE-BIM [12]-Corinair

3.2.5. Other (category 1.A.5.a and 1.A.5.b)

In this section the emissions originating from the military transport (domestic air transport) are included (category 1.A.5.b). These emissions are calculated in the same way as explained in section 3.2.3.

No activities under category 1.A.5.a take place in Belgium.

3.2.6. Fugitive emissions from fuels (category 1.B.1 and 1.B.2)

Solid fuel transformation (category 1.B.1.b)

Emissions during the cokes production are caused by the loading of the coal into the ovens, the oven/door leakage during the coking period and by extracting the coke from the ovens. Emissions of CH₄ originating from the production of cokes were estimated in Flanders until the previous submission by using emission factors of CITEPA [2], which are in line with the emission factors of the EMEP/CORINAIR handbook (400 g CH₄/ton cokes).

During this submission a revision of the emissions of CH₄ was carried out due to the availability of more detailed information of the industry involved. Based on monitoring results carried out in 2001, 2002 and 2004, the emissions of CH₄ were optimized from 1990 on.

In Wallonia and Brussels, the CH₄ emissions are estimated with the emission factor of the EMEP/CORINAIR handbook (400 g CH₄/ton cokes).

Activity data (tons of cokes) are delivered by the corresponding industry.

Petroleum refineries (category 1.B.2.a)

Estimation of the emissions of CH₄ and N₂O from the sector petroleum refining occurs as mentioned in section 3.2.1.: CH₄- and N₂O-emissions from petroleum refining are calculated using a combination of monitoring results (for the 2 largest companies) and emission factors of CITEPA [2] for the smaller companies. All CH₄-emissions of this sector are allocated in category 1.B.2.a and all N₂O-emissions are allocated in category 1.A.1.b because of the diffuse character of the CH₄-emissions.

Gas distribution (category 1.B.2.b)

The methodology to calculate the emissions of CH₄ originating from the gas distribution (category 1.B.2.b ii/distribution) is completely optimized since the submission in 2004 for all the regions in Belgium. These emissions are determined on the basis of the length of gas distribution pipelines. The lengths of the main pipelines (exclusive additional pipelines which are pipelines going to households) per public utility board are available. The number of additional pipelines in Flanders is estimated at 1

500 000 for the year 2003 and this with an increase of 24 000 every year. In Wallonia, it's estimated at 588 458 for the year 2002. The length per additional pipeline measures 5 m. In Brussels, the number of additional pipelines is estimated at 183 325 for the year 2003 and the average length is 3m (urban environment). Depending on the material of the pipeline other emission factors are used. In particular 869, 7865, 869 and 95 m³/y/km for respectively steel, cast iron, fibre cement and synthetic material. The density of methane is 0,716 kg/m³. The methane content of natural gas distributed is 85 %. For each material the length of the pipelines is multiplied by its emission factor. This results in de total natural gas emission in m³ per year. Multiplying this figure by the methane content and the density of methane we obtain the methane emission originating from gas distribution. Based on the composition of the natural gas, emissions of CO₂ from the gas distribution are newly calculated in the Flemish region and added to the inventory (natural gas contains +/- 1% of CO₂) in category 1.B.2.bii/distribution.

Emissions of CH₄ (category 1.B.2.b.ii/transmission) originating from the storage and transport of natural gas in Belgium are calculated and added to the inventory since the previous submission. Before the emissions were estimated only for the years 1990 and 2003 by Fluxys (independent natural gas transport company) and the emissions for the others years were approximated by a linear regression. During this submission, the emissions became available by this transport company for the intermediate years as well and are included in the greenhouse gas inventory. These emissions are estimated on the basis of measurements and calculations (taken into account pressure, distance, volume) carried out . All necessary interventions in case of problems are known and the amounts of gas blown off is registered as accurate as possible.

The activity data reported for the category 1.B.2.b is the annual total natural gas amount, consumed in Belgium.

3.2.7. International bunkers (category Memo Items – International Bunkers)

Marine bunkering comes from the Belgian energy statistics.

The emissions of CH₄ and N₂O of the marine bunkers are newly calculated during this submission by using emission factors of CITEPA [2], the same factors are used as these used in the category 1.A.2.(see section 3.2.2).

For international air transport, bunkers fuel consumption of the international air transport is given directly by the two Walloon airports. For the airports in Flanders, the reported kerosene fuel is assigned to the bunker fuels and all gasoline for air transport is allocated to domestic air transport (see justification of this approach in the section 3.2.3). Default emission factors to calculate the CO₂ emissions for all products are used (see table 3.1).

3.2.8. CO₂ emissions from biomass

Emissions of CO₂ from biomass are presented in CRF table 1s2. The emissions of CO₂ reported in this table are estimated as good as possible, depending on the information (activity data) available in the different regions in Belgium. These emissions are probably not complete.

3.2.9. Non-energy use of fuels and related emissions (categories 1.A.2, 2.B and 2.G)

The emissions of non-energy use of fuels and related emissions (emissions from recovered fuels from processes) are reported under categories 1.A.2, 2.B.1, 2.B.5 and 2G.

In Flanders, a recalculation of the non-energy use and related CO₂ emissions was performed for the previous NIR 2005, based on the results of a study conducted in 2003 [43]. The default % of carbon stored in the IPCC Guidelines were considered to be inaccurate in the Flemish situation. The default %

of carbon stored in the 1996 IPCC guidelines are not well defined: it is not clear what is included or excluded in these default % (f.i. is the waste phase included or not?). Belgium participated in a European network on the CO₂-emissions from non-energy use (see website <http://www.chem.uu.nl/nws/www/nenergy/>) and one of the conclusion of this network is that the new IPCC guidelines need to give more info on this subject.

To our opinion, the guidelines are also not very clear on the allocation of the resulting emissions: in table 1.A(d), as part of the reference approach, in the documentation box a country should specify where these emissions are allocated. This problem of allocation had to be tackled also.

Since the petrochemical industry is important in Flanders (and Belgium) and the emissions from feedstocks are a key source in the Belgian inventory, the study was conducted to get more detailed, country-specific information. A distinction was made between :

1. The use of recovered fuels from cracking units or other processes where a fuel is used as a raw material and where part of this fuel (or transformed product) is recovered for energy purposes (these are reported under 1.A.2 c 'other fuels'). This is the largest source of CO₂ emissions. The involved industry was asked to report CO₂ emissions and PJ directly for these recovered fuels.
2. CO₂ emissions occurring during chemical processes, for example the production of ammonia based on natural gas or the production ethylene oxide where CO₂ is formed in a side reaction (reported respectively under 2.B.1 and 2B.5 other). The industry involved is reporting these CO₂ emissions directly for these processes.
3. Use of products as solvent or lubricants (reported under 2G as 'non-energy use'). The best possible estimation of emissions of CO₂ is made for this sector. This source is the least important one in order of magnitude.
4. Waste treatment of final products is not included in the study. This is practically impossible due to import/export of plastic products, etc (it is also not clear if the waste phase is included in the default IPCC carbon stored % or not). The emissions of waste incineration are therefore calculated separately and are reported under the sector of waste (category 6.C) or under the sector of energy (category 1.A.1.a), whether or not energy recuperation takes place during the process.

The result of the study made a recalculation possible for all years. The effect of the recalculation was greater in the more recent years because the petrochemical industry has expanded its activities in the beginning of the nineties (that's one of the reasons this sector is a key source).

The resulting emissions are reported under different sections. The first and largest part (recovered fuels) of the resulting emissions is reported under 1.A.2 c, under 'other fuels'. This includes other fuels in the chemical sector, a result of recovered fuels in the steam cracking units in petrochemical industry (approx. 2/3) and other recovered fuels from the chemical industry (approx. 1/3). These recovered fuels are reported directly in the yearly surveys carried out by the chemical federation in cooperation with the Vito [1] to establish a yearly Flemish energy balance. The choice was made to allocate these fuels under 'other fuels' and not 'liquid fuels' or 'gaseous fuels', for transparency reasons.

Another part of the emissions surveyed in the study, are considered to be process emissions and are reported under 2.B. These include the CO₂-emission during the production of ammonia (2.B.1) and other process CO₂ emissions (2.B.5) reported by the chemical industry in Flanders (for example production of ethylene oxide, production of acrylic acid from propene, production of cyclohexanone from cyclo-hexane, production of paraxylene/meta-xylene, etc). These CO₂ emissions result from the same surveys in the chemical sector in Flanders as those reported under 1.A.2.c. In the survey, more sources of emissions from chemical processes are reported than are described in the IPCC 1996 guidelines.

A small part of non-energy use is still calculated using the default IPCC emission factors (mostly use of lubricants and solvents). These emissions are reported under 2.G. and include also the use of these products in some other sectors than the chemical industry. The emissions are based on an estimate of the use of these products in Flanders and in Wallonia, multiplied with an emission factor and the default % of carbon stored of other petroleum products. These emissions are rather small.

3.3.Reference approach

CO₂ emissions from fuel combustion were estimated in accordance with the “Reference Approach” (Tier 1 Approach – IPCC Guidelines). This estimation is based on the national energy balance, which is derived from national statistics of fuel supply. Default values recommended in the IPCC guidelines were adopted for carbon emission factors, fraction of carbon oxidised, and fraction of carbon stored (feedstock’s). The details of this estimation are provided in the CRF tables 1.A(b), 1.A(c), 1.A(d) for all years.

The comparison with the sectoral approach (Table 1.A(c)) shows a differences between -2,82% (in 2004) and +6,90% (in 2000). The difference between the reference approach and the national inventory for all years is visualised in the next figure.




Figure 3.1. : Difference between the Reference approach and the national inventory.

There can be several reasons why there is a difference between the results of the reference approach and the national inventory and also why the difference seems to be getting larger.

Reason number 1: The results for the reference approach and the national inventory are based on different data sets which show different results

The IPCC Reference Approach is ‘top-down’, based on statistics of production, imports, exports and stock changes of fuels from federal statistics. The Federal Energy balance is based on transparent and statistical rules and elaborated according to the rules of International institutions (common questionnaire IEA, Eurostat, United Nations). For the petroleum sector, data are directly asked from all petroleum operators working on Belgium territory via a common questionnaire (Federal Energy Administration and NIS=National Institute of Statistics). In addition, the questionnaire sent to all petroleum operators was validated by the NIS. However, presently the federal government is working

on improving their petroleum statistics, which includes an extension of the number of actors that are obliged to fill out the questionnaires.

The national inventory is based on a ‘bottom-up’ approach that uses fuel consumption data from regional energy balances based on information from plants or studies with extrapolation, models and surveys. The work is done in close cooperation with professional federations and individual companies.

A significant proportion of the discrepancy between the IPCC Reference Approach and the ‘bottom up’ approach arises consequently from these differences in methodology between federal and regional energy balances and in the difference in collecting data particularly with solid and liquid fuels.

This problem of inconsistency between regional and national energy balances is well known for several years, and continuous efforts are made in order to harmonise the methodologies used by the different institutions. During 2002, a study was conducted to examine the differences between the national top-down energy balance, and the sum of the regional bottom-up balance. The year of investigation was 1999 [38].

The main objectives of the study were :

- To compare the sum of the three regional balances with the federal balance
- To highlight the most significant differences between the two methodologies
- To propose some leads for improvement

The main results and conclusions of the study show :

- The two approaches are different. The federal balance is a supply balance, the regional balance is a consumption balance
- Some problems remain in the housing and the transport sectors (work is currently going on to solve them, by adding some information to the questionnaires, allowing a further disaggregation of the federal balance)
- The main problem stems from oil and the different petroleum products; in particular, the biggest problem is due to the non-energy use of oil (naphta for the petrochemistry, only in Flanders).

In the figure below, the evolution of the consumption of naphta in the petrochemical industry is shown, based on the federal petroleum balance and based on data received from industry itself in the Flemish energy balance.




Figure 3.2. : Evolution of the consumption of naphta in the petrochemical industry in Belgium based on the federal energy balance and of the consumption in Flanders, based on data used in the Flemish energy balance from the industry itself.

In 1990, there were only 2 steam cracking units which used naphta as input. In 1992, a third unit was put into operation, followed by a 4th in 1994. In the Flemish energy balance, data for these units are made available by the industry itself. It seems that from a certain point in time, not all naphta is included in the statistics made up by the federal government. In 1990, the difference in the datasets was 14 PJ, in 2004 the difference is almost 162 PJ.

In the following figure, the total results are shown as the difference between federal energy balance and the sum of the regional balances.




Figure 3.3. : Differences per energy sources in the global balances (values 1999 in ktce NCV) [38].

In percentage, the total federal energy balance shows an energy use of 3% less than the sum of the regional energy balances.

In 2003, a working group under the National Climate Commission was installed, to further the work of harmonizing the different energy balances as far as possible. The work is still ongoing.

Reason number 2: Methodology of reference approach – effect of liquid fuels

The IPCC Reference Approach uses data on primary fuels such as crude oil and natural gas liquids, which are then corrected for imports, exports and stock changes of secondary fuels. Thus the estimates obtained will be highly dependent on the conversion factors and the default carbon contents used for the primary fuels. The ‘bottom-up’ approach is based completely on the consumption of secondary fuels where the carbon contents are known with greater certainty. In particular the carbon contents of the primary liquid fuels are likely to vary more than those of secondary fuels.

In Belgium, the apparent consumption is made up of about 50% of liquid fuels. A preliminary analysis was made on the reference approach of 2001, where the uncertainty on the apparent consumption of liquid fuels in tonnes, on the conversion factors from tonnes to TJ and on the emission factors was chosen to be 1% (95% uncertainty interval, normal distribution). The effect on cell O29 of table 1.A(b) = ‘carbon content of liquid fossil fuels total’ was studied.




Figure 3.4. : Sensitivity chart for the ‘total carbon content of liquid fuels total’ in 2001, based on certain assumptions on tonnes of liquids consumed, conversions factors to TJ and carbon content.

Only 2 factors are important in the calculation of the carbon content of the liquid fossil fuels consumed: the total tonnes of apparant consumption of crude oil and its carbon content. An uncertainty of 1% in both, can cause the value (95% interval) of the total carbon content of the fossil fuel to lie between 18,3 or 20,9 Mton C (calculated value is 19,5 Mton C). This means that the uncertainty introduced in the data on crude oil, can have an effect on the overall CO₂ emissions of approximately 4 Mton CO₂ more or less. In the figure below, the resulting uncertainty range is visualised.




Figure 3.5. : Uncertainty range of “carbon content total fossil liquid” in 2001, based on certain assumptions on tonnes of liquids consumed, conversions factors to TJ and carbon content (Monte Carlo Analysis, using Crystal ball software).

This very rude and preliminary analysis simply indicates that for countries where the calculation of the apparant consumption is mainly based on one product like it is in Belgium for crude oil, small

uncertainty on these data (tonnes consumed, conversion factors and carbon content) has a enormous total effect on the calculation of the reference approach for liquid fuels.

Reason number 3 : Methodology of reference approach – effect of solid fuels

In the reference approach, all the apparent consumption of solid fuels is multiplied by its carbon content to become CO₂ estimates for the energy use of solid fuels. However, in the bottom-up approach using the regional energy balances, not all CO₂ from the solid fuels used in iron and steel is reported under the energy section. A considerable part is considered to be ‘process emission’ (where coke is used as a reducing agent) from iron steel and is reported under the section of industrial processes. Therefore the CO₂ emissions based on the apparant consumption of solid fuels in the reference approach and the reported CO₂ emissions in the energy sector in the national inventory are not entirely comparable. Approximately, about 1Mton CO₂ (depending on the year) in the reference approach is considered to be ‘process emission’ in the national inventory.

Reason number 4: Stored carbon from non-energy use of fuels

Estimates of the non-energy use of fuels differ between the bottom-up and top down approach, especially the naphta input of the bottom-up approach (used in the national inventory) is much larger than this of the Reference Approach. Also, to calculate CO₂ emissions, the IPCC Reference Approach uses default IPCC storage factors that are not applicable to the Belgian (Flemish) situation.

In the figure below, the effect is shown that if data from the bottom-up Flemish energy balance would be used in the reference approach in table 1.A (d), instead of the data from the federal petroleum balances. According to the default fraction stored from naphta in products (80%), the difference in stored C in 1990 would be 0,23 Mton C and in 2004 2,6 Mton between the federal data or the regional data (i.e. equivalent CO₂ emissions respectively 0,8 Mton and 9,5 Mton CO₂).




Figure 3.6. : Kton C stored based on default IPCC % of stored naphta, calculated based on federal statistics and on Flemish bottom-up data.

Conclusion

The reasons mentioned in this section, are the most pertinent reasons that come to mind trying to explain the differences in results from the reference approach and the national inventory for Belgium. There may still be other reasons than those stated above.

It is very difficult to put an accurate quantitative measure on the correction needed on the reference approach, but an attempt is made in the following table. A first correction (subtraction) is made for the difference in carbon stored when data for the non-energy use of naphta from the regional Flemish energy balance would be used instead of those of the federal petroleum statistics (see reason 4). A second correction is made by subtracting an estimate of C reported under 'process emissions' in the national inventory instead of the energy sector for the iron and steel industry (see reason 3).

	1990	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004
reference approach (Mton CO ₂)	110,0	117,7	121,9	118,4	120,8	118,3	121,6	120,8	111,7	119,0	113,2
national approach (Mton CO ₂)	110,0	113,6	118,3	112,5	118,1	112,7	113,7	114,4	112,9	116,4	116,5
<i>difference in %</i>	-0,81%	3,65%	2,98%	5,22%	2,26%	4,91%	6,90%	5,53%	-1,07%	2,24%	-2,82%
naphta stored correction (Mton CO ₂)	0,8	8,4	6,2	6,0	6,0	6,7	6,4	5,4	5,5	6,8	9,5
CO ₂ from iron and steel correction (Mton CO ₂)	1	1	1	1	1	1	1	1	1	1	1
reference approach corrected for naphta stored (Mton CO ₂)	109,2	109,3	115,7	112,4	114,8	111,6	115,1	115,3	106,2	112,2	103,7
<i>difference in %</i>	-0,77%	-3,71%	-2,26%	-0,08%	-2,82%	-1,03%	1,23%	0,79%	-5,95%	-3,59%	-10,97%
reference approach corrected for naphta and solid fuels (process emissions from iron and steel industry, where solid fuels are partly used as an reducing agent) (Mton CO ₂)	108,2	108,3	114,7	111,4	113,8	110,6	114,1	114,3	105,2	111,2	102,7
<i>difference in %</i>	-1,68%	-4,59%	-3,10%	-0,97%	-3,66%	-1,91%	0,35%	-0,09%	-6,83%	-4,45%	-11,83%

Table 3.10. : Corrections and their effect on the result of the reference approach and the difference between reference approach and national inventory for the years 1990; 1995-2004.

In the following figure, the data from the table are visualised for all years.




Figure 3.8. : Possible corrections and their effect on the result of the reference approach in comparison with the national inventory.

For some years, the reference approach after correction and the national inventory are more comparable (for example 1999, 2000 and 2001). For other years, the corrections make the difference larger (for example, in 2002 or 2004).

As demonstrated in reason 2, an uncertainty of 1% on data for crude oil in the calculation of the total carbon content of liquid fossil fuels, can give rise to an uncertainty of approximately 4 Mton CO₂ more

or less on the total emissions from liquid fuels. This 4 Mton represent approximately 3,5 to 4% of the total corrected data for the reference approach, which seems to be a reasonable figure.

In the following figure, this uncertainty range is visualised in relation to the data from the national inventory.




Figure 3.9. : The uncertainty margins (+ or - 4Mton CO₂) on the corrected data for the reference approach in relation to the results for the national inventory.

The results of the national inventory lie between the top range and bottom range of the corrected data of the reference approach or even above this top range (for the years 1993,1994,1995, 2002, 2003 and 2004).

The general conclusion is that there are several reasons why the reference approach may differ from the estimate in the national inventory for Belgium. A brief explanation was given for some reasons. Where possible, a rough estimate was made on the quantity of CO₂ involved. When these corrections are made on the results of the reference approach and an uncertainty range was included, the national bottom-up inventory estimates approach these of the (top-range of) reference approach or even exceed them.

3.4. Recalculations and planned improvements

3.4.1 Recalculations

- Some minor corrections for the years 1999,2001 and 2002 are made during this submission in the Flemish region on the emissions of CH₄ and N₂O for the CHP-installations of the manufacturing industry (category 1.A.1.a).
- Some recalculations are carried out in the category 1.A.2 in the Flemish region for the emissions of CH₄ and N₂O: the emission factor used for LPG was corrected because a wrong one was used before and the emissions in the iron and steel sector are corrected after contacts with the involved industry. These corrections were done for all years from 1990 on.
- Some minor errors are corrected in Wallonia : CO₂ emissions in the category 1.A.2.f. in 2003, CO₂ emissions in the category 1.A.2.a. in 2002, CO₂ emissions in the category 1.A.1.a. in 1993 and N₂O emissions in the category 1.A.2.b. in 1994.

- The N₂O emissions from the glass sector in Wallonia are newly calculated using the default emission factors of IPCC. These emissions are in the same order of magnitude compared to measurements carried out in two glass production plants (category 1.A.2.f)
- In the iron and steel sector in Wallonia, the energy consumption was previously based partly on a bottom-up approach. A complete recalculation was made on a top-down approach by using the Walloon energy balance for all years.
- The model that is used to calculate the emissions of the domestic aviation in the Flemish region (category 1.A.3.a) has undergone minor changes during this submission for all years.
- In Wallonia, the Walloon energy balance in 2003 was recalculated in the residential sector (category 1.A.4.b) and in the chemical sector (category 1.A.2.c).
- Emissions of CH₄ and N₂O originating from the storage and transport of natural gas (energetic activities) are newly calculated in the Flemish region and added to the inventory (category 1A.3.e), it was a source of smaller importance but which was still missing in the greenhouse gas inventory in Belgium. A change in allocation is carried out during this submission: in the previous submission the CO₂ emissions of this sector were allocated to the category 1.B.2.b.
- All emissions from road transport (category 1.A.3.b) are recalculated in the Flemish region for all years during this submission because of the use of a new model, the so-called MIMOSA-model (see sections 3.1.3. and 3.2.3 for more information and the exception for the emissions of CO₂).
- The emissions of navigation (category 1.A.3.d) are optimized in the Flemish region for all years during this submission. A new developed model, the so-called susatrans-model, is used (see section 3.2.3 for further information).
- The emission factors of CO₂ used to calculate the energy related emissions for the Brussels region (see table 3.1.) have been harmonized with the emission factors used in Flanders and Wallonia.
- The fraction of organic municipal waste of the Brussels region has been reviewed from analyses of dustbins [37 and 48] and have led to a fraction of biomass origin, variable for the whole time-series, from 62 % to 53 %. This fraction decreases because the recycling increases.
-
- Small corrections are made in the Flemish region on the emissions of military aviation (category 1.A.4.c) for the years 1990,1991 and 1992. In the previous submission these years did not include all military airports. Also some small corrections are made in the Flemish region for all years on the model used to calculate the emissions of the fisheries (category 1.A.4.c).
- To obtain a harmonisation with the Walloon region, the emissions of CO₂ in the Flemish region are newly calculated in the category 1.B.2.b, fugitive emissions of the distribution of gas. This calculation is based on the composition of the natural gas used and carried out for all years.
- Emission of CH₄ from the production of cokes in the Flemish region (category 1.B1.b) is optimized for all years during this submission and monitoring results are taken into account instead of only emission factors used in previous submissions.
- The non-energetic emissions of CH₄ originating from the storage and transport of natural gas (category 1.B.2.b) are obtained during this submission for the complete time series (see section 3.2.6 for more detail) so no longer estimations were needed for the years 1991 to 2002.

- The emissions of CH₄ and N₂O from the marine bunkers (category 1 – memo items) are newly calculated for all years (Flemish region) using the emission factors of CITEPA [2] (see section 3.2.7 for further information).
- A recalculation of the emissions of CH₄ and N₂O in the refinery sector is carried out for all years during this submission. This recalculation has led to a change in allocation: all CH₄-emissions are put under category 1.B.2.a and all N₂O-emissions are allocated to category 1.A.1.b (see sections 3.2.1 and 3.2.6 for more details). During this recalculation small missing emissions of CH₄ and N₂O was detected of the CHP-installation of one of the refineries.

3.4.2 Planned improvements

- No specific planned improvements are foreseen in the near future in the estimation of greenhouse gas emissions in Belgium in the energy sector.

CHAPTER 4: INDUSTRIAL PROCESSES

4.1. Overview

4.1.1. Description of the sector

The structure of the industrial sector has undergone profound changes over recent decades. The mining industries have practically disappeared with the closure of the last coalmines. The metallurgy and textile sectors have been relatively stable, after several waves of closures and restructuring. The metallurgy industry nevertheless remains one of the key sectors of Belgian industry, both in terms of employment and turnover. The two other key sectors of industrial activity are the chemical industry and the food processing industry, which contribute respectively 3.8% and 2.5% to the GDP.

In this sector of industrial processes the emissions of industrial activities are included which are not related to the combustion of fossil fuels. Also the emissions of F-gases are included in this sector.

4.1.2. Allocation of emissions

The industrial processes in Belgium are covered by

(1) categories 2.A.1 (cement production) and 2.A.2 (lime production), activities which take place only in the Walloon region and category 2.A.7 (production of glass and ceramics), activities which take place in the Flemish and the Walloon region;

(2) categories 2.B.1 (ammonia production), 2.B.2 (nitric acid production), these activities take place both in the Flemish and the Walloon regions and category 2.B.5 other industrial in the chemical industry in the Walloon region i.e. the production of maleic anhydride and in the Flemish region i.e. the production of caprolactam and other process emissions reported by the chemical industry (f.e. the production of ethylene oxide, acrylic acid, ...);

(3) category 2.C.1 (metal production i.e. iron and steel industry), these activities take place both in the Flemish and the Walloon regions;

(4) categories 2.E (production of halocarbons and SF₆) and 2.F (consumption of halocarbons and SF₆);

(5) category 2.G (other industrial processes) i.e. a small amount of emission from the non-energy use of energy carriers used as solvents or lubricants in different (industrial) sectors.

4.2. Methodological issues

The main process emissions of CO₂, CH₄ and N₂O are calculated in Belgium by using production figures, mainly directly originating from the industrial plant, combined with emission factors presented in reference works like CITEPA [2], EMEP/CORINAIR handbook [3], IPCC Guidelines or other specific bibliographies or calculated via measurements carried out by the industrial companies.

4.2.1. Mineral products (category 2.A)

The mineral industry is one of the most important sectors of industrial process emissions in Belgium and contributes to more than 30% (37% in 2004) of greenhouse gas emissions in this sector.

In Belgium, cement production (category 2.A.1) only take place in Wallonia. The activity data is the clinker production collected directly from individual plants following the Tier 2 method.

These emissions are estimated by using a plant-specific emission factor. The emission factor is determined on the basis of the CaCO₃ content of raw material (analysis), the CaO produced and the stoichiometric ratio of the equation : $\text{CaCO}_3 \rightarrow \text{CaO} + \text{CO}_2$. The emission factor can be further adjusted taking into account the process efficiency (CaCO₃ may be not fully converted into CaO or the CaO produced sometimes contains impurities). Emission factors used in Wallonia are estimated between 522 and 566 kg CO₂/T clinker.

An average emission factor by plant has been estimated in 2002 and is applied on the all time-series 1990-2001. Since 2002, the emission factor varies each year and was calculated directly by the plant. Since 2004, plant data's include information on the CaO content of the clinker and non-carbonate sources of CaO. The CO₂ emission factor is estimated as described for Tier 2 method.

Production of lime also occurs only in the Walloon region of Belgium. These emissions of lime production (category 2.A.2) are estimated by using a plant-specific emission factor (754-790 kg CO₂/T lime, 910 kg CO₂/T dolomite). This is presented in table 4-1. A part of the lime production is coming from the kraft pulping process : the CO₂ liberated during the conversion of calcium carbonate to calcium oxide in the lime kiln in the kraft pulping process contains carbon which originates in wood. This CO₂ is not included in the net emissions (CO₂ biomass in table 4-1).

The activity data is the lime and dolomite lime production and is collected directly from individual plants. The emission factors are also collected directly from individual plants.

One recalculation was performed concerning errors in the amount of lime produced in 1990, 1991 and 1992.

	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004
Lime (kt)	2091	2037	1981	1962	2057	2080	1897	1993	2050	2075	2085	1770	1742	1785	1927
IEF lime (kg CO ₂ /t)	0,75	0,76	0,75	0,75	0,76	0,76	0,75	0,75	0,75	0,75	0,75	0,75	0,74	0,74	0,75
Dolomite lime (kt)	570	452	408	393	401	374	360	347	385	419	555	823	939	826	851
IEF dolomite lime (kg CO ₂ /t)	0,91	0,91	0,91	0,91	0,91	0,91	0,91	0,91	0,91	0,91	0,91	0,91	0,91	0,91	0,91
IEF global (kg CO ₂ /t)	0,79	0,78	0,78	0,78	0,78	0,78	0,78	0,78	0,78	0,78	0,78	0,8	0,8	0,8	0,8
CO ₂ emissions (kt)	2097	1951	1865	1828	1921	1921	1756	1819	1895	1944	2066	2070	2144	2072	2228
CO ₂ biomass emissions (kt)	40,9	42,8	42,8	16,6	38,4	30,8	41,9	41,9	45,6	45,6	57,2	48	56,1	61,5	62,3

Table 4-1 : Lime and dolomite lime production in Wallonia.

The CO₂ emissions in the “limestone and dolomite use” category are mainly reported in others source categories : table 2(I).A-G, under A. Mineral products, 7 “other” (ceramic sector and glass production) and table 2(I).A-G, under C. Iron and Steel production (sinter production). In these sectors, the CO₂-emissions are mostly due to the use of limestone in the production processes. In Wallonia, the CO₂-emissions due to the use of limestone in pollution control are negligible and non-estimated.

Soda Ash production has been occurred in Wallonia until 1993 in Solvay’s plant in Couillet. The production of soda ash was discontinued at the end of 1993 and the plant was closed in 1998. The process used was the Solvay process. From stoichiometric considerations, the industrial process

emission of CO₂ associated with the Solvay Process is zero. The excess CO₂ emitted from soda ash production originated from coke oxidation is included in the combustion sector.

The production of glass (category 2.A.7) in Belgium takes place in the Flemish and in the Walloon regions. The CO₂ emission factors used in the Walloon region in the glass production (category 2.A.7) for the decarbonation are originating from the joint EMEP/CORINAIR handbook [3] and are 150 kg/ton glass (container glass and glass wool) and 140 kg/ton glass (flat glass). Since 2003, a part of the CO₂ emission factors are calculated by the glass plant. It's difficult to make a recalculation between 1990 and 2002 due to a lack of data's.

In the Flemish region these process emissions of CO₂ from the glass production were newly added in the previous submission for the complete time series after consultation with the industrial companies involved. An emission factor of 125 kg CO₂/ton glass, as proposed by the glass federation, is used. Because of the comparability of the melting process in the production of glass and enamel, both industries are related in Flanders and consequently put under the same category 2.A.7. For the one company involved in the enamel production in Flanders, an emission factor of 650 kg CO₂/ton is used. This emission factor is given by the company involved and is based on the European BREF-documents (reference document Best Available Technology).

Also newly put in the previous submission are the process emissions of CO₂ originating from the ceramic sector (category 2.A.7) in Flanders for the complete time series. In consultation with the federations involved, an estimate is given of these emissions of CO₂.

During this submission the emissions of the ceramic sector in the Walloon region are newly put in the inventory for the complete time series with an average emission factor established in 2005 by the ceramic plants.

4.2.2. Chemical industry (category 2.B)

The chemical industry is the most important sector in industrial processes in Belgium and contributes for 38% (in 2004) of greenhouse gas emissions in this sector. The different sectors involved are described below.

4.2.1.1. Ammonia production (category 2.B.1)

Nowadays there is ammonia production in 2 companies in Belgium.

In Flanders the emissions of CO₂ originating from the production of ammonia are obtained as a result of the yearly surveys carried out by the chemical federation in cooperation with the Vito [1]. See section 3.2.9. for more information.

In the Walloon region, the CO₂ emissions are calculated based on the natural gas used as feedstock. 100% per cent of the carbon content of the natural gas is presumed to be emitted; the default IPCC emission factor for CO₂ for natural gas (55,8 kton CO₂/PJ) is used to calculate the total CO₂ emissions. The amount of natural gas used in the process is given directly by the plant.

A part of the process CO₂ emissions is used by two other plants and released after use but all the CO₂ emissions are allocated to the ammonia plant.

4.2.1.2. Nitric acid production (category 2.B.2)

The N₂O emissions from the production of nitric acid (category 2.B.2) are estimated in Flanders by using an emission factor of 8 kg N₂O/ton HNO₃ from CITEPA [2]. The three plants involved in

Flanders since 1990 agreed with this factor of 8 kg N₂O/ton HNO₃ and give their nitric acid production figures each year. Since 2000 only one plant is still involved in this sector. From 2003 on lower emission factors, based on monitoring results, are used to calculate the emissions of N₂O (5.6 kg/t). The use of catalysts reduces these emissions. A further reduction of these emissions will be obtained in the future because of the extension of the use of catalysts in the different installations involved.

Although the closure of 2 plants in the Flemish region, in 1995 and in 2000 respectively, the production of nitric acid still increases and the emissions of N₂O decreases in time due to undertaken measures. One of the companies is still testing catalysts to further decrease their emissions in the future.

The producer of nitric acid in the Walloon region provides the N₂O emissions based on their production and on monitoring. There are three installations on the plant. The global emission factor used in this region is 4,928 kg/t in 2004. There is only one installation with an abatement technology (SCR) installed in 1996 which lead also in a strongly increasing of the production in 1996.

4.2.1.3. Other (category 2.B.5)

In the other chemical industrial processes, the CO₂ emissions originate from

(1) the non-energy of fuels i.e. the use of n-butane for the production of maleic anhydride in the Walloon region. The emissions are estimated by the chemical industry (2) the emissions of N₂O originating from the production of caprolactam. Only one company is involved in Belgium in the Flemish region and since 1997 this company offers each year the results of the monitoring carried out. This company estimates the emissions of the previous years from 1990 on as accurate as possible; (3) other process CO₂ emissions reported by the chemical industry in Flanders (for example production of ethylene oxide, production of acrylic acid from propene, production of cyclohexanone from cyclohexane, production of paraxylene/meta-xylene, the emissions of CO₂ of flaring in the chemical industry etc). These CO₂ emissions result from surveys in the chemical sector in Flanders. See also section 3.2.9 for more details.

4.2.3. Metal production (category 2.C)

Metal production, more specific the iron and steel production (category 2.C.1.) is the third most important sector of industrial process emissions in Belgium and contributes to more than 10% (11% in 2004) of greenhouse gas emissions in this sector of industrial processes. These activities are situated in the Flemish and the Walloon regions .

In Flanders, the calculation of the process CO₂ emissions from iron and steel production is based on the production figures of fluid steel and pig iron and on the consumption of electrodes of the only two industrial plants in this sector in Flanders and with an emission factor approved by these plants (% carbon blown off and an emission factor of 158 kg CO₂/ton pig iron).

In Flanders the emissions of CH₄ originating from the production of sinter are completely revised during this submission and based on information in the reference document of the Best Available Techniques of the sector iron and steel and on monitoring results from 2001 on. Small amounts of emissions of CH₄ are measured in 2001 and because of the switch of cokesgrit into antracite during some months in 2004 (because of environmental technical reasons) an emission of 416 ton CH₄ was measured in 2004. Emissions of CH₄ in the remaining years are negligible.

In the Walloon region, iron is produced through the reduction of iron oxides (ore) with metallurgical coke (as the reducing agent) in a blast furnace to produce pig iron. Steel is made from pig iron and/or scrap steel using electric arc or basic oxygen.

The method used is the Tier 2 method.

The emission estimates in this sub-sector include also emissions from the production of steel in basic oxygen type furnaces but not emissions from the combustion of the fuel.

The emission factors in the basic oxygen furnace steel plant are found in table 4-3. The plants approved these emission factors. Until 2002, 100 % of the CO₂ in the pig iron produced the blast furnace is estimated to be emitted in the basic oxygen furnace due to the lack of data's (purchased pig iron, C in steel produced, C in steel scrap). Following the industry, the amount of C in steel scrap is equivalent of the amount of C in steel produced and so, the amount of C resulting is approximately zero. It was confirmed with the emission trading data's.

The process CO₂ emissions from electric arc furnaces are based on the consumption of electrodes with the following emission factor : 5 kg CO₂/ t steel.

	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004
C in pig iron (% weight)	4,6	4,6	4,6	4,6	4,6	4,6	4,6	4,6	4,6	4,6	4,6	4,6	4,6	4,66	4,66
CO ₂ emission factor (kg/t pig iron)	169	169	169	169	169	169	169	169	169	169	169	169	169	171	171
CO ₂ emission factor (kg/t steel) basic oxygen furnace	153	152	154	155	158	158	161	166	165	169	167	164	165	164	162
CO ₂ emission factor (kg/t steel) electric arc furnace	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5

Table 4-3: Emission factors used in the iron and steel sector in the Walloon region (Source: plant specific /ULG)

This sub-sector included a part of the CO₂ emission in the sinter plant. These emissions are calculated by using an IPCC emission factor: 200 kg CO₂/T sinter. The emissions calculated involve combustion and process emissions. Combustion emissions are reported in the energy sector (fuel consumption x emission factor (table 3-1) and the remaining is in the process sector. These process emissions are coming from additive in the furnace as limestone. In 2003, one sinter plant has calculated emission factor but it's not yet integrated in our inventory because it's a data for one year and on a voluntary basis. In the future, it will be difficult to make recalculation due to the lack of data's on the all time series.

CH₄ and N₂O emissions are included in the energy sector (emission factors in table 3-6).

Generally the emissions of CO₂ from the iron and steel production (category 2.C) were slightly decreasing between 1990 and 2004 and this slight decreasing trend is more or less comparable with the production of pig iron during this period.

4.2.4. Fluorinated gases (categories 2.E and 2.F)

The emissions of the categories 2.E and 2.F (production and consumption of halocarbons and SF₆) contribute to about 12% of total greenhouse gas emissions in the sector of industrial processes in Belgium.

For estimating the emissions of the F-gases described in Annex A to the Kyoto Protocol (hydrofluorocarbons HFCs, perfluorocarbons PFCs, sulphur hexafluoride SF₆), a country-specific methodology was developed by 2 consultancies (ECONOTEC and ECOLAS) in 1999 based on the IPCC Guidelines [34][35][10][28] and since then updated every year and further optimised by ECONOTEC, the last time in collaboration with VITO [45].

The present contribution of the F-gases to the total GHG emissions covered by the Kyoto Protocol (about 1.25% in 2004) is significantly lower than in 1995 (3.3%), mainly thanks to abatement measures in the chemical industry, but it has been increasing steadily since 1999, as a result of the current regulations relating to the substitution of ozone depleting substances.

No systematic emission inventories of fluorinated greenhouse gases were made for the years 1990-1994. This is because it was very difficult to obtain reliable information for these gases in Belgium for that period.

However, the emissions of the chemical process industry, which represent 87% of the total fluorinated GHG emissions in 1995, are known for the complete time series 1990-2004. For the years 1990-94, the emissions of the remaining sources (13% in 1995) were assumed constant and equal to their level of 1995. As a result, the emission inventory of fluorinated gases from 1995 to 2004 can be considered as time consistent for the complete time series.

2E Production of halocarbons

The emissions of category 2.E (Production of halocarbons) are those of an electrochemical synthesis (electro-fluorination) plant, which emits, or has emitted, SF₆, CF₄, C₂F₆, C₃F₈, C₄F₁₀, C₅F₁₂ and C₆F₁₄, as well as fluorinated greenhouse gases not covered by the Kyoto Protocol (among which CF₃SF₅, C₇F₁₆, C₈F₁₈ and C₈F₁₆O). This plant produces a broad range of fluorochemical products, which are used as basic chemicals as well as end products (mainly in the electronic industry). The emissions of this key emission source are partly fugitive and partly non-fugitive.

A gas incinerator with HF recovery has been installed in 1998 to reduce the non-fugitive emissions. This as well as a substantial change in product mix in 2001 have resulted in a drastic reduction of the emissions, which for 2004 are estimated at about 300 kt CO₂ equivalents (for the gases covered by the Kyoto Protocol), down from 4.4 Mton CO₂ equivalents in 1995.

The process causing the emissions is unique in the EU (there are however some similar plants in the US). This means that there is no readily available documentation on the processes, or reported emission factors. The emissions are calculated by using mass balances in combination with measurements. These measurements are based on EPA Method 320 using FTIR (Fourier Transform InfraRed spectroscopy) and GC/MS (gas chromatography combined with mass spectrometry).

The emission estimates are complicated due to the fact that all emissions come from batch processes and that there are many reactors and process steps. For each process step (around 60 steps for the GHG emissions) an emission factor is reported. The emission factors are combined with detailed specific production data. Due to the complexity and for reasons of confidentiality, the detailed emission calculations cannot be made public.

An external audit was performed on the emission inventory by CH2M HILL. One of the findings was: "CH2M HILL finds that the company has been diligent in its effort to remove scientific uncertainty from the downstream emission estimates, the company has gone above and beyond the expectations outlined in the GHG Protocol in its attempts to reduce uncertainty, and the resulting emission estimates are transparent and provide a basis for consistent reporting of GHG emissions." (August 2005).

2F Consumption of halocarbons

Emissions of fluorinated greenhouse gases are mainly estimated on the basis of the consumption of the different substances for each application, the consumption of products containing such substances, figures on external trade in substances or products containing substances, as well as on emission modelling by application and assumptions on leakage rates.

For the calculation of the potential emissions, the external trade in products containing halocarbons is taken into account. The potential bulk halocarbon emissions have been estimated on the basis of the production, consumption and destruction figures directly, rather from official statistics on external trade, which are not available for the relevant substances.

The actual emissions of HFCs come from the following categories: Refrigeration (industrial & commercial and household refrigerators) and air conditioning equipment (in stationary applications and in vehicles), Foams (closed cell foams, polyurethane cans and foam in refrigerators/freezers), Metered Dose Inhalers (MDI), aerosols other than MDIs and fire extinguishing (fixed installations).

For the refrigeration sector, the consumption and emission of refrigerants are modelled on the basis of an annual inquiry among refrigerant distributors on their national supply by refrigerant mixture, as well as on assumptions on average loss rates. The refrigerant consumption and emissions of the transportation sector are estimated by modelling the number of vehicles and the penetration of air conditioning or refrigerated transport, by category of vehicles.

For the foam sector, the modelling of consumption and emissions of blowing agents are based on an annual inquiry among the foam manufacturers and assumptions on emission rates for manufacturing and product use, as well as on external trade, by type of insulation foam.

The SF₆ emissions originate from the production and the stock of soundproof double-glazing and to a minor extent from the electricity sector.

HFC emissions have been gradually increasing (+238% between 1995 and 2004), as a result of the current regulations relating to CFC and HCFC substitution. HFCs are mainly used in the refrigeration sector and for the production of synthetic foams.

4.2.5. Non-energy use of fuels (category 2.G)

Listed here are the CO₂ emissions calculated using the IPCC default factors of carbon stored during the use of lubricants and solvents in Flanders, mostly in industry. These emissions are relatively small. More explanation about the estimation of these emissions can be found in section 3.2.9.

Since this submission, the CO₂ emissions coming from the use of lubricants and solvents in Wallonia are included for all the time series. The fraction carbon stored is 0,75.

4.3. Recalculations and planned improvements

4.3.1. Recalculations

- In the Walloon region the process emissions of CO₂ from the ceramic production are newly added in this submission for the complete time series with an emission factor based on the emission trading data in 2004.
- In the lime sector, the activity data's in 1990, 1991 and 1992 were corrected in the Walloon region

- In the iron and steel sector, the CO₂ emission factor in the basic oxygen furnace was recalculated with the emission trading data in 2004, and the complete time series was recalculated in the Walloon region.
- The CO₂ emissions coming from the use of lubricants and solvents in Wallonia are newly included for all the time series.
- Contrary to the previous submission the emissions of CO₂ from the flaring activities in the chemical industry are allocated to the category 2.B.5. instead of category 6.C (as described in the IPCC Good Practice Guidance) because these emissions are also included in the surveys which are carried out on a yearly basis by the chemical federation in cooperation with the Vito and because it's difficult to take out these emissions (Flemish region).
- In comparison with the update in the previous submission, the following improvements have been made in the emission inventory of fluorinated gases : Compared to the previous submission, some emission figures for the years 1990 to 2003 have been recalculated, as a result of new assumptions, better data, improved calculation methods or error corrections, with the aim to keep the emission inventories of fluorinated substances consistent for the complete time series. The overall results obtained for these years are a little higher than previously (less than 180 kt CO₂-eq). The changes made are the following:
 - For the first time, an enquiry has been made among the distributors of HFC for fire extinguishing installations. The results show figures that are significantly lower than the rough estimates previously obtained from the sector.
 - Given the increasing share of the emissions of car air conditioning, their calculation has been comprehensively revised and improved. Besides, figures from a first inquiry (carried out by the Federal Public Service on Mobility) on the proportion of new cars with air conditioning have been taken into account. The calculation of air conditioning of buses and coaches has been improved along the same lines. The emission figures for refrigerated road transport have also been improved, on the basis of a more detailed calculation.
 - The emissions linked to the production and consumption of polyurethane cans have been significantly revised, after discussions with the main manufacturer and on the basis of a recent German study.
 - The 2001 and 2002 fugitive emissions of the electrochemical synthesis plant have been changed a little, as more precise information has been obtained from the company.
- The emissions in category 2.G (non-energy use) in the Flemish region were estimated as '0' during the previous submission for the years 1991 to 1993 because of missing relevant information for these years. Because of the small difference in emissions between the years 1990 and 1994, the Flemish region decided to take over the emissions of the year 1990 for the years 1991 to 1993.
- In Flanders the emissions of CH₄ originating from the production of sinter are completely revised during this submission and based on information in the reference document of the Best Available Techniques of the sector iron and steel and on monitoring results from 2001 on. Small amounts of emissions of CH₄ are measured in 2001 and because of the switch of cokesgrit into antracite during some months in 2004 (because of environmental technical reasons) an emission of 416 ton CH₄ was measured in 2004. Emissions of CH₄ in the remaining years are negligible.

4.3.2. Planned improvements

- One of the planned improvements is the addition in the next submission of some missing process emissions of CO₂ for the years 2003 and 2004 (Flanders). These emissions originate from the combustion of sludge (containing CaCO₃) in the paperindustry in Flanders (the sludge comes from the recycling of old paper).

CHAPTER 5: SOLVENT AND OTHER PRODUCTS USE

5.1 Overview

In Belgium the emissions of NMVOC in the source category 'Solvent and other product use' include paint application (building industry & households), production of medicines, paints, inks and glues, domestic use of other products (incl. glues and adhesives), coating processes in general (incl. assembly of automobiles), printing industry, wood conservation, treatment of rubber, storage and handling of products, recuperation of solvents and extraction of oil, cleaning and degreasing and dry cleaning.

No estimation of the CO₂ equivalent emissions of the solvent consumption is carried out in Belgium except in the Flemish region where emissions of CO₂ from the non-energy use of lubricants and solvents is reported under category 2.G.

The greenhouse gas emissions in this category 3 in Belgium are related to the use of N₂O as an anaesthetic.

5.2. Methodological issues

The regions in Belgium are using comparable methodologies to estimate the emissions in their region. The emissions of NMVOC in Flanders are estimated by using the results of a study started by the University of Gent in 1998 and continued by the Flemish Environment Agency (VMM).

In Wallonia, the calculation is based on a methodology established by Econotec [39].

In the Brussels region, the emissions are calculated by using the results of the research projects [16], [17] and [20].

Because of the less importance of these emissions in the greenhouse gas story, only a general view of how these emissions are calculated in Belgium is given below.

Broadly speaking, emissions of NMVOC are estimated in Belgium as follows :

- All emissions of category 3.A (NMVOC emissions for Paint Application...), and some of category 3.C (production of paints, inks and glues) as well as some of category 3.D (other domestic use, wood and textile coating, printing industry, wood conservation, recovery of solvents, treatment of rubber, coating of synthetic material and paper) are estimated based on production figures that are given by the specific industry or professional federations. The emission factors used are mainly the solvent content of the product.

- The remaining emissions of category 3.D (storage and handling of products and assembly of automobiles, extraction of oil seeds) are estimated based on information gathered in the industrial databases mainly originating from the yearly reporting obligations of the industrial companies.

- The emission calculation for the emission of N₂O from anaesthesia (3D) is based on the number of hospital beds in Belgium and the average consumption of anaesthetics per bed. The emission factor is 10,3 kg N₂O/bed/year. This factor was determined by inquiries carried out in 1995 by an independent consultant agency Econotec [39].

It has been assumed that all of the nitrous oxide used for anaesthetics will eventually be released to the atmosphere. The number of beds used for the emissions calculations was obtained from the DGASS (General Directorate for Health and Social Action).

- There is no estimation carried out in Belgium of the CO₂ equivalents calculated out of the emissions of NMVOC of the solvent consumption because of the unreliability of this factors proposed in literature.

5.3 Recalculations and planned improvements

5.3.1. Recalculations

During this submission the activity data used for calculating the emissions of N₂O from anaesthesia are actualized for all years (Flanders).

Emission estimates of NMVOC originating from coating processes are revised in the Flemish region during this submission.

5.3.2. Planned improvements

No planned improvements are foreseen in the near future.

CHAPTER 6: AGRICULTURE

6.1. Overview

6.1.1. Description of the sector

The main types of rearing and cultivation business and their numbers are represented in tables 6.1 and 6.2. Those data are available on a yearly basis and are used as one of the activity data for the agricultural sector (see 6.2.1.). Tables 6.1 and 6.2 are presented here to give an overview of the sector in Belgium.

	Belgium	Evolution 2004-2005	Flemish Region	Walloon Region	Brussels Capital region
Number of businesses	51.540	-3,2%	34.410	17.109	21
Agricultural land (ha)	1.385.582	-0,6%	629.684	755.545	353
Grassland (ha)	600.509	-1,1%	226.314	374.054	141
Grains (ha, without maize)	267.975	0,3%	91.397	176.494	83
Maize (ha)	218.081	-0,5%	162.533	55.485	62
Sugar beet (ha)	85.527	-2,5%	32.747	52.765	15
Potatoes (ha)	64.952	-2,7%	40.218	24.712	22
Others (ha)	148.538	1,8%	76.474	72.035	29

Table 6.1. : Main types of cultivation in Belgium (NIS, 2005).

	Belgium	Evolution 2004-2005	Flemish Region	Walloon Region	Brussels Capital region
Bovins (total)	2.698.649	-1,5%	1.350.304	1.348.032	313
Bovines under 1 year	786.773	-0,3%	434.988	351.696	89
Male bovine between 1 and 2 years	141.814	-5,3%	76.942	64.872	0
Female bovine between 1 and 2 years	378.106	-2,0%	183.612	194.471	23
Male bovine more than 2 years	37.427	-5,2%	18.960	18.465	2
Female bovine more than 2 years	350.601	-1,9%	168.743	181.784	74
Dairy cows	523.281	-3,6%	292.842	230.374	65
Brood cows	480.647	1,3%	174.217	306.370	60
Porcs (total)	6.318.213	-0,6%	5.952.518	365.693	2
Piglet under 20 kg	1.661.344	-1,0%	1.607.322	54.022	0
Piglet between 20 and 50 kg	1.291.375	-4,6%	1.203.425	87.948	2
Fattening pigs more than 50 kg	2.762.858	1,9%	2.563.978	198.880	0
- Breeding males	10.105	-6,1%	9.482	623	0
Sows	592.531	-1,3%	568.311	24.220	0
Sheep	152.384	1,2%	95.976	56.392	16
Goats	26.209	2,9%	15.984	10.215	10
Horses	33.404	4,6%	21.684	11.659	61
Poultry (total)	35.569.320	-2,6%	30.385.744	5.182.800	776
laying hens	13.214.955	-1,7%	11.605.059	1.609.723	173
Broilers	21.073.353	-3,1%	17.633.155	3.439.718	480
Others	1.281.012	-2,6%	1.147.530	133.359	123

Table 6.2. : Number of heads in the main livestock categories in Belgium (NIS, 2005).

The land used for agriculture in 2005 extends to 1.385.582 hectares (Table 6.1), or 45.6% of Belgium. In 2005, the number of agricultural and horticultural businesses amounted to 51.540. This number had dropped by 17 % in 5 years, the disappearing of small businesses being a general trend in the sector, also reinforced by the successive crises that have hit the agricultural sector (BSE [*Bovine Spongiform Encephalitis*], dioxin). Additionally in Flanders, this partly can be explained due to the subsidized cut down of the number of cattle. This counted in 2001 and 2002 only for swine, in 2003 also for bovine and poultry. Nevertheless the land area used for agricultural purposes remained identical during this period. In 2005 Wallonia has 55% of the land used for agriculture, but 67% of agricultural businesses are situated in Flanders. The land area used for farming is on average 18 ha per farm in the Flemish region and 44 ha per farm in the Walloon region.

Organic farming and the businesses in transition towards this type of farming only represent 1% of the total. The evolution of the Belgian agricultural sector is of course directly related to the Common Agricultural Policy of the European Union.

6.1.2 Allocation of emissions

Some agricultural sectors such as rice cultivation, prescribed burning of savannahs (categories 4.C and 4.E) and field burning of agricultural residues (category 4.F) are not occurring in Belgium. The agricultural sector in Belgium covers the categories 4.A, 4.B and 4.D.

The agricultural activities on the Brussels territory are extremely small compared with the 2 other regions in Belgium. As one can see in table 6.2, the agricultural area or the number of animals in the Brussels region never exceed 0,02 % of the national figure. Keeping in mind the large uncertainty on agricultural emissions, the emissions in the Brussels region are deemed negligible and are not estimated.

6.2. Methodological issues

6.2.1. Data sources

The main activity data are the land-use and the livestock figures. The National Institute of Statistics (NIS) [26] publishes these numbers yearly. All agricultural businesses have to fill a form each year about the situation at 1 may of that year and sent it to the NIS. Further details on the agricultural census methodology and QA/QC issues can be found on the NIS website: www.statbel.fgov.be.

For nitrogen fertiliser use, data from the Centre for Agricultural Economics are used. The institute conducts surveys on a representative sample of the different types of agricultural businesses and produces yearly weighted average values on the fertiliser use.

With an average temperature of 9,8 °C (11°C in 2005, www.meteo.be), Belgium as a whole has a "cool" climate.

In Wallonia, the data on sludge spreading on agricultural soils are available on the website of DGRNE (<http://www.environnement.wallonie.be/>). The allocation of animals to AWMS come from the NIS agricultural census of 1992 and 1996, where those data were collected by animal type. Those data are not collected yearly by the NIS given their slow pace of change. However, an update of the 1996 data would likely be useful in a near future but we have no information about the NIS planning regarding this type of census.

In Flanders, the N₂O emission calculation model follows IPCC methodology but uses region-specific data wherever available. The allocation of animals to AWMS as well as the detailed data for nitrogen excretion factors and processed animal manure originate from the Manure Bank of the Flemish Land Agency (www.vlm.be) and is based on the regional situation. The nitrogen leaching (N₂O model) comes from the SENTWA model (System for the Evaluation of Nutrient Transport to Water) that is yearly updated [45].

In Wallonia, the emissions are calculated using a model developed by a consultant agency Siterem [30] with recognised experience in this field. Some amendments have been applied on the model in order to better comply with the UNFCCC requirements and to keep only the relevant regional specific emission factors. Different data are used as inputs in the model which then calculates CH₄, N₂O and NH₃ emissions (NH₃ is used for other mandatory reporting than UNFCCC). Four emissions sources were pointed: animal husbandry, the excreta of agricultural animals deposited in buildings and collected as either liquid slurry or solid manure, application of animal manure to land and mineral fertilisers.

6.2.2. Enteric fermentation

CH₄ emissions from enteric fermentation from animal husbandry are estimated using the Tier 1 methodology described in the IPCC Good Practice Guidance [10]. Although enteric fermentation is a key source, Belgium does not use a Tier 2 methodology because data such as gross energy intake are not available and the use of Tier 2 without reliable activity data does not appear likely to reduce the overall uncertainty of the estimate.

CH₄ emission (ton) = number of animals * emission factor

The IPCC emission factors are used for most animal categories. In Wallonia, the emission factor for dairy cattle, which is the most important subcategory in this sector, is adjusted regarding the increasing milk production. The IPCC 1996 guidelines states that animal size and milk production are important determinants of emission rates for dairy cows. IPCC provides different EF different milk productions, and a similar approach was applied to adjust the EF according to the measured milk production. The resulting EF is very close to the IPCC default, from 100 kg CH₄/yr in 1990, with an average milk production of 4021 litres, to 110 kg CH₄/yr in 2003, with a milk production of 5222 litres.

Further harmonisation of the emission factors between the regions is foreseen. The classification of the animal categories occurs according to the IPCC methodology.

The emission factors presented in the CRF tables are a weighted average of the emission factors used at the regional level.

6.2.3. Manure management

Flanders

CH₄ emissions from manure management in Flanders are estimated using the Tier 2 method. Because of the availability of detailed statistics on livestock composition in Flanders, including data on e.g. slaughter weights, a more extended variant of the IPCC methodology has been applied, integrating countryspecific data. The integrator used in following formula takes into account the fact that the weight of the cattle over the whole lifetime is not the same as the slaughter weight, and integrates therefore between the weight at birth and the slaughter weight.

Since 1996 Flanders has got a Manure Action Plan (MAP), which foresees in processing of the surplus of manure (based on the Nitrate Directive). A study performed by the Flemish Institute for Technological Research (Vito), indicates that CH₄ emissions during manure processing are negligible. Further studies are undertaken to estimate N₂O losses during manure processing.

CH₄ emission (m³) = number of animals * average adult weight⁽¹⁾ (kg) * integrator⁽¹⁾ * manure production⁽¹⁾ (kg/day/1000kg) * 365/1000 * volatile solid⁽²⁾ (%) * emission potential⁽²⁾ (m³/kg VS) * CH₄ potential⁽²⁾ (m³) [(1) Source : Flemish Land Agency; (2) Source : Casada & Safley [46]].

CH₄ emission (ton) = CH₄ emission (m³) * density (kg/m³)

<i>Category</i>	<i>Weight (kg)</i>	<i>Integrator</i>	<i>Manure production (kg/d/1000kg)</i>	<i>VS (%)</i>	<i>Emission Potential (m³/ kg VS)</i>	<i>MCF (%)</i>
<i>Bovine</i>						
Slaughter calves in stable	160	0,62	86	11.6	0.33	15
Bovine under 1 year						
In stable	300	0,56	86	11.6	0.33	15
On pasture	300	0,56	58	12.4	0.17	10
Bovine from 1 to 2 year						
In stable	400	0,88	86	11.6	0.33	15
On pasture	400	0,88	58	12.4	0.17	10
Bovine more than 2 year						
In stable	500	1	86	11.6	0.33	15
On pasture	500	1	58	12.4	0.17	10
<i>sheep</i>	50	1	40	23	0.19	10
<i>goats</i>	50	1	41	26.6	0.17	10
<i>swine</i>						
Piglet under 20 kg	20	0,75	84	10.1	0.45	20
Piglet between 20 and 50 kg	35	1	84	10.1	0.45	20
Fattening pigs between 50 and 80 kg	65	1	84	10.1	0.45	20
Fattening pigs between 80 and 110 kg	95	1	84	10.1	0.45	20
Fattening pigs more than 110 kg	150	0,87	84	10.1	0.45	20
Breeding male	140	1	84	10.1	0.45	20
Breeding sows and old males and sows	125	1	84	10.1	0.45	20
<i>Horses</i>	500	1	51	19.6	0.33	10
<i>Mules</i>	250	1	51	20	0.33	10
<i>poultry</i>						
Broilers (for breeding)	2	1	85	19.4	0.32	10
Broilers (for fattening)	1,3	0,52	85	19.4	0.32	10
Laying hens	2	1	85	19.4	0.32	15
Young laying hens	1,3	0,52	85	19.4	0.32	10
Ducks	2,5	0,54	85	19.4	0.32	20
Goose	7,5	0,65	47	19.4	0.30	20
Turkeys	7	0,49	47	19.4	0.30	20
Guinia fowl	1,2	0,55	85	19.4	0.32	20

Table 6.3. : Calculation factors used for the CH₄ emissions from manure management in the Flemish region (Source: Flemish Land Agency, Casada & Safley).

Wallonia

Emission factors for each animal category have been developed by Siterem [30]. Those factors take into account the type and volume of manure produced during the time spent in stables, its density and carbon content, and its carbon volatilisation ratio. The parameters come from studies conducted in Wallonia or in France. The calculation of these EF implies large excel spreadsheets, which cannot be reproduced in the NIR. Those emission factors are multiplied by the number of animals to estimate the total emissions from manure management.

The resulting EF are comparable to the default IPCC EF (table 4-6 of the IPCC 1996 guidelines for western Europe, cool climate) : in 2004, the EF used in Wallonia are 5,18 kg/head.yr for non-dairy cattle (IPCC default = 6), 12,47 for dairy cattle (IPCC default = 14) and 2,54 for swine (IPCC default = 3). For non-dairy cattle and swine, the implied EF in the CRF tables for Wallonia is a weighted average of specific EF for further disaggregated animal categories (see table 6.2 for example). For this reason, the EF is changing from year to year, according to the changing proportions of the subcategories of swine and non dairy cattle. The EF for sheep is 0,25 compared to 0,19 in the 1996 IPCC guidelines. It can be pointed that in 2004, sheep represents only 0,16 % of the CH₄ emissions from manure management in Wallonia.

6.2.4. Agricultural soils

Methane

Following the centralised review report and in harmony with the IPCC 1996 guidelines the methane emissions from wetlands, unmanaged surface waters and removals in forest soils, grassland and agricultural soils are no longer reported in the national inventory.

Wallonia calculates the CH₄ emissions on the basis of the manure applied during grazing.

In both regions, this source is very small compared to enteric fermentation and manure management.

Nitrous oxide

The N₂O emission estimation depends on two major sources : the manure storage and the emission from agricultural soils (direct and indirect). The N₂O emissions are calculated according to IPCC methodology but uses country or region specific data where available.

The N₂O emission estimation from manure storage is based on the nitrogen excreted by each animal category, estimated through local production factors. The calculation takes into account the number of days in pasture and the ratio of liquid systems and solid storage. In Wallonia. Such factors were first determined for the implementation of the CE Nitrates Directive 91/676 (see annexes of the decree downloadable on : http://www.nitrawal.be/pdf/arretenitrates_mb2.pdf, but were representing the nitrogen *after* deduction of the atmospheric losses, so new factors were calculated on this basis for the purposes of estimating atmospheric emissions.

In Flanders, the nitrogen excretion factors were revised during this submission for the time series 1996-2004, taking into account the reduced nutrient content in the animal feed (see table 6.5).

In Belgium, the local excretion factors are more or less comparable to the 1996 IPCC default value, especially if the principle of Table 4.14 of the IPCC Good Practice Guidance is taken into account : adjustment factors for the IPCC 1999 table 4-20 are given according to the age range, and in Belgium, the agricultural census allows a detailed desagregation in subcategories according to the age or the weight of the animals (see table 6.2).

The IPCC default emission factors for liquid systems and solid storage are then applied (respectively 0,001 and 0,02 kg N- N₂O/kg N excreted).

In Wallonia, the allocation of animals to AWMS comes from the NIS agricultural census of 1992 and 1996, where those data were published by animal type. Those data are not collected yearly by the NIS given their slow pace of change.

In Flanders, the allocation of animals to AWMS comes from the Flemisch Land Agency (see table 6.5).

<i>Category</i>	Nex (kg N/animal/yr)	AWMS
<i>Bovine</i>		
Slaughter calves	10.5	24% liquid storage 36% solid storage 40% pasture
Other bovine under 1 year		
Male	25.76	ditto
Female	36.96	ditto
Bovine from 1 to 2 year		
Male		
for the reproduction	62.72	ditto
other	68.32	ditto
Female		
Fattening cows	68.32	ditto
For replacement of dairy cows	62.72	ditto
Bovine more than 2 year	86.24	ditto
Dairy cows	108.64	39% liquid storage 19% solid storage 42% pasture
<i>Sheep</i>		
Sheep under 1 year	4.36	19% liquid storage 81% pasture
Sheep more than 1 year and goats	10.5	ditto
<i>Swine</i>		

Piglet under 20 kg	2.51	96% liquid storage 4% daily spreading
Piglet between 20 and 50 kg	12.17	ditto
Fattening pigs between more than 50 kg	15.69	ditto
Breeding pigs more than 50 kg		ditto
Boars	23.36	ditto
Sows	23.18	
covered sows	22.73	76% liquid storage 24% solid storage
Non-covered sows	23.18	ditto
Horses		
Horses under 6 months	35	96% pasture 4% other
Farming horse more than 6 months	65	ditto
Other horses more than 6 months	50	ditto
Mules	35	ditto
Rabbit	8.64	ditto
Furred animals	3.22	ditto
poultry		
Broilers (for breeding)	0.94	85% solid storage 15% other
Broilers (for fattening)	0.59	ditto
Laying hens (for breeding)	0.55	44% storage within housing 23% solid storage 33% other
laying hens	0.69	ditto
Breeding cocks	0.69	100% solid storage
Turkeys	1.89	ditto
ostriches	8.6	100% liquid storage
other	0.24	ditto

Table 6.5 : Nitrogen excretion factors and allocation of animals to AWMS for each category in Flanders.

N₂O is also emitted as a by-product during soil nitrification and denitrification processes. There is a very high variability in the emission rates and the estimation methodologies try to take into account local conditions to reduce the uncertainty.

The N₂O direct soil emissions (category 4.D.1) include the N₂O emissions from daily spread, spreading of mineral fertilisers, spreading of organic fertilisers and nitrogen from crop residues.

The N₂O emissions from mineral fertilisers account for the nitrogen volatilised as NH₃ (and NO). The model uses a volatilisation rate from mineral nitrogen to NH₃ (In Wallonia the average rate of 2,3 % based on the default values recommended by IIASA for different types of fertilisers and in Flanders the weighted average for NH₃ and NO volatilisation is 4.4%). The N₂O emissions from organic fertiliser spreading are calculated in the same way than N₂O emission from mineral fertiliser spreading. The N₂O emissions from crop residues can vary according to the preceding culture. The nitrogen residual from soil is estimated by multiplying, for each culture, the cultivated area by the nitrogen residual average quantity for the culture considered. The N₂O emission from these 3 sources is estimated by applying the IPCC default emission factor (0.0125 kg N-N₂O/kg nitrogen).

The nitrogen from grazing is estimated, taking into account the number of days in pasture and the nitrogen excreted by each animal category. Available nitrogen is the difference between the manure nitrogen content and the manure nitrogen volatilisation in NH₃ and NO form. The IPCC default emission factor of 0.02 kg N-N₂O / kg N is then used to estimate the emissions.

In Flanders, during this submission the implied emission factor for histosols is updated from 5 to 8 kg N₂O-N / kg N. Also the area histosols has been corrected using region specific data based on an intersection between the CORINE Land Cover Geodataset from 1990 and the Belgian 'Soilassociationmap'. The area is held constant for the entire time series [48].

The indirect emission (category 4.D.3) considers the N₂O emissions from atmospheric deposition, leaching and runoff.

The atmospheric deposition is estimated at 10.9 kg N/ha. It is considered that 1 % of this nitrogen is volatilised as N₂O. The N₂O emissions from leaching and runoff are estimated by multiplying available nitrogen quantity in soil (animals excreta from grazing, mineral and organic fertilisers spreading, crop residues decomposition, sludge and atmospheric deposition) by two emission factors. The first estimates the fraction of nitrogen lost by leaching and runoff, with a value coming from local studies and which falls into the IPCC range (0.17 kg N / kg N available). The second estimates the volatilisation rate in N₂O form with the IPCC default value (0.025 kg N-N₂O / kg N, table 4.18 of the IPCC Good Practice Guidance).

The category other (4.D.4) consists of N₂O emission from sludge spreading on agricultural soils. It is considered a fixed contribution of 0.1 kg N/ha x year and an emission factor equal to 0.0125 kg N-N₂O/kg N from sludge.

6.3. Recalculations and planned improvement

6.3.1 Recalculations

- In Flanders recalculations for the time series (1996-2004) have been done for the nitrogen excretion factors taking into account the reduced nitrogen content in the animal feed (category 4.B and 4.D.2).
- Also in Flanders the inconsistency in the livestock population data for sheep and swine reported in tables 4.A, 4.B(a) and 4.B(b) is solved during this submission for all years.
- Following the centralised review report, the methane emissions from wetlands, unmanaged surface waters (rivers and lakes) and removals from forest, grassland and agricultural soils in Flanders are no longer reported in the national inventory (category 4.D.1, table 4s2, cel B20).

- In Flanders, the default emission factor for histosols is updated from 5 to 8 kg N₂O-N/kg N. Also the area has been revised for the entire time series according to region specific information (category 4.D.1).
- A correction of the total emissions of N₂O in the sector of agriculture is made in the CRF tables for 1990 (table 4s1 - cel C7). The formula to calculate this total was removed by mistake for this year.
- In Wallonia, following the S&A report 2003, the IPCC default value is used since the submission of 2005 for the swine category for the calculation of CH₄ emissions from enteric fermentation. The mineral fertiliser volatilisation rate has also been corrected. This mainly changes the NH₃ emissions (important for other reporting obligations), but also has a small effect on N₂O emissions from soils. These corrections were made for all years in categories 4.A, 4.D.1 and 4.D.3.
- In Wallonia, an allocation mistake in table 4B(b) was corrected : in the inventory years 2002 and 2003, nitrogen excretion was wrongly reported under "daily spread" instead of "pasture range and paddocks" (category 4.B).

6.3.2. Planned improvements

- In Flanders an effort will be done to obtain updated histosol areas for 2000 by doing an intersection between the Corine Land Cover Geodataset 2000 with the Belgian Soilassociationmap.
- Also in Flanders the difference between the livestock population data for poultry between the tables 4.B(a) and 4.B(b) is due to the fact that dugs and ostriches are included unther poultry in table 4.B(b), but not in table 4.B(a). For the next submission dugs and ostriches will be reported in the category 'other'.
- In Wallonia the methane emissions from the manure applied during grazing are reported under agricultural soils (category 4.D). These emissions will likely be included in the manure management category in the next submission.

CHAPTER 7: LAND-USE CHANGE AND FORESTRY

7.1. Overview

Belgium has a temperate maritime climate, with moderate temperature variability, prevailing westerly winds, heavy cloud cover and regular rain.

Belgium decides to adopt the following forest definition for use in accounting for its activities under the Convention, and Article 3.3 and 3.4 of the Kyoto Protocol:

- Minimum tree crown cover: 20 %
- Minimum land area : 0.5 ha
- Minimum height at maturity: 5 m

These choices allow to use the result of the actual and projected regional forest inventories (Wallonia and Flanders) to calculate the C stock of different pools (biomass, dead organic matters and mineral soil). This definition is fully consistent with the official FAO definition and is already reported in the 2005 Forest Resource Assessment (FRA 2005).

The distribution of forests in Belgium is shown in table 7.1. The total productive forest area in Flanders amounted to 146381 ha in 2000, based on the regional forest mapping (Van de Walle *et al.*, 2005), while Walloon forests covered 458700 ha (Perrin *et al.*, 2000). Moreover, the non-productive areas as open spaces, roads, rivers etc. in the Flemish and Walloon forests were also excluded from the analysis.

Considering the very small forest area in the Brussels region (0,3 % of the total forested area), no inventory of the emissions has been conducted so far.

Table 7-1: Forest cover in Belgium (source: National Institute of Statistics and regional forest inventories, Year 2000)

Regions	Total area	Forest area	Forest cover	% of the total
	(km²)	(km²)	(%)	Belgian forest area
Wallonia	16845	4587	27,2%	75,8%
Flanders	13521	1447	10,7%	23,9%
Brussels Capital	162	20	12,3%	0,3%
Belgium	30366	6054	19,9%	100,0%

7.2. Methodological issues

7.2.1 Changes in Forest and Other Woody Biomass Stocks

A. Above and below ground biomass in forest

Forest inventories were conducted both in the Flemish and the Walloon regions using similar sampling techniques. The inventories are drawn up by sampling to determine the surfaces by categories of property (Private or Public: State, Province, Community), type of forest, species, age, size and quality. The sampling points of the regional forest inventories were selected according to a 1.0 km x 0.5 km grid oriented from the east to the west on the National Geographic Institute (NGI) maps at a scale of 1/25000. The rectangular grid had the advantage of going against the orientation of the relief elements oriented along a southwest – northwest axis and against ecological and geological gradients predominant in the N-S orientation. Each grid intersection, located in a forest, represented the centre of a sampling plot. For plots at edges or borders, the plot centre was moved towards the inside of the plantation. The overall impact of changing the plot centre don't conduct to any systematic bias (still a random procedure (Lecomte & Rondeux, 1994; AB&G, 2001).

Sampling plots are circular and of 10 are each. The following information was collected : category of property (private or public : state, region or province), municipality, forest type, stand structure and development stage, commercial quality for broadleaf species with a section exceeding 22 cm circumference, evidence of damage caused by game and the health and condition for harvest (these two last categories are only available for the Walloon forests) (see Figure 7.1.). Topography (exposition and slope), soil texture and drainage class, age (class), canopy closure, tree species, circumference at 1.5 m and total and dominant heights were also collected. Basic information in the Flemish and the Walloon inventories was therefore very similar. Moreover, the same cubage tables were applied to calculate the total solid wood (TSW) volume from tree circumference and tree height. The terminology ‘total solid wood’ refers to the combination of stem and branches with a circumference exceeding 22 cm (Dagnelie et al., 1999).

The first Walloon forest inventory was completed in 1984. The current permanent systematic sampling started in 1994 and covers each year 10 % of the approximately 11000 sampling points (Lecomte & Rondeux, 1994). In 2000, 50 % of the sample points of the second inventory were measured. In Flanders, 2665 plots were sampled in the framework of the first forest inventory, which was constituted in the period 1997-1999 (AB&G, 2001). This regional inventory is intended to be repeated every 10 years, to allow e.g. the calculation of growth rates in the Flemish forests.

With more than 13000 plots over a territory of 30528 km², forest inventories in Belgium have one of the highest sampling rates in Europe. Compared to other countries or regions, the Belgian sampling grid, with each sampling point representing 50 ha of forest, is very dense (Laitat et al., 2000). In comparison, one plot represents 2400 ha of forest land in the U.S. (Brown, 2002).

Based on the information of the regional forest inventories, the total solid wood volumes (TSW) of each species, spread over three age classes, were calculated for Flanders and Wallonia, as given in table 7.2. Values for Belgium were calculated by summing up the Flemish and Walloon forest areas and wood volumes.




Figure 7.1. : schema of a sampling unit and data collected (Rondeux *et al*, 2005)

Table 7.2 : volume per specie in the forest inventories (TSW in Mm³)

Species	Wallonia	Flanders	TOTAL
Picea abies (Norway Spruce)	52,5	0,5	53,0
Quercus petraea et Q. robur (Oaks)	25,2	3,6	28,9
Fagus silvatica (Beech)	16,3	2,4	18,7
Pinus silvestris (Scots Pine)	2,9	8,6	11,5
Populus sp (Poplars)	2,8	5,1	7,9
Betula sp (Birch)	3,4	1,4	4,8
Pinus laricio (Corsican Pine)	0,4	3,9	4,4
Fraxinus excelsior (Ash)	3,6	0,4	4,0
Larix sp (Larch)	2,6	0,8	3,4
Pseudotsuga menziesii (Douglas fir)	2,9	0,4	3,3
Other species	13,0	4,5	17,6
	125,7	31,7	157,4
<i>Total</i>			

The calculation of the amount of carbon stored in the biomass of trees is usually based on biomass expansion factors s.l We converted solid wood volumes into carbon. For each dominant species, we transformed: volumes of solid wood in total dry mass multiplying by the infra-densities (WD); solid wood total dry mass in total above-ground dry biomass (biomass expansion factor 1 or BEF 1); above-ground dry biomass in total dry biomass (roots included, biomass expansion factor 2 or BEF2) and total dry biomass in carbon quantities (carbon content or CC). Some explicit conditions were applied for the selection of biomass expansion factors s.l. from the literature. For the expansion factors s.s., foliage had to be included, in accordance with the IPCC-methodology (IPCC, 2003). The analysis was limited to data reported for Austria, Belgium, Denmark, France, Germany, Great Britain, Ireland and The Netherlands. Values were selected for ‘coniferous’ and ‘deciduous’ species separately, but also for the most important tree species in the Belgian forests: pines (*Pinus* sp.), Douglas fir (*Pseudotsuga menziesii* (Mirb.) Franco), larches (*Larix* sp.), Norway spruce (*Picea abies* (L.) Karst.), beech (*Fagus sylvatica* L.), oaks (*Quercus robur* L. and *Q. petraea* L.), mixed ‘noble’ species (including maple (*Acer pseudoplatanus* L.), elms (*Ulmus* sp.), ash (*Fraxinus excelsior* L.) and red oak (*Quercus rubra* L.)) and poplars (*Populus* sp.). We established the frequency distribution of the values used in neighboring countries and selected the median (see Vandewalle et al, 2005). The selected factors are shown in table 7.3.

Table 7-3 : Conversion factors used to derive forest inventory data for deciduous and coniferous forests in Belgium (METAGE report, 2006)

Species	Wood density (t.m ⁻³)				Carbon content (t.t ⁻¹)			
	Min	Max	Med	#	Min	Max	Med	#
Spruce	0.34	0.45	0.38	15	0.40	0.51	0.50	5
Pines	0.39	0.60	0.48	13	0.40	0.55	0.50	9
Douglas fir	0.37	0.54	0.45	7	0.50	0.50	0.50	1
Larch	0.41	0.55	0.47	8	0.40	0.50	0.50	3
Other resinous	0.35	0.50	0.40	20	0.40	0.50	0.50	7
Beech	0.55	0.72	0.56	11	0.44	0.51	0.49	10
Oaks	0.50	0.72	0.60	9	0.45	0.50	0.50	3
« Nobles » species	0.52	0.69	0.59	9	0.50	0.50	0.50	1
Poplars	0.34	0.55	0.41	48	0.50	0.50	0.50	1
Other deciduous	0.38	0.77	0.55	34	0.45	0.50	0.50	6
Species	BEF 1 : Total aboveground biomass / Solid wood mass (t.t ⁻¹)				BEF 2 : Total below ground biomass / total above ground biomass (t.t ⁻¹)			
	Min	Max	Med	#	Min	Max	Med	#
Spruce	1.14	1.71	1.29	9	0.2	0.2	0.2	
Pines	1.14	1.40	1.32	5	0.16	0.16	0.16	1
Douglas fir	1.18	2.24	1.28	10	0.17	0.17	0.17	1
Larch	1.14	1.36	1.30	3	0.2	0.2	0.2	
Other resinous	1.14	1.71	1.33	5	0.18	0.25	0.20	3
Beech	1.16	2.04	1.34	9	0.23	0.25	0.24	2
Oaks	1.24	1.39	1.32	2	0.2	0.2	0.2	
« Nobles » species	1.29	1.29	1.29	1	0.2	0.2	0.2	
Poplars	1.4	1.4	1.4		0.2	0.2	0.2	
Other deciduous	1.24	1.40	1.32	2	0.20	0.22	0.21	2

The geographic distribution of the biomass organic carbon (BOC) stock in Belgian forests in 2000 is shown in Figure 7.2. The high BOC stocks of the broadleaf forest on loam soils in central Belgium are visible, as well as in the Walloon Ardennes. The low BOC stocks on the sand soils of Kempen, Sand Region and the coast region are visible as well.

Figure 7-3 gives the evolution of biomass carbon stock (BOC). For then 1990-2000 simulation, a working hypothesis of a linear trend in forest areas and overall biomass increase was made. A distinction was made between the main deciduous and coniferous species for estimating the annual wood growth. The annual wood harvest is estimated through a comparison of the estimated annual increase of the carbon stock (based on the annual wood growth) with the effective annual carbon stock variation observed in the inventories.

For the 2001-2003 period, a model simulating the evolution of the forest biomass, called EFOBEL which stands for 'Evolutions de la FORêt BELge' (Trends for Belgian Forest in English) was used (Laitat et al, 2005). EFOBEL is a dynamic .xls spreadsheet using 20 tables. The complete description is done in Perrin (2005). The inputs of the model refer to every grid cells of the Belgian Forest Inventories as published for the year 2000: the solid wood volume and the area of the stands, by species and by age classes. The parameters are the annual growth increment for each species, the revolution, the period between harvest and replanting (also called latency), and the percentage replacement of one species by another according policy rules under implementation by the respective forest administrations. The prediction of BOC result from various scenarios. The most probable

scenario is the continuation of the current forestry practices in a scenario "Sylviculture has usual". The parameters relating to such a scenario are obtained either by the inventories themselves, or by literature searches in reference works.

A comparison between the annual wood harvest calculates with the model EFOBEL and the result of forest statistic confirm the accuracy of the methodology.




Figure 7.2. Biomass organic carbon (BOC) stock (t C ha⁻¹) in forest in 2000 (Lettens et al, 2003)




Figure 7.3 : evolution of biomass carbon stock in belgian forest (Perrin 2005)

Belgium use two different methodologies : a linear interpolation for the 1990-2000 period and a mechanistic model for the 2001-2004 period. A significant overestimation of carbon sink in biomass are observed during 2001, 2002 and 2003, due to a underestimation of real harvest (link to the model assumption). After 2003, the model shows a stabilisation of the annual carbon net removals (1300 - 1500 Gg CO₂ per year). Belgian will improve the time-series consistency, using the result of a scientific study (Agricultural University of Gembloux) and the actualisation of the forest inventories and wood harvest statistics.

The table 7.4. represents the confidence interval (ci 95%) associated with the volume estimation. We combine the error due to the measurement techniques (diameter, height, number of trees per plot) and the error linked to the surface and volume estimation for the whole region (error dependent on the sampling plot number per species).

Table 7.4. confidence interval associated with the volume estimation per species (2000 forest inventories)

		Wallonia	Flanders
Spruce	<i>Picea excelsa</i>	2,20%	15,10%
Douglas fir	<i>Pseudotsuga menziesii</i>	13,20%	14,40%
Larches	<i>Larix</i> sp,	9,50%	15%
Pines	<i>Pinus</i> sp	6,80%	6,50%
Other resinous		7,50%	20,20%
Beech	<i>Fagus sylvatica</i>	4,70%	12%
Oaks	<i>Quecus robur</i> and <i>Q. petraea</i>	3%	12,40%
"Noble" broadleaves		4,20%	11,10%
Other broadleaves		5,20%	2,20%
Poplars		17,10%	11,70%

Solid stem wood volume was converted to carbon as described in the figure at the left with conversion factors preferably selected from COSTE21 publications (Table 7.2.).

A frequency distribution was established for the values used in neighbouring countries, assuming a normal distribution of the selected variable. The relative error could be derived from this frequency distribution. Consecutively a Monte Carlo analysis (10000 simulations) was applied to the calculation of the 2000 stock.

According our calculations, the carbon stock in the biomass averages 59.8 Mton in 2000, with a relative confidence interval (CI95%) on the mean of 10.3%.

B. Carbon in Deadwood and litter (forest only)

The definition of deadwood applied in the Inventory's methodology is all standing dead trees and fallen logs and branches. A dead tree is considered as fallen when it tilts at a vertical angle equal or superior to 45°. Veteran trees are taken into account in the living trees section.

The objectives of the collection of deadwood information consist in estimating the volume of standing dead trees and fallen logs and branches, contributing to the estimation of the carbon-stock in Wallonia's forests and estimating biodiversity indicators throughout the importance of deadwood.

The collecting method varies according to the type of deadwood.

Entire dead trees (snags) and broken dead trees (candles) are both taken into account by the Inventory. Trees of different sizes are taken into account in each circular plot according to the same rules as for living trees. This means that a standing dead tree is included in a circular plot according to its

circumference. Dead trees under 20 cm of circumference are not taken into account (threshold of the inventory).

Fallen logs and branches are taken into account in a circular plot for which the size varies depending on the average circumference (Coverage) of the living stand. If the unit is located in a clear cut, clearing or impenetrable stands for which no stand measurements are performed, downed deadwood is taken into account in the 9m plot. Logs of at least 1 m long and 20 cm circumference are considered by the Inventory and their volume is estimated by volume functions. Crown (logging residue) is also taken into account (as deadwood) if it is 3 years old. Logs and branches inferior to 20 cm circumference are taken into account by the Inventory and their volume is considered by visual estimation.

For the carbon in deadwood pool, the forestry practices evolve according two contradictory tendencies : increased harvest of the residues in the zones without important constraint of biological conservation (ie bioenergy) and more deadwood left in forest in the zones where dominating conservation of the biodiversity (zones Natura 2000, which represent more than 30% of forest area). We assume that the actual stock (1.38 Mt.C) remains constant.

For the carbon in litter pool, the default IPCC factors were used. The C stock in litter pool was estimated about 13.73 Mt.C. Despite the increase of above and below ground biomass, Belgium consider the stability of the C stock (conservative approach).

B. Soil organic carbon in agricultural and forest mineral soils

Methodology

The Belgian territory was divided into landscape units (LSU) by the topological intersection of the 1990 version of the Corine Land Cover (CLC) geo-dataset (European Commission 1993) and the digitized Soil Association map of Tavernier et al. (1972). The CLC geo-dataset has been produced by manual digitization of printed LANDSAT-images, taking into account a minimal mapping unit of 25 hectares. The 34 of the 44 possible classes of the original legend that occur in Belgium were aggregated into the 11 broader classes: (i) cropland, (ii) grassland (both permanent and temporary), (iii) broadleaf forest, (iv) coniferous forest, (v) mixed forest, (vi) fallow land, (vii) heath land, (viii) inland marshes, poplar in pasture, rush and reed vegetation, (ix) clay pits, mineral extraction sites and excavated soils, (x) peat bogs, (xi) not specified. The Soil Association map (1:500,000) represents broad zones with similar topsoil texture and drainage conditions in 64 soil associations. The overlay of both geo-datasets resulted in 567 landscape units (LSU), each characterized by one soil association and one land use class, scattered over 101,376 polygons.

Due to the generalised nature of the CLC geo-dataset and the Soil Association map, LSUs are pseudo-homogeneous with respect to soil and land use composition. This is especially true in highly fragmented landscapes, as those present in major parts of Belgium, and is illustrated by the fact that according to CLC, there is 1,782,028 ha of arable and grassland in Belgium while official net land use statistics show 1,400,300 ha (NIS, 2000). Moreover, a CLC compatible geo-dataset for 1960 and 2000 is not available. Therefore, LSUs derived from CLC-1990 are used for 1960 and 2000 as well. Hence, spatially explicit land use changes between 1960, 1990 and 2000 are not accounted for and no data can be generated on the effect of land use change on SOC stocks as derived from multi-temporal assessments. This assumption of absent land use changes may be fairly realistic with regard to the overall delineation of the LSUs. The total agricultural area for example, increased by less than 3% between 1990 and 2000, as indicated by agricultural statistics (NIS, 1990). However, the increase of within-LSU heterogeneity of land use, e.g. the obvious growth of rural residential areas, mostly at the expense of agricultural land fragments, is disregarded.

The methodology uses the stock change method for estimating CO₂ fluxes from the LSUs i.e. soil organic carbon (SOC) stocks of different years are compared. It is assumed that the per-LSU and total CO₂ flux is equal to the observed change in SOC stock in CO₂ equivalents over a certain time span and that the per-LSU-fluxes can be aggregated to yield total fluxes at regional or national levels. SOC stocks for LSUs are computed for the years 1960, 1990 and 2000. The SOC estimations are based on a number of heterogeneous databases and modelling efforts. Three cases can be distinguished when computing per-LSU SOC values.

When elementary point measurements are available, they are attributed to the LSU in a process called matching (Van Orshoven et al., 1993). Through matching, points are attributed to the LSU either based upon their location within the boundaries of the LSU (“geomatching”) or based upon corresponding soil and land use characteristics as the LSU (“classmatching”). Classmatching may be completely independent of the point’s location. In our approach classmatching was restrained by a stratification by soil association.

With regard to agriculture, a number of data sources provide an average SOC-percentage per municipality or other type of administrative unit. These data can be considered to be indirectly geo-referenced to the administrative units, functioning as alternative LSUs (further termed ALSU) that do not correspond spatially with the LSUs to which we want to attribute the data. Therefore, the measurements are first disaggregated to the intersection of the ALSU and the LSU and then re-aggregated to the LSU.

For LSUs for which no measurements are available, the stocks can be estimated using a mechanistic model (YASSO for forest soils, ROTH C for agricultural soils). This has been done for the 1990-stocks of forested LSUs.

Result

Due to the absence of forests in the 1990 assessment, the SOC content of only 130 agricultural LSU can be compared between the years 1990 and 2000 by means of a pair-wise comparison. The SOC stock in the 0-20 cm layer of 87 LSUs (74% of the total agricultural area) decreased between 1990 and 2000. For 25 (48% of the total agricultural area) of these LSU, the decrease is significant at the 95% confidence level. Those LSUs are mostly under cropland and all of them occur in northern or central Belgium. Most of the remaining 43 LSUs (26%) with increased SOC content are situated in southern or central Belgium. Also the 1 LSU (3%) that shows a significant increase of SOC content is located in southern Belgium.

On average, the SOC content of both the land use type grassland and cropland decreased significantly between 1990 and 2000. Grassland SOC decreased from 64 t C ha⁻¹ in 1990 to 60 t C ha⁻¹ in 2000 (0-20 cm). Cropland soils stored 38 t C ha⁻¹ in 1990 and 36 t C ha⁻¹ in 2000. If only the soil associations are considered, 39 of the 65 associations have lost SOC between 1990 and 2000. They are situated in the coastal zone and in northern and central Belgium. The 16 associations with a significant decrease in SOC are restricted to northern and central Belgium. The 4 associations with a significant increase in SOC are all situated in southern Belgium.

Finally, the total SOC stock in agricultural land was compared between 1990 and 2000. In 1990 this stock amounted to 178 Mt C in the upper 100 cm and for 2000 it decreased to 169 Mt C. This decrease is significant at the 95% confidence level (Figure 7.4.).




Figure 7.4. : Average SOC content and 95% confidence intervals (t C ha⁻¹) for 0-20 cm for the land use types broadleaf forest, coniferous forest, mixed forest, grassland and cropland for 1960, 1990 and 2000 (Lettenens et al, 2003)




Figure 7.5 : SOC change of landscape units in Belgium between 1960 and 2000 in the upper 20 cm of mineral soil. Hatched areas represent non-significant changes (Lettenens et al, 2003)

D. Land-use change

Agricultural land occupies the largest part of the national territory (Table 7.5). Its total area has declined since 1990 (-4.7%), while built-up areas grew nearly 18% during the same period. Forests occupy nearly 20% of the national territory, down slightly from 1990 (-0.6%). For the time being, Belgium considered a negligible impact of land-use changes on carbon stock.

Table 7.5. Land use – relative figures (% of total surface area, 2005) and evolution (1990-2005)

Land-use	% total area	Evolution 1990-2005
Total agricultural land ⁽¹⁾	57,1%	-4,7%
Forest and woodlands	19,9%	-0,6%
Built-up and related areas ⁽²⁾	19,2%	17,8%
Miscellaneous ⁽³⁾	3,0%	1,4%
Water ⁽⁴⁾	0,8%	0,0%

(1) including idle land

(2) except for scattered farm buildings

(3) fens, heaths, marshes, waste ground, rocks, beaches, dunes

(4) OECD estimate

Source: I.N.S. and Ministry of Finance (land register). I.N.S. calculations based on OECD/Eurostat definitions

7.3. Recalculations and planned improvement

7.3.1. Recalculations

For the first time, all categories are covered.

7.3.2. Planned improvements

Regarding the category "forest land remaining forest land", Belgium will improve the time-series consistency. The result of scientific study and a update of forest inventory will be available by the end of 2006.

The present estimation of land-use change should be considered as a rough calculation. An important scientific and administrative work is scheduled within the two next years to improve the consistency of land-use definition and methodology and to monitor the land-use changes.

CHAPTER 8: WASTE

8.1. Overview

8.1.1. Description of the sector

The production of waste arising from the residential sector and from commercial activities ('municipal waste') amounted to 535 kg per inhabitant in 1999, 52% of which was not recycled. Manufacturing industry is the largest source of waste (13.8 Mt). The three regions have implemented waste management plans.

The objectives and actions of the Flemish region for waste are defined in the report *MiNa [Flemish Environmental Policy Plan 2003-2007]*. For further information the website www.ovam.be of the institute responsible for waste management in Flanders (OVAM) can be consulted.

The *Wallonia waste plan 'Horizon 2010'*, adopted in 1998, contains a series of 70 actions targeted on the prevention, the recycling and the recovery of energy, and the elimination of waste. The *Waste Prevention and Management Plan in Brussels-Capital Region 2003-2007* also subscribes to this double strategy of waste prevention and recovery.

In addition, a body (FOST Plus) has been created by the private sector to finance, co-ordinate and promote the selective collection, the sorting and recycling of household packaging waste. FOST Plus was created to enable industry to respond in a global and concrete way to the legislation on packaging and, more specifically, to the introduction of European Directive 94/62/EC of 20/12/1994, and the Co-operation Agreement between the Regions of March 1997 relating to the prevention and management of waste from household packaging. The recovery of used materials is becoming a major industry in Belgium and creates plenty of employment. The industries most intensive in manpower are textile recycling, the recycling of paper and of construction materials.

8.1.2. Allocation of emissions

The waste emission inventory in Belgium covers categories 6.A, 6.B, 6.C and 6.D.

Category 6.A.1. contains the emissions of CH₄ originating from the solid waste disposal sites in Belgium. No waste disposal sites are located in the Brussels region in Belgium.

The industrial wastewater (category 6.B.1) is not considered because a lack of data. Only domestic wastewater emissions are calculated in Belgium for the time being (category 6.B.2).

CH₄ emissions originating from the production of compost is put under category 6.D Waste/Other.

The waste incineration category (category 6.C) includes incineration of municipal wastes, incineration of hospital wastes and the incineration of corpses. Emissions originating from flaring activities are allocated partly to the sector 2.B.5. (Flemish region, see section 4.2.2.3 for further information) and partly to the sector 6.C (Walloon region).

In Brussels only category 6.B (municipal wastewater treatment plant since half 2000) and 6.C (waste incineration) are relevant in this waste section. About the incineration, the municipal waste incineration occurs with energy recuperation and is allocated under 1.A.1.

8.2. Methodological issues

8.2.1. Solid waste disposal on land

Flemish region

CH₄ emissions from solid waste disposal on Land (category 6.A.1) were studied by the Vito [1] in 1994 [8]. The data available for Flanders are specific and accurate, what allows a more refined methodology than the one proposed in the IPCC Guidelines.

Since 1994 waste policies in Flanders (cfr. Ladder of Lansinck which prefers waste burning over waste dumping) have made some results. The amount of waste of households dumped decreased since 1994 and from 1998 on, more waste is burned than dumped. A real moratorium in dumping organic waste is set up since 2000.

The methodology used to calculate the emissions from solid waste disposal on land differs between the 2 regions in Belgium where these sites are located (Flanders and Wallonia).


In the Flemish region a combination of 2 models is used: a multiphase model for the estimation of emissions of the sites which are permitted and a first order decay model for all other, old waste disposal sites which are no longer permitted to dispose but where still emissions occur after the ban of disposal on these sites (these are the solid waste disposal sites in after-care).

In the course of 2005 all data used in the models and originating from the OVAM (public waste agency in the Flemish region) are checked with the responsible people of OVAM and optimized if necessary.

A short presentation of the 2 models is given below:

1) The first order decay model takes into account residential and industrial waste. Data for these sites are available from 1981 on. It has been assumed that the ratio of waste landfilled to waste produced in the period 1970 to 1980 is the same as for the year 1981. An assumption is made that the waste decomposes during a period of 25 years. With respect to the waste composition a biodegradable fraction of 18% is assumed, conform to studies carried out in the Netherlands [46]. In an other study conducted in the Netherlands [47] methane emissions at 3 landfills sites have been measured and a mean degradation coefficient of k of 0,1/year calculated. An active lifetime is assumed of 25 years for the Flemish landfills, including an aerobic period of 1 year and an anaerobic period of 24 years. The formula used to calculate the emissions of methane in solid waste disposal sites is:

$S_t = a \cdot Q_i \cdot B_o \cdot k \cdot \exp(-kt)$ (first order kinetic approach of waste gas production S on time t after disposal) based on biodegradation of C₆H₁₀O₄



With a = conversion 1m³ waste gas originates from 1 kg organic waste (based on the reaction above)

S_t = waste gas production on time t after disposal (in m³)

Q_i = the amount of disposed biodegradable waste on time t=0 (in ton)

B_o = the initial concentration of biodegradable material in the disposed waste (in kg/ton)

k = the first order velocity constant of biodegradation (in year⁻¹)

The biogas contains 55% of methane (see reaction of Parken & Owen) and an oxidation of methane of 10% in the upper layer is assumed.

2) The multiphase model treats 15 solid waste disposal sites (category II) which are permitted in Flanders and contains mainly domestic waste. This domestic waste is divided into residential, rough and urban waste. Because a different interpretation of different local authorities, urban waste is supposed to be similar to domestic waste.

This model uses velocities of gasproduction that are more accurate compared to first order models. The model assumes that the gasproduction starts 1 year after disposal and goes immediately to a maximum.

The following biodegradation rates are used:

Quick biodegradation: $k_1=0.173$ ($t_{1/2}=4$)

Average biodegradation: $k_2=0.069$ ($t_{1/2}=10$)

Slow biodegradation : $k_3 = 0.023$ ($t_{1/2} = 30$)

The amounts of organic matter for different kinds of waste categories originates from literature.

The biodegradable fractions of rough waste on the solid waste disposal sites are:

paper and carton: 3%

trim wood (from gardening): 10%

wood (construction & demolition, furniture): 20%

textile: 6%

The amount of organic C in each phase of biodegradation rate of domestic waste (dw) and rough waste (rw) are presented in table 8.1.

Biodegradation rate	W_{dw} (...-1990)	W_{dw} (1991-...)	W_{rw}	d	o	c
quick	0.44	0.49	0.00	0.44	0.51	0.45
average	0.24	0.17	0.13	0.70	0.85	0.45
slow	0.09	0.10	0.26	0.77	0.73	0.45

Tabel 8.1: Characteristics for the determination of the fraction of organic carbon in each phase of biodegradation rate of domestic waste (dw) and rough waste (rw).

The calculation of organic carbon in the category II industrial waste uses other w-values. Following characteristics could be defined:

Process waste: 36%

Non-process waste: 36%

Recycled residues: 3%

Sludge: 9%

Medical waste: 1%

Inert rest: 15%

Biodegradation rate	C_{iw}	W_{iw}
quick	$c_{0,1} = 49$ kg/ton	0.52
average	$c_{0,2} = 8$ kg/ton	0.03
slow	$c_{0,3} = 18$ kg/ton	0.05

Tabel 8.2: Characteristics for the determination of the fraction of organic carbon in each phase of biodegradation rate of industrial waste (iw)

The fraction of biodegradable material is assumed to be 77%.

The biogas contains 50% of methane and an oxidation of methane of 10% in the upper layer is assumed.

The production of waste gas Q_g in the year t (in m^3 /year) is calculated as:

$$Q_g = \zeta a \left[\sum_{j=0}^m \sum_{i=1}^n A_j k_i C_{o,i,j} e^{-k_i(t-j)} \right]_{domesticwaste} + \zeta a \left[\sum_{j=0}^m \sum_{i=1}^n A_j k_i C_{o,i,j} e^{-k_i(t-j)} \right]_{roughwaste} + \zeta a \left[\sum_{j=0}^m \sum_{i=1}^n A_j k_i C_{o,i,j} e^{-k_i(t-j)} \right]_{industry}$$

with a the factor to transfer the amount of carbon to the amount of waste gas (1,87 m^3 /kg C)

with A_j the amount of waste disposed in year i (in ton/year)

with the biodegradation rate k_i of each phase of biodegradation rate (in 1/year) with the total amount of phases = 3 (quick, average and slow)

with $C_{o,i,j}$ the amount of organic carbon in each phase

with ζ a formation factor for the reduction of waste gas in some parts of the disposal site (because of local unfavourable conditions of micro-organisms. This factor corrects for uncertainties such as level of humidity, pH, temperature, ... and indicates how much gas is really formed. In practice this factor is assumed to be more or less 0,6.

The **recoverable amount of waste gas** Q_r is determined by the recovering efficiency η :

$$Q_r(t) = \eta Q_g(t) \quad (8)$$

The recovering efficiency η is determined by the ratio of the disposed volume out of which the waste gas is recovered effectively and the total disposed volume and can be improved by an extension of the amount of sources and/or the placement of impenetrable over- or undercovering.

Walloon region

The CO_2 and CH_4 emissions from solid waste disposal on land are calculated with a model that considers separately the emissions of industrial and municipal waste. The model, developed by the Vito [24], acknowledges the fact that methane is emitted over a long period of time. We use a first order decay model to take into account the various factors that influence the rate and extent of methane generation and release from landfill.

The model calculates the biogas emissions using the following relation :

$$S_{p,Y} = Q_Y * DOC * k * C * \exp^{-k * \Delta t}$$

$S_{p,Y}$ = biogas generation rate at year P (m^3)

Q_Y = the quantity of waste disposed year Y (Ton)

DOC = initial degradable organic carbon (kg/Ton)

k = biodegradation rate constant (% / year)

C = % of DOC really degraded (%)

Δt = the time since initial disposal (Y-P) (year)

In order to estimate the current biogas emissions from waste placed in all years, the equation is solved for all values of Q_Y and the results summed. The methane production is then calculated taking into account the biogas composition and an oxidation factor of 10% in the upper layer. The overall methodology follows the Tier 2 IPCC methodology (equation 5.1, IPCC Good Practice Guidance [10]). The constant used for household and industrial waste are presented in the table 8.1.

Constant	Municipal waste	Industrial waste
DOC(x) (in kg C/tonne waste)	180 (before 1986) 170 (1986-1990) 142,9 (1995) 112,5 (2000)	26,8 (1970-1995) 23,6 (2000)
K	10	10
DOCf	77	77

Table 8.3. : Solid waste disposal on land. Constant used in the model in Wallonia. For DOC, linear interpolation is used to estimate the intermediate values.

The model assumes that :

- the waste decompose during 25 years
- there is a aerobic period of 1 year where there is no methane production
- the landfill gas contain 55 % of CH₄ and 45 % of CO₂
- there is a CH₄ oxidation in the upper layer (10 %)
- the DOC reduction reflects the increased sorting of municipal waste

The model provides, for each year, estimation for the range of CH₄ and CO₂ production. The biogas CO₂ emissions are not reported in the CRF tables 6.A as it is from biogenic source.

The CH₄ recovered is subtracted from total emissions. This CH₄ is assumed to be completely converted into CO₂ through the combustion process. In previous submissions, this CO₂ emission was reported in this submission and included in national totals (see also section 8.3.3, planned improvements). The CO₂ produced by the biogas recovery is not reported anymore in the CRF tables 6.A, according to footnote 4 on page 5.10 of the IPCC Good Practice Guidance [10].

CH₄ recovery started in 1993 and largely increased since that year, by gradually equipping more and more disposal sites . It is the main driver for the reduction of the net emissions in this sector.

In Wallonia, the quantity of waste disposed comes from the statistics of OWD (Walloon Waste Office). It publishes each year the industrial and municipal waste disposed, based on the taxes declaration forms covering 50 solid waste disposal sites of various sizes. The data are classified according to 12 main categories (119 subcategories), thus allowing an accurate calculation of the amounts of waste and its degradable organic carbon content (IPCC Good Practice Guidance [10] equation 5.4, page 5.9), which are used as an input in the model. Those statistics are available on a yearly basis since 1994. The calculation involves large excel spread sheets which cannot be reproduced in the NIR. For the years before, the amounts have been estimated using available data and OWD expert judgement assumptions. The evolution of the ratio of biogenic waste in the waste incineration sector reflects the implementation of the Wallonia Waste Plan, as the "green waste" are increasingly sorted by the citizens and collected for compost production, thus decreasing the ratio of biogenic waste deposited in solid waste disposal sites.

The DOC value for municipal waste lies in the default value range from IPCC revised 1996 Guidelines and was chosen according to national expert judgement. The value for industrial waste was estimated calculated using the detailed waste types from OWD and the IPCC Good Practice Guidance methodology (equation 5.4, page 5.9). This detailed estimation led to a complete recalculation, as the new estimated DOC were much lower than the default value previously used.

The biodegradation rate constant and the rate of DOC really degraded also come from the revised 1996 IPCC Guidelines and the IPCC Good Practice Guidance [10]. The new default value of 0,5-0,6 for DOC_f , proposed in the IPCC Good Practice Guidance if lignin is included in the DOC value, has been tested in the model. It leads to a major problem in the sense that from 2002 and on, the biogas recovery (measured in volume and CH_4 fraction, thus appearing to be reliable estimate) becomes larger than the emissions as estimated by the model. Consequently, the former default value of 0,77 has been deemed more suited to the Walloon context and kept in the model.

Each year, all the landfills with CH_4 recovery (12 in 2002) are contacted to collect data on the amount and CH_4 content of the biogas recovered (flaring or energy purposes). The CH_4 content is measured by landfill owners as it determines the possible use of the biogas (only "rich" biogas" is used in engines, the rest is flared). Following a 1997 legal decree, a contract with the ISSEP (Scientific Institute for Public Service in Wallonia) also organises a close following of the environmental impacts of the Solid Waste Disposal Sites on Air, Water and Health. Seven main sites are followed for the time being and the report includes biogas analysis. Details can be found on the website of DGRNE.

8.2.2. Wastewater treatment

In the category domestic and commercial wastewater (category 6.B.2), the CO_2 emissions from municipal wastewater treatment plant are not reported in Belgium because the carbon derives from biomass raw materials. In this category, two sources of methane emissions are taken into account, the municipal wastewater treatment plant and the septic tanks.

The methodology for the septic tanks is based on an article (Vasel, 1992) [32], which describes the characteristics and parameters of individual septic tanks. For the CH_4 emission factor, the IPCC default value of 0.6 kg CH_4 /kg BOD. Each habitant produce 60 g BOD/day, whose 60 % eventually settle (IPCC fraction that readily settle). It is considered that only 25 % of the BOD loading is anaerobically degraded ($60 \cdot 0.6 \cdot 0.25$), because the septic tanks are regularly emptied and that the sludge is then treated aerobically. The annual emission factor becomes 1,971 kg CH_4 /inhab*year ($60 \cdot 60\% \cdot 25\% \cdot 0,6 \text{kg} CH_4/\text{kg BOD}$). This is the emission factor used in the Walloon region. In the Flemish region the old factor of 1,5 kg CH_4 /inhab*year is still used during this submission. The CH_4 emissions are estimated by multiplying these emission factors by the number of inhabitants not connected with a municipal wastewater treatment plant.

In the Walloon region, after discussion with the regional responsible for municipal wastewater treatment plants, it appears that most of the plants are conducted aerobically. Those who use anaerobical digestion of the sludge recover the CH_4 for energy purpose. Consequently, no CH_4 emissions are accounted in this subcategory.

In the Brussels region, the municipal wastewater treatment plant is conducted aerobically; no CH_4 emissions are then estimated for this subcategory.

In the Flemish region the emissions of CH_4 of the municipal waste water treatment plants are estimated by using the methodology as described in the EMEP/CORINAIR guidebook [3]. An emission factor of 0,3 kg/inhab*year is used to calculate these emissions.

The N₂O emissions are estimated by using the methodology described in the IPCC Guidelines. The default values for N fraction in protein and N₂O emission factor are 16 % and 0.01 kg N-N₂O / kg protein. The figures of protein consumption originates from the FAO statistics. The population figures comes from the National Institute of Statistics.

8.2.3. Waste incineration

N₂O emissions from domestic waste incineration are calculated using activity data known from the individual companies involved combined with the emission factor of CITEPA [2], which is 60 g N₂O/ton waste. CH₄ emissions are not relevant here, as IPCC Good Practice Guidance [10] states on page 5.23: "Emissions of CH₄ are not likely to be significant because of the combustion conditions in incinerators (e.g. high temperatures and long residence time)".

For CO₂ emissions, each region applies its own methodology according to the available activity data (see below).

The emissions of CO₂ from the flaring in the chemical industry are reported in category 6.C according to the IPCC Guidelines (Wallonia region). Contrary to the previous submission the emissions of CO₂ from the flaring activities in the chemical industry in the Flemish region are allocated to the category 2.B.5. instead of category 6.C (as described in the IPCC Good Practice Guidance) because these emissions are also included in the surveys which are carried out in this region on a yearly basis by the chemical federation in cooperation with the Vito and because it's difficult to take out these emissions.

Flanders

In Flanders, only the fraction of organic-synthetic waste is taken into consideration (assuming that organic waste does not give any net CO₂ emissions). For the municipal waste, the institute responsible for waste management in Flanders (OVAM) is given the analysis of the different fractions in the waste. Based on this information, the amount of non-biogenic waste (excluding the inert fraction) is determined. The carbon emission factor is based on data from literature for the different fractions involved. For industrial waste, the amount of biogenic waste is considered to be the same as in municipal waste. The remaining amount is considered to be the non-biogenic part in which no inert fraction is present. For industrial waste, it is more difficult to determine the content of C and therefore the results of a study carried out by the Vito 'Debruyne en Van Rensbergen 'Greenhouse gas emissions from municipal and industrial wastes of October 1994' are used. This study gives a content of C of the industrial waste of 65,5 %.

Wallonia

In Wallonia, following a legal decree in 2000, the air emissions from waste incineration are measured by ISSEP and the results are validated by a Steering Committee . These results allow a crosscheck with the results of measurements directly transmitted by the incinerators to the environmental administration.

There is a distinction between the emission from municipal waste incineration and hospital waste incineration. The CO₂ emissions of municipal waste incineration are reported assuming that 68 % of the waste is composed of organic material. This is based on the average garbage composition in Wallonia and the use of IPCC equation on organic content of the various materials. The CO₂ emissions from hospital waste incineration are measured by the Walloon incinerators and are fully reported. Emissions from the incineration of corpses are calculated using the EMEP/CORINAIR emission factors and statistical data on the number of corpses.

Brussels

The emission factors for the incineration of hospital and municipal waste and corpses are estimated by measurements in situ in connection with EPA and EMEP/CORINAIR emission factors.

8.2.4. Others

CH₄ emissions from compost production are estimated using regional activity data combined with a default emission factor of 2,4 kg CH₄/ton compost. The previous emission factor of 20 kg CH₄/ton compost resulted in a large overestimation of these emissions. The emission factor of 2,4 kg CH₄/ton compost is used after consultation of our colleagues in the Netherlands who uses this factor as a result of measurements carried out. This monitoring program was carried out in the Netherlands and the Ministry as well as the waste sector were involved. The monitoring was not a random indication of emissions but was carried out over a longer period.

8.3. Recalculations and planned improvements

8.3.1. Recalculations

General

- In the category 6.D the emissions of the composting are recalculated for the complete time series by using a much lower emission factor 2,4 instead of 20 kg CH₄/ton compost. This lower emission factor is based on monitoring results carried out in the Netherlands.

Flanders

- Revised activity data in the waste incineration sector (category 6.C) for all years are used during this submission. This correction has a minor impact on the emissions in this sector.
- Minor corrections are carried out in the emissions of CH₄ of the solid waste disposal sites for the years from 2001 on (category 6.A). A revision of the activity data (amount of disposed waste) took also place during this submission.
- Some minor corrections are made on the activity data used to calculate the emissions from waste water handling (category 6.B) to ensure data consistency concerning the number of inhabitants and in the same sector the methodology to calculate the emissions of N₂O from human sewage has undergone a revision.
- In category 6.C the activity data for 2002 of production of compost are actualized during this submission.

Wallonia

- It has been noticed during the 2005 submission that, due to a small bug in the Reporter software (Reporter is an interface developed by the European Environment Agency which is used to fill in the CRF tables from the Collector database), the emissions from hospital waste were previously not reported in the CRF tables. This causes a small change in the emissions of waste incineration from 1997 to present.
- The EF for waste water handling (septic tanks) has been revised according to IPCC Good Practice Guidance. The CH₄ emissions from municipal treatment plants have been revised according to updated information on the aerobic type of plants used.

8.3.2. Planned improvements

Belgium

- CH₄ recovery in the wastewater treatment plant has not been estimated for the time being because lack of data. It will be tried to collect those data for a future submission.
- The CO₂ emissions from biomass should be reported under "memo items" in the CRF tables. The effective reporting of these emissions has to be checked for the time series.

Wallonia

According to the IPCC Good Practice Guidance [10], (page 5.10), , the recovered emissions of CH₄ in solid waste disposal should be subtracted from the amount generated before applying the oxidation factor. This is not the case for the time

CHAPTER 9: RECALCULATIONS AND PLANNED IMPROVEMENTS

9.1. Recalculations and achieved improvements

The sector specific recalculations and methodological improvements achieved since the last submission are presented in the respective chapters of this report. This chapter presents the general issues that have been addressed since the last submission.

The efficiency of the institutional arrangements for the preparation of the inventory still has been improved. A detailed planning for the co-ordinated preparation of the inventory allows the timely submission of the inventory at the European and international level. On the technical side, all the national sectoral tables have been fulfilled in this submission.

In all regions, the emissions were completely updated for the time series 1990-2003 and provisional emissions are calculated for 2004.

The results of the draft centralized review report of the 2005 greenhouse gas inventory submission of Belgium are taken into account as much as possible during this submission.

Most important recalculations (with a major impact on the total emissions) on the Belgian inventory were carried out during the previous submission.

The carbon emissions and removals by soils were included for the first time in this CRF submission.

9.2. Implication on emission levels and trends

No major implications on emission levels and trends of greenhouse gases in Belgium took place during this submission.

-

9.3. Planned improvements

- As explained in section 1.5, independent audits are realised in the 3 regions in Belgium. However, some identified gaps, such as the lack of human resources, have not been adjusted so far, despite the signals sent by the inventory agencies. Nevertheless, a National Climate Commission has been put in place and its permanent secretariat is likely to provide some help for the preparation of the UNFCCC reporting.
- A working group has been established in order to improve the consistency of the energy balances available at different levels (regional, national, Eurostat). Some main gaps have already been identified but their correction requires changes in the data collection system at different levels. This long-term work is still ongoing (see section 3.4).

REFERENCES

- [1] Vito Vlaamse Instelling voor Technologisch Onderzoek = Flemish Institute for Technological Research, Boeretang 200, B-2400 MOL (www.emis.vito.be).
- [2] CITEPA Centre Interprofessionnel Technique d'Etudes de la Pollution Atmosphérique, rue du Faubourg Poissonnière 10, F-75010 PARIS – Emission Inventory of CH₄ and N₂O in the European Community 10/10/1990.
- [3] Joint EMEP/CORINAIR Atmospheric emission inventory guidebook, second edition, prepared by the EMEP Task Force on Emission Inventories, edited by Stephen Richardson – September 1999.
- [4] TNO Institute of Environmental Sciences, P.O. Box 342, 7300 Apeldoorn.
- [5] Copert III, Computer Programme to calculate Emissions from Road Transport, European Environment Agency, Technical reports n°49 & 50, Leonidas Ntziachristos and Zissis Samaras ETC/AEM – November 2000.
- [6] Greenhouse gas emissions from agriculture and livestock management, W. Debruyne and J. Van Rensbergen, ENE.RA9408 Energy division – April 1994.
- [7] Inventarisatie van de N₂O emissies uit de landbouw in Vlaanderen 1990-2000, Pascal Boeckx en Oswald Van Cleemput, Faculteit Landbouwkundige en Toegepaste Biologische Wetenschappen, Universiteit Gent – Oktober 2001.
- [8] Greenhouse gas emissions from municipal and industrial wastes, W. Debruyne and J. Van Rensbergen ENE.RA9410 Energy division – October 1994.
- [9] TEMAT model : Onderzoeksopdracht "Milieu-impactbepaling van het ontwerp Mobiliteitsplan Vlaanderen d.m.v. strategische m.e.r" - Deelrapport 1: Conceptontwikkeling voor strategische milieueffectrapportage van mobiliteitsplannen (UA, september 2001).
- [10] IPCC Good Practice Guidance and Uncertainty Management in National Greenhouse Gas Inventories.
- [11] Bilans énergétiques de la Région de Bruxelles-Capitale ; 11 rapports finaux ; Institut Wallon ; 1990-2001.
- [12] Collecte des données sur les émissions atmosphériques liées à des consommations énergétiques en Région de Bruxelles-Capitale, rapport final ; Institut Wallon ; décembre 1997.
- [13] Recensement de la circulation, Ministère des Communications et de l'Infrastructure, 1990-2000.
- [14] Collecte des données sur les émissions atmosphériques liées au transport routier en Région de Bruxelles-Capitale, 6 rapports finaux ; Institut Wallon ; 1995-2000.
- [15] Ntziachristos L., Samaras Z, 2000. COPERT III, Computer programme to calculate Emissions from Road transport, Methodology and emissions factors. European Environment Agency, Technical report N°49.
- [16] Etude sectorielle des émissions atmosphériques spécifiques, Collecte des données liées aux émissions du secteur des imprimeries ; Aries ; Décembre 1997.
- [17] Etude sectorielle des émissions atmosphériques spécifiques, Collecte des données liées aux émissions du secteur des nettoyage à sec ; Aries ; Décembre 1997.
- [18] Etude sectorielle des émissions atmosphériques spécifiques, Collecte des données liées aux émissions du secteur des stations-services; Aries ; Décembre 1997.
- [19] Etude sectorielle des émissions atmosphériques spécifiques, Collecte des données liées aux émissions du secteur des incinérateurs; Aries ; Décembre 1997.

- [20] Etude sectorielle des émissions atmosphériques spécifiques, Collecte des données liées aux émissions du secteur des carrosseries ; Aries ; Décembre 1997.
- [21] DGTRE (2001), Bilan énergétique de la région wallonne 1999, rapport juillet 2001, réalisé par l'Institut Wallon.
- [22] Econotec (1997), Analyse prévisionnelle des émissions de gaz à effet de serre, CH₄, N₂O et CO₂ en Région wallonne à l'horizon 2000-2005, Etude réalisée pour le Ministère de la Région Wallonne, DGRNE, Namur.
- [23] Econotec (2001), Analyse prévisionnelle des émissions atmosphériques liées au secteur du transport en région wallonne. Etude réalisée pour le Ministère de la Région wallonne, DGRNE, Namur.
- [24] EMEP/CORINAIR Emission Inventory Guidebook - 3rd edition (2001), European Environment Agency.
- [25] FEDIEX (1990), Phone contact between the DGRNE and the Fedix (Fédération Belge des Industries Extractives).
- [26] INS-agriculture (2001), "Recensement agricole et horticole au 15 mai 1999", (2002) "Recensement agricole et horticole au 15 mai 2000", (2002)"Recensement agricole et horticole provisoire au 15 mai 2001", Ministère des affaires économiques, Institut national de statistiques.
- [27] INS-transport (2001), "parc des véhicules à moteur au 1^{er} août 1999", Ministère des affaires économiques, Institut national de statistiques.
- [28] IPCC (1996), revised 1996 IPCC Guidelines for National Greenhouse Gas inventories.
- [29] MCI (2000), Recensement de la circulation en 1999. N° 17. Ministère des communications et de l'infrastructure Août 2000.
- [30] Siterem (2001), "Estimation des émissions dans l'air de CH₄, NH₃ et N₂O par le secteur agricole en région wallonne". Rapport final demandé par le Ministère de la Région Wallonne, Direction Générale des Ressources Naturelles et de l'Environnement.
- [31] ULG (1998), Inventaire des émissions atmosphériques en Région Wallonne pour 1996 réalisé par l'Université de Liège.
- [32] Vasel J.L. (1992), La fosse septique. Les dispositifs d'épuration individuel, Tribune de l'eau, n°560/6-Nov.Déc.1992.
- [33] Perrin D. and al., Calculation on the impacts of forestation, afforestation and reforestation on the C-sequestration potential in Belgian forests ecosystems, Biotechnol. Agron. Soc. Environ. 2000 (4), 259-262.
- [34] Econotec (2000), Update of the emission inventory of ozone depleting substances, HFCs, PFCs and SF₆ for 1998 and 1999, Study carried out for the Vlaamse Milieu Maatschappij.
- [35] Econotec, Ecolas (1999), Développement d'une méthodologie d'inventaire des émissions des substances détruisant la couche d'ozone et des gaz à effet de serre HFC, PFC et SF₆, Etude réalisée pour le compte des Services Fédéraux des Affaires environnementales et de la Vlaamse Milieu Maatschappij.
- [36] IPPC (1999), Best Available Techniques Reference Document on the Production of Iron and Steel.
- [37] Centre Entreprise-Environnement, UCL, (2000), « analyse des déchets ménagers et de certains flux de déchets non ménagers à haut potentiel recyclable », rapport demandé par l' IBGE.

[38] Bilan énergétique de la Belgique-energiebalans België 1999 (comparaison entre le bilan du Ministère des Affaires Economiques et le bilan agrégé des bilans régionaux, pour le compte du Ministère des Affaires Economiques), November 2002.

[39] Econotec (1997), Inventaire 1996 des émissions atmosphériques en région wallonne, groupes 2, 5 et 6 de la nomenclature snap, Etude réalisée pour le Ministère de la Région Wallonne, DGRNE, Namur.

[40] S. Monni and S. Syri, (2001) Uncertainties in the finnish greenhouse gas emission inventory. VTT research notes 2209(www.vtt.fi/inf/pdf).

[41] K. Rypdal and L-C. Zhang (200) Uncertainties in the Norwegian greenhouse gas emission inventory. Report 2000/13 , Statistics Norway.

[42] Rypdal, K. and Winiwarter, W. (2001) Uncertainties in greenhouse gas inventories – evaluation, comparability and implications. Environmental Science and Policy, Vol 4. Issue, 2-3, pp 107-116.

[43] Theunis et al., Vlaamse koolstofbalans voor het niet-energetisch verbruik, Vito rapport 2003/IMS/R/185.

[44] Joint EMEP/CORINAIR Atmospheric emission inventory guidebook, third edition, prepared by the EMEP Task Force on Emission Inventories and Projections – September 2004.

[45] ECONOTEC, VITO (2006), Update of the emission inventory of ozone depleting substances, HFCs, PFCs and SF6 for 2004, Final report, study commissioned by the Federal Public Service of Public Health, Food Chain Safety and Environment – DG Environment.

[46] Van Amstel et al., Methane: the other greenhouse gas, RIVM Report 481507001, 58-59, 1993.

[47] Verschut et al., Broeikasgassen uit vuilstorts in Nederland, TNO Report 91-444, 1991.

[48] IBGE, « Le projet de plan de prévention et de gestion des déchets », septembre 1991

Note : Some National Inventory Reports from other Annex I Parties are referenced in this report. All these are downloaded on www.unfccc.int.

ANNEXES

Annex 1 : Key sources analysis

Level assessment

IPCC Source Categories ^a	Direct	Sector	Base Year	Current Year	Level	Cumulative
	Greenhouse Gas		Estimate (1990)	Estimate (2004)	Assessment (2004)	Total
			(Gg CO ₂ eq.)			
1.A.3.b. Road Transportation	CO2	energy	19270	25799	17,4%	17,4%
1.A.1.a. Public Electricity and Heat Production	CO2	energy	23420	23822	16,1%	33,6%
1.A.4.b. Residential	CO2	energy	20213	22802	15,4%	49,0%
1.A.2.a. Iron and Steel	CO2	energy	14213	10838	7,3%	56,3%
1.A.2.c. Chemicals	CO2	energy	6311	7847	5,3%	61,6%
1.A.2.f. Other (Manufacturing Industries and Construction)	CO2	energy	8069	7068	4,8%	66,4%
1.A.4.a. Commercial/Institutional	CO2	energy	4272	6124	4,1%	70,5%
1.A.1.b. Petroleum Refining	CO2	energy	4299	5111	3,5%	74,0%
4.A.1. Cattle	CH4	agriculture	4301	3665	2,5%	76,5%
2.B.2. Nitric Acid Production	N2O	industrial processes	3562	3118	2,1%	78,6%
2.A.1. Cement Production	CO2	industrial processes	2824	2837	1,9%	80,5%
1.A.2.e. Food Processing, Beverages and Tobacco	CO2	energy	2998	2431	1,6%	82,1%
1.A.4.c. Agriculture/Forestry/Fisheries	CO2	energy	2730	2318	1,6%	83,7%
2.A.2. Lime Production	CO2	industrial processes	2097	2228	1,5%	85,2%
4.D.1. Direct Soil Emissions	N2O	agriculture	2471	2166	1,5%	86,7%
2.C.1. Iron and Steel Production	CO2	industrial processes	1946	1652	1,1%	87,8%
4.B.8. Swine	CH4	agriculture	1432	1356	0,9%	88,7%
2.B.1. Ammonia Production	CO2	industrial processes	694	1265	0,9%	89,6%
2.F.1. Refrigeration and Air Conditioning Equipment	HFCs	industrial processes	74	1113	0,8%	90,3%
2.B.5. Other (Chemical Industry)	CO2	industrial processes	224	1069	0,7%	91,0%
4.D.3. Indirect Emissions	N2O	agriculture	1184	940	0,6%	91,7%
4.B.1. Cattle	CH4	agriculture	1131	932	0,6%	92,3%
1A.3. Transport	N2O	energy	352	829	0,6%	92,9%
1A.4. Other Sectors	N2O	energy	789	828	0,6%	93,4%
4.D.2. Animal Production (2)	N2O	agriculture	941	823	0,6%	94,0%
6.A. Solid Waste Disposal on Land	CH4	waste	2630	815	0,6%	94,5%
4.B.12. Solid Storage and Dry Lot	N2O	agriculture	897	807	0,5%	95,1%
1.A.2.d. Pulp, Paper and Print	CO2	energy	637	624	0,4%	95,5%
1.A.2.b. Non-Ferrous Metals	CO2	energy	624	547	0,4%	95,9%
2.A.7. Other (Mineral Products)	CO2	industrial processes	414	452	0,3%	96,2%
6.C. Waste Incineration	CO2	waste	337	440	0,3%	96,5%
1.A.1.c. Manufacture of Solid Fuels and Other Energy Industries	CO2	energy	2144	425	0,3%	96,8%
1.B.2.b. Natural Gas	CH4	energy	519	407	0,3%	97,0%
1.A.3.d. Navigation	CO2	energy	267	366	0,2%	97,3%
1A.1. Energy Industries	N2O	energy	209	343	0,2%	97,5%
2.G. Other (industrial processes)	CO2	industrial processes	416	316	0,2%	97,7%
2.E. Production of Halocarbons and SF6	PFCs	industrial processes	1753	306	0,2%	97,9%
2.B.5. Other (production of caprolactam)	N2O	industrial processes	372	278	0,2%	98,1%
6.B. Wastewater Handling	N2O	waste	270	267	0,2%	98,3%
1A.2. Manufacturing Industries and Construction	N2O	energy	388	259	0,2%	98,5%
3. Total Solvent and Other Product Use	N2O	solvent	246	250	0,2%	98,7%
4. G. Other	N2O	agriculture	237	224	0,2%	98,8%
2.F.2. Foam Blowing	HFCs	industrial processes	324	210	0,1%	98,9%
4.A.8. Swine	CH4	agriculture	211	200	0,1%	99,1%
1.A.3.e. Other Transportation	CO2	energy	196	154	0,1%	99,2%
1.B.2.c. Venting and Flaring (Fugitive Emissions from Fuels)	CO2	energy	84	145	0,1%	99,3%
2.F.4. Aerosols/ Metered Dose Inhalers	HFCs	industrial processes	35	137	0,1%	99,4%
1.A.3.c. Railways	CO2	energy	202	122	0,1%	99,5%
Total			143231	147073	99,5%	
^a LUCF is not included in this analysis						

Trend assessment

IPCC Source Categories ^a	Direct	Sector	Base Year	Current Year	Trend	Contribution	Cumulative
	Greenhouse		Estimate	Estimate			
	Gas		(1990)	(2004)	Assessment	to Trend	Total
			(Gg CO ₂ eq.)				
1.A.3.b. Road Transportation	CO2	energy	19270	25799	0,042	19,2%	19,2%
1.A.2.a. Iron and Steel	CO2	energy	14213	10838	0,024	11,0%	30,3%
1.A.4.b. Residential	CO2	energy	20213	22802	0,015	7,1%	37,3%
6.A. Solid Waste Disposal on Land	CH4	waste	2630	815	0,012	5,7%	43,1%
1.A.4.a. Commercial/Institutional	CO2	energy	4272	6124	0,012	5,5%	48,6%
1.A.1.c. Manufacture of Solid Fuels and Other Energy Industries	CO2	energy	2144	425	0,012	5,4%	54,0%
2.E. Production of Halocarbons and SF6	SF6	industrial processes	1559	0	0,011	4,9%	58,8%
2.E. Production of Halocarbons and SF6	PF6s	industrial processes	1753	306	0,010	4,5%	63,4%
1.A.2.c. Chemicals	CO2	energy	6311	7847	0,010	4,4%	67,8%
1.A.2.f. Other (Manufacturing Industries and Construction)	CO2	energy	8069	7068	0,007	3,4%	71,3%
2.F.1. Refrigeration and Air Conditioning Equipment	HFCs	industrial processes	74	1113	0,007	3,2%	74,4%
2.B.5. Other (Chemical Industry)	CO2	industrial processes	224	1069	0,006	2,6%	77,0%
1.A.1.b. Petroleum Refining	CO2	energy	4299	5111	0,005	2,3%	79,4%
4.A.1. Cattle	CH4	agriculture	4301	3665	0,005	2,2%	81,5%
1.A.2.e. Food Processing, Beverages and Tobacco	CO2	energy	2998	2431	0,004	1,9%	83,4%
2.B.1. Ammonia Production	CO2	industrial processes	694	1265	0,004	1,7%	85,1%
2.B.2. Nitric Acid Production	N2O	industrial processes	3562	3118	0,003	1,5%	86,6%
1A.3. Transport	N2O	energy	352	829	0,003	1,5%	88,1%
1.A.4.c. Agriculture/Forestry/Fisheries	CO2	energy	2730	2318	0,003	1,4%	89,5%
4.D.1. Direct Soil Emissions	N2O	agriculture	2471	2166	0,002	1,0%	90,5%
2.C.1. Iron and Steel Production	CO2	industrial processes	1946	1652	0,002	1,0%	91,5%
4.D.3. Indirect Emissions	N2O	agriculture	1184	940	0,002	0,8%	92,3%
4.B.1. Cattle	CH4	agriculture	1131	932	0,001	0,7%	93,0%
1A.2. Manufacturing Industries and Construction	N2O	energy	388	259	0,001	0,4%	93,4%
4.D.2. Animal Production (2)	N2O	agriculture	941	823	0,001	0,4%	93,8%
1A.1. Energy Industries	N2O	energy	209	343	0,001	0,4%	94,2%
2.F.2. Foam Blowing	HFCs	industrial processes	324	210	0,001	0,4%	94,6%
1.B.2.b. Natural Gas	CH4	energy	519	407	0,001	0,4%	95,0%
2.G. Other (industrial processes)	CO2	industrial processes	416	316	0,001	0,3%	95,3%
4.B.12. Solid Storage and Dry Lot	N2O	agriculture	897	807	0,001	0,3%	95,6%
2.F.4. Aerosols/ Metered Dose Inhalers	HFCs	industrial processes	35	137	0,001	0,3%	95,9%
2.A.2. Lime Production	CO2	industrial processes	2097	2228	0,001	0,3%	96,2%
2.B.5. Other (production of caprolactam)	N2O	industrial processes	372	278	0,001	0,3%	96,5%
6.C. Waste Incineration	CO2	waste	337	440	0,001	0,3%	96,8%
4.B.8. Swine	CH4	agriculture	1432	1356	0,001	0,3%	97,1%
1.A.3.d. Navigation	CO2	energy	267	366	0,001	0,3%	97,4%
1.A.2.b. Non-Ferrous Metals	CO2	energy	624	547	0,001	0,3%	97,7%
1.A.3.c. Railways	CO2	energy	202	122	0,001	0,3%	97,9%
1.A.5. Other (Fuel Combustion)	CO2	energy	166	94	0,000	0,2%	98,2%
1.A.1.a. Public Electricity and Heat Production	CO2	energy	23420	23822	0,000	0,2%	98,4%
1.B.2.c. Venting and Flaring (Fugitive Emissions from Fuels)	CO2	energy	84	145	0,000	0,2%	98,5%
1.A.3.e. Other Transportation	CO2	energy	196	154	0,000	0,1%	98,7%
6.D. Other (composting)	CH4	waste	7	47	0,000	0,1%	98,8%
1.A.4. Other Sectors	CH4	energy	129	92	0,000	0,1%	98,9%
2.F. Consumption of Halocarbons and SF6	SF6	industrial processes	103	66	0,000	0,1%	99,0%
1.A.3. Transport	CH4	energy	102	68	0,000	0,1%	99,2%
2.A.7. Other (Mineral Products)	CO2	industrial processes	414	452	0,000	0,1%	99,3%
2.A.1. Cement Production	CO2	industrial processes	2824	2837	0,000	0,1%	99,3%
1A.4. Other Sectors	N2O	energy	789	828	0,000	0,1%	99,4%
1.A.2.d. Pulp, Paper and Print	CO2	energy	637	624	0,000	0,1%	99,5%
Total			144334	146498	0,2	1,0	
^a LUCF is not included in this analysis							

Annex 2: GHG emission trends in the three Regions

Introductory note: Greenhouse gas emissions follow very different patterns in the three regions of Belgium (Flanders, Wallonia, Brussels-Capital), due to the different structure of the sectors, and to local circumstances. Emission trends of the main greenhouse gases and for the main sectors are for the three Regions presented in this annex.




Figure 1. GHG emissions 1990-2004 in the three regions (excl. LUCF).

Unit: Index point (base year emissions = 100).

Note: For the fluorinated gases, the base year is 1995; as the y-axis refers to the base year, the index value for the year 1990 is not necessarily 100.








Figure 2. GHG emissions : share of emissions between the three regions (2004).

Flanders



Wallonia



Brussels









Figure 3. Share of greenhouse gases in the three regions (2004), and changes compared to base year (1990 for CO₂, CH₄ and N₂O; 1995 for F gases) (in ktonne CO₂ eq. and in %).

Flanders



Wallonia



Brussels





Figure 4. GHG emissions : share of main sectors (2004) in the three regions & changes 1990-2004 (in %).